



**DEEP
TRACTION**

**PREMIUM
WIDE TRAC**

**ROAD
ROLLER**

TIRE SIZE	TUBE TYPE	ITEM CODE	TIRE WEIGHT	RIM WIDTH	TREAD DEPTH	MAX LOAD	SECTION WIDTH	DIAMETER
CARLISLE INDUSTRIAL DEEP TRACTION FORKLIFT TIRE								
5.70/5.00-8/8	TT	5542A1	11.5	4.5/3.0	9	2450	5.5	18.2
6.90/6.00-9/10	TT	554204	20.2	5.5/4.0	19	3665	6.9	21.9
6.50-10/10	TT	554263	26.3	5.00	20	4225	7.4	23.4
7.00-12/12	TT	554212	36.3	5.00	21	5995	7.8	27.4
8.25-15/12	TT	554231	58.7	6.50	23	8680	9.8	33.6
29X8-15/12	TT	554216	47.5	5.50	25	6870	7.5	29.2
CARLISLE PREMIUM WIDE TRAC FORKLIFT TIRE								
5.70/5.00-8/10	TT	54P2E7	15.5	4.5/3.0	17	2790	5.5	18.5
18X7-8/16	TT	54P255	23.0	4.33	21	4695	6.6	18.3
6.90/6.00-9/10	TT	54P204	28.6	5.5/4.0	32	3665	6.0	22.2
6.50-10/10	TT	54P263	37.6	5.00	32	4225	7.1	23.8
7.00-12/12	TT	54P212	51.1	5.00	32	5995	7.5	27.3
7.50-15/12	TT	54P269	61.0	6.00	22	5260	8.7	32.4
28X9-15/12	TT	54P2B5	52.2	7.00	18	6880	8.8	27.3
29X8-15/12	TT	54P216	57.0	5.50	32	6870	7.5	28.9
8.25-15/14	TT	54P2D5	84.3	6.50	24	9385	9.8	33.6
2.50-15/18	TT	54P2H2	67.8	7.50	24	10100	9.1	29.1
3.00-15/20	TT	54P2H3	118.2	8.00	26	14500	11.3	32.7
28X12-15/20	TT	54P262	82.0	9.75	24	10800	11.5	28.1
7.50-16/12	TT	54P2K8	56.4	6.00	22	8000	8.5	32.3
CARLISLE ROAD ROLLER FORKLIFT TIRE								
7.5-15/12	TT	58R252	45.5	6.0	N/A	5860	8.6	30.9
7.5-15/14	TT	58R2E1	45.5	6.0	N/A	6300	8.6	30.9
8.5/90-15K/6	TL	58R3A2	39.8	6.0	N/A	3900	8.6	30.9

APPROXIMATE EQUIVALENTS

43.3	-	1100	14.9	-	380
35.5	-	900	13.6	-	340
30.5	-	800	12.4	-	320
28.0	-	710	11.2	-	290
24.5	-	650	9.5	-	250
23.1	-	580	9.0	-	230

CONVENTIONAL COMPARABLE METRIC

14.9R28	380/85R28	20.8R38	520/85R38
16.9R28	420/85R28	18.4R42	480/80R42
14.9R30	380/85R30	20.8R42	520/85R42
16.9R30	420/90R30	18.4R42	480/80R42
14.9R34	380/85R34	20.8R42	520/85R42
18.4R34	480/85R34	NONE	420/80R46
18.4R38	480/80R38	18.4R46	480/80R46



TIRE SIZE	ITEM CODE	TIRE WEIGHT	RIM WIDTH	TREAD DEPTH	MAX LOAD	SECTION WIDTH	DIAMETER
-----------	-----------	-------------	-----------	-------------	----------	---------------	----------

TITAN HI-TRACTION LUG RADIAL R-1 WITH T99 STUBBLE GUARD COMPOUND

12.4R24	TL	122A8/B	4RD414GY	136	11	44	3300	13.3	46.1
14.9R24	TL	120A8/B	4RD434	148	13	47	3080	17.0	49.9
13.6R24	TL	128A8/B	4RD422	141	12	46	3200	14.3	48.3
12.4R28	TL	121A8/B	4RD412	136	11	44	3200	12.7	49.6
13.6R28/3*	TL	3*	48E324	194	12	50	3740	14.2	52.5
18.4R30	TL	143A8/B	4RD450	273	16	50	6000	19.4	61.7
24.5R32	TL	5*	48E599	568	21	59	12800	25.3	70.6
320/85R24	TL	142A8/B	4RDH14	148	13	47	5840	15.4	50.4
380/85R28	TL	133A8/B	48E438	206	13	50	4540	16.0	54.2
380/85R30	TL	135A8/B	48E430	220	13	50	4800	16.0	56.2
380/85R34	TL	137A8/B	48E435	232	13	52	5080	16.0	60.2
380/85R34	TL	148A8/B	48E79A	253	13	52	6950	16.0	60.2
380/90R46	TL	144A8/B	48EA32	311	13	50	6150	15.7	72.3
380/90R46	TL	149A8/B	48ED32	328	13	50	7150	15.7	72.3
380/90R46	TL	156A8/B	48EH32	259	13	50	8800	15.7	72.3
380/90R46	TL	168A8/B	48E032	409	13	50	12300	15.7	72.3
420/85R28	TL	139A8/B	48E448	259	15	52	5360	18.1	56.5
420/90R30	TL	142A8/B	48E479	255	15	56	5840	17.8	58.9
480/80R38	TL	149A8/B	48E477	348	16	53	8550	18.8	77.1
480/80R38	TL	152A8/B	48E677	361	16	53	7850	19.8	69.1
480/80R42	TL	151A8/B	48E442	379	16	53	7600	19.3	73.1
480/80R42	TL	154A8/B	48E542	366	16	53	8250	19.3	73.1
480/80R42	TL	162A8/B	48E842	397	16	53	10500	19.3	73.1
480/80R42	TL	166A8/B	48E942	411	16	53	11700	19.3	73.1
480/80R46	TL	155A8/B	48E447	386	16	53	8550	18.8	77.1
480/80R46	TL	158A8/B	48E547	388	16	53	9350	18.8	77.1
520/85R38	TL	148A8/B	48E489	425	18	55	6950	21.3	72.9
520/85R38	TL	158A8/B	48E689	453	18	55	9100	21.3	76.9
520/85R42	TL	157A8/B	48E452	485	18	55	9100	21.3	96.9
520/85R38	TL	158A8/B	48E689	453	18	55	9100	21.3	76.9
520/85R42	TL	157A8/B	48E452	485	18	55	9100	21.3	96.9

TITAN HIGH TRACTION LUG BIAS R-1

7-14/6	TL		48D665	26.0	6	33.0	990	6.7	27.5
7-16/6	TL		48D666	27.0	6	34.0	1100	7.3	29.3
8-16/6	TL		48D667	34.1	6	31.0	1360	8.0	30.5
8.3-24/6	TL		48D684	52.0	7	37.0	1360	8.3	39.1
9.5-16/6	TL		48D695	48.3	8	40.0	1390	9.5	33.3
9.5-20/6	TL		48D663	54.8	8	41.0	1650	9.2	37.7
9.5-24/6	TL		48D694	70.0	8	41.0	1870	9.5	41.2
11.2-24/4	TL		48D404	75.0	10	43.0	1650	11.8	43.6
11.2-24/6	TL		48D604	90.0	10	43.0	2090	11.8	43.6
11.2-24/8	TT		47D804	91.1	10	36.0	2540	11.8	43.6
11.2-24/8	TL		48D804	98.9	10	36.0	2540	11.8	43.6
11.2-28/4	TL		48D410	95.0	10	43.0	1760	11.8	47.6
12.4-24/4	TL		48D414	100.0	11	44.0	1870	13.0	46.7
12.4-24/6	TL		48D614	111.2	11	44.0	2400	13.0	46.7
12.4-24/8	TL		48D814	100.0	11	44.0	2830	13.0	46.7
12.4-28/4	TL		48D412	106.7	11	44.0	1980	13.0	49.8
12.4-28/6	TL		48D612	113.0	11	44.0	2540	13.0	49.8
12.4-28/8	TL		48Y812	119.8	11	44.0	3000	13.0	49.8
12.4-42/6	TT		47D619	156	11	32.0	3080	12	64

TIRE SIZE		ITEM CODE	TIRE WEIGHT	RIM WIDTH	TREAD DEPTH	MAX LOAD	SECTION WIDTH	DIAMETER
12.4-42/10	TL	48D019	188	11	44.0	4180	12	64
12.4-42/12	TL	48D119	180	11	48.0	4680	12	64
13.6-24/4	TL	48D422	128	12	46.0	2040	14	47.9
13.6-24/6	TL	48D622	123	12	46.0	2680	14	47.9
13.6-24/8	TL	48D822	137	12	46.0	3080	14	47.9
13.6-28/	TT	47D424	126	12	46.0	3080	14	51.9
13.6-28/4	TL	48D424	134	12	46.0	2200	14	51.9
13.6-28/6	TT	47D624	132	12	46.0	2830	14	51.9
13.6-28/6	TL	48D624	127	12	46.0	2830	14	51.9
13.6-28/10	TL	48D024	148	12	46.0	3740	14	51.9
14.9-24/4	TL	48D434	125	13	47.0	2200	15.4	50.4
14.9-24/6	TT	47D634	130	13	47.0	3000	15.4	50.4
14.9-24/6	TL	48D634	140	13	47.0	3000	15.4	50.4
14.9-24/8	TL	48D834	131	13	47.0	3520	15.4	50.4
14.9-28/6	TT	47D638	132	13	47.0	3200	15.4	54.1
14.9-28/6	TL	48D638	132	13	47.0	3200	15.7	54.1
14.9-28/10	TL	48D038	161	13	47.0	4180	15.7	54.1
14.9-30/10	TL	48D030	175	13	47.0	4300	15.7	56.1
15-38/6	TT	47D674	188	14	46.0	3520	15.9	62.7
15-38/8	TT	47D874	184	14	46.0	4080	15.9	62.7
16.9-24/6	TL	48D645	156	15	48.0	3420	17.8	53.0
16.9-24/8	TL	48D845	169	15	48.0	4080	17.8	53.0
16.9-26/6	TL	48D646	166	15	48.0	3520	17.7	55.0
16.9-26/10	TL	48D046	183	15	48.0	4540	17.7	55.0
16.9-28/6	TL	48D648	170	15	48.0	3640	17.8	57.0
16.9-28/8	TT	47D848	168	15	48.0	4300	17.8	57.0
16.9-28/10	TL	48D048	188	15	48.0	4680	17.8	57.0
16.9-30/6	TT	47D679	201	15	48.0	3740	17.8	59.0
16.9-30/6	TL	48D679	196	15	48.0	3740	17.8	59.0
16.9-30/8	TT	47D879	184	15	48.0	3740	17.8	59.0
16.9-34/6	TT	47D644	194	15	48.0	3960	17.8	63.0
16.9-34/8	TT	47D844	190	15	48.0	3740	17.8	63.0
16.9-38/6	TT	47D620	202	15	48.0	4180	17.8	67.0
16.9-38/8	TT	47D820	205	15	48.0	4940	17.8	67.0
18.4-16.1/8	TL	48D890	166	16	50.0	2910	17.8	44.7
18.4-26/6	TL	48D656	188	16	50.0	3960	186.6	57.7
18.4-26/10	TL	48D056	206	16	50.0	5200	19.4	57.7
18.4-26/12	TL	48D156	207	16	50.0	5840	19.4	57.7
18.4-30/6	TL	48D650	219	16	50.0	4180	19.4	61.7
18.4-30/8	TT	47D850	208	16	50.0	4800	19.4	61.7
18.4-30/10	TT	48D050	257	16	50.0	5520	19.4	61.7
18.4-34/6	TT	47D654	213	16	50.0	4400	19.4	65.7
18.4-34/8	TT	47D854	219	16	50.0	5080	19.4	65.7
18.4-34/10	TL	48D054	262	16	50.0	6000	19.4	65.7
18.4-38/6	TT	47D677	238	16	50.0	4680	19.4	69.7
18.4-38/8	TT	47D877	244	16	50.0	5360	19.4	69.7
18.4-38/10	TT	47D077	269	16	50.0	6400	19.4	69.7
20.8-34/8	TT	47D801	276	18	51.0	5840	21.7	68.9
20.8-38/8	TT	47D889	302	18	51.0	6150	21.7	72.9
23.1-26/8	TL	48D886	307	20	52.0	5680	24.1	64.3
23.1-26/10	TL	48D086	328	20	52.0	6400	24.1	64.3
23.1-26/12	TL	48D186	338	20	52.0	7150	24.1	64.3
23.1-26/14	TL	48D386	338	20	52.0	7850	24.1	TBA
23.1-26/16	TL	48D586	337	20	52.0	8800	24.1	57.7
23.1-34/8	TT	47D888	311	20	52.0	6400	24.1	72.3
24.5-32/10	TL	48D099	390	21	53.0	7850	25.5	72.2
24.5-32/12	TL	48D199	421	21	53.0	8800	25.5	72.2
24.5-32/14	TL	48D399	422	21	53.0	9650	25.5	72.2
30.5L-32/12	TL	48D196	517	27	54.0	9350	31.9	71.8
30.5L-32/16	TL	48D596	550	27	54.0	11000	31.9	71.8



HI POWER LUG R-1



FARM TRACTOR
R-1 BIAS



TIRE SIZE	ITEM CODE	TIRE WEIGHT	RIM WIDTH	MAX LOAD	SECTION WIDTH	DIAMETER
-----------	-----------	-------------	-----------	----------	---------------	----------

TITAN HI POWER LUG R-1

11.2-24/4	TT	473404	80	10	42	1650	11.6	43.5
11.2-24/4	TL	483404	88	10	42	1650	11.6	43.5
11.2-38/4	TT	473408	112	10	42	2090	11.6	57.5
11.2-38/4	TL	483408	119	10	42	2090	11.6	57.5
11.2-38/6	TL	483608	122	10	42	2540	11.6	TBA
12.4-38/4	TT	473418	140	11	44	2340	12.9	59.6
12.4-38/8	TL	483818	159	11	44	3520	12.9	59.6
12.4-38/12	TL	483118	176	11	44	4400	12.9	59.6
13.6-28/6	TT	473624	126	12	46	2830	14.1	51.6
13.6-38/6	TT	473628	153	12	46	3300	14.1	61.6
14.9-24/4	TT	473434	132	13	47	2200	15.1	49.8
14.9-24/4	TL	483434	146	13	47	2200	15.1	49.8
14.9-24/6	TT	473634	143	13	47	3000	15.1	49.8
14.9-24/6	TL	483634	153	13	47	3000	15.1	49.8
14.9-26/6	TT	473631	158	13	47	3080	15.1	51.8
14.9-26/10	TL	483031	188	13	47	4080	15.1	51.8
14.9-26/12	TL	483131	196	13	47	4400	15.1	51.8
14.9-28/6	TL	483638	133	13	47	3200	15.1	54.9
14.9-28/8	TL	483838	146	13	47	3740	15.1	54.9
14.9-28/10	TL	483038	161	13	47	4180	15.1	54.9
14.9-38/6/6	TT	473673	189	13	47	3740	15.1	63.8
15.5-38/6	TT	473674	183	12	46	3520	14.1	61.8
16.9-30/6	TT	473679	180	15	48	3740	17.6	58.5
18.4-28/6	TT	473658	181	16	50	4080	19.1	59.1
18.4-30/6	TT	473650	203	16	50	4180	19.1	61.1
18.4-34/6	TT	473654	213	16	50	4400	19.1	65.1
18.4-38/6	TT	473677	238	16	50	4680	19.1	69.1
18.4-38/8	TT	473877	244	16	50	5360	19.1	69.1
20.8-38/8	TT	473889	302	18	51	6150	21.6	72.2
23.1-26/10	TL	483086	339	20	52	6400	24.0	62.5
23.1-30/8	TT	473882	339	20	52	6000	24.0	66.5
23.1-30/10	TL	483082	367	20	52	6800	24.0	66.5

TITAN FARM TRACTOR R-1 BIAS

9.5-36/6	TT	470697	85	8	38	2270	9.7	52.7
11.2-34/4	TT	470402	96	10	42	1980	11.6	53.4
11.2-36/4	TT	470406	89	10	44	2040	11.2	55.4
12.4-36/6	TT	470616	129	11	44	2830	12.6	57.1
13.9-36/6	TT	470693	126	12	44	3200	14.2	58.7



**HI-FLOTATION RIB
IMPLIMENT I-1**



**TRACTION
IMPLEMENT I-3**

TIRE SIZE	ITEM CODE	TIRE WEIGHT	RIM WIDTH	MAX LOAD	SECTION WIDTH	DIAMETER
-----------	-----------	-------------	-----------	----------	---------------	----------

TITAN HI-FLOTATION RIB IMPLEMENT

26X12.00-12/4	TL	410361	28	8	12	1780	11.7	25.5
8.5L-14/6	TT	410289	24	6	11	1870	8.6	28.6
8.5L-14/6	TL	410389	27	6	11	1870	8.6	28.6
9.5L-14/6	TL	410398	27	7	11	1930	9.8	29.2
9.5L-14/8	TT	410299	26	7	11	2400	9.8	29.2
9.5L-14/8	TL	410399	29	7	11	2400	9.8	29.2
9.5L-15/8	TT	410244	30	7	11	2470	9.8	30.2
9.5L-15/8	TL	410344	34	7	11	2470	9.8	30.2
9.5L-15/12	TT	4102D7	37	7	11	3200	9.8	30.2
11L-14/6	TL	410364	31	8	11	2040	10.7	30.0
11L-15/8	TT	410218	35	8	11	2540	10.8	31.0
11L-15/8	TL	410318	37	8	11	2540	10.8	31.0
11L-15/10	TL	410319	43	8	11	2910	10.8	31.0
11L-15/12	TL	410317	50	8	11	3200	10.8	31.0
11L-15*/18	TL	41L315	56	8	11	4180	10.8	31.0
11L-16/8	TT	410222	39	8	11	2680	10.7	32.0
12.5L-15/8	TL	410340	46	8	11	3000	10.7	32.1
12.5L-15/10	TT	410241	46	10	11	3420	12.1	32.1
12.5L-15/10	TL	410341	50	10	11	3420	12.1	32.1
12.5L-15/12	TL	410305	52	10	11	3860	12.1	32.1
12.5L-15/12*	TL	41L305	52	10	11	3860	12.1	32.1
12.5L-15/20*	TL	41L327	67	10	11	5080	12.1	32.1
12.5L-16/14	TT	410253	51	10	11	4180	11.9	31.9
12.5L-16/14*	TL	41L353	55	10	11	4180	11.9	31.9
14L-16.1/8	TL	410368	71	11	12	3860	14.8	37.4
14L-16.1/8*	TL	41L368	71	11	12	3860	14.8	37.4
14L-16.1/12	TT	410262	75	11	12	4680	14.8	37.4
16.5L-16.1/10	TL	410350	102	14	14	5200	17.1	40.9
16.5L-16.1/10*	TL	41L350	101	14	14	5200	17.1	40.9
16.5L-16.1/14	TL	4103L1	115	14	14	6400	17.1	40.9
19L-16.1/10	TL	4103H7	130	16	17	6000	19.1	43.6
19L-16.1/12	TL	4105H7	141	16	17	6600	19.1	43.6
21.5L-16.1/10	TL	410349	166	18	17	6600	21.4	45.0
21.5L-16.1/14	TL	4103J1	174	18	17	7850	21.4	45.0
21.5L-16.1/18	TL	4103Q4	180	18	17	8800	21.4	45.0

TITAN TRACTION IMPLEMENT I-3

7.50-20/4	TL	422303	36	5.5	17	1760	8.10	38.9
7.50-24/4	TL	422204	32	7	17	1870	8.70	38.9
13.50-16.1/6	TL	499505	81	11	23	3520	13.50	40.8



TITAN
INDUSTRIAL
CONTRACTOR F-3



AMERICAN FARMER
TIRE
FARM SPECIALIST
I-1 RIB IMPLEMENT

TIRE SIZE	TYPE	ITEM CODE	TIRE WEIGHT	RIM WIDTH	TREAD DEPTH	MAX LOAD	SECTION WIDTH	DIAMETER
-----------	------	-----------	-------------	-----------	-------------	----------	---------------	----------

TITAN INDUSTRIAL CONTRACTOR F-3

11L-15/8	TL	465318	50	8	15	2090	11.00	31.30
11L-15/10	TL	465310	52	8	15	2340	11.00	31.30
11L-16/10	TL	465315	55	8	15	2470	11.00	32.30
11L-16/12	TL	465317	60	8	15	2760	11.00	32.30
14.5/75-16.1/10	TL	465388	74	11	18	3200	13.70	35.50

AMERICAN FARMER MULTI RIB IMPLEMENT (I1) - TUBELESS

9.5L-14/8	TL	FC1A5	26	7.0	11	2400	9.7	29.6
11L-14/8	TL	FA3V5	29	8.0	11	2800	10.5	30.0
9.5L-15/6	TL	FC1C3	27	7.0	11	2320	9.7	30.5
9.5L-15/8	TL	FC1C5	27	7.0	11	2470	9.7	30.5
9.5L-15/12	TL	FA3C9	32	7.0	11	3200	9.7	30.5
11L-15/8	TL	FC1D5	30	8.0	10	2540	10.5	31.4
11L-15/10	TL	FC1D7	34	8.0	10	2910	10.5	31.4
11L-15/12	TL	FC1D9	37	8.0	10	3200	10.5	31.4
12.5L-15/8	TL	FC1E5	38	10.0	12	3000	12.2	33.0
12.5L-15/10	TL	FC1E7	40	10.0	12	3420	12.2	33.0
12.5L-15/12	TL	FC1E9	42	10.0	12	3860	12.2	33.0
12.5L-15/16*	TL	FC1ED	49	10.0	12	4200	12.2	33.0
12.5L-15/20	TL	FC1CT	52	10.0	12	4515	12.2	33.0
11L-16/8	TL	FC1F5	31	8.0	10	2680	10.2	31.4
12.5L-16/12	TL	FC1H9	45	10.0	12	3960	11.4	33.4
12.5L-16/14	TL	FC1HB	45	10.0	12	4180	11.4	33.4
9.00-10/4	TL	FC157	25	TBA	TBA	TBA	TBA	TBA
7.50-14/4*	TL	FB1Y1	18	5.5	10	1360	7.6	26.8
4.00-15/4	TL	FA3EA	10	3.0	6	785	4.0	23.5
5.00-15/4	TL	FA3J1	13	3.0	7	965	5.1	24.9
6.70-15/4	TL	FC1X1	19	4.5	8	1280	7.3	28.0
7.60-15/6	TL	FC113	22	5.5	10	1760	7.6	28.5
7.60-15/8	TL	FC115	22	5.5	10	2090	7.6	28.5
10.00-15/8	TL	FA395	41	8.0	13	3000	11.0	33.7
10.00-15/12	TL	FA399	48	8.0	13	3960	11.0	33.7
7.50-16/8*	TL	FA3N5	26	5.5	13	2200	7.9	29.9
7.50-20/10	TL	FA3BF	33	5.5	11	2600	7.6	35.0
20.5X8-10/8	TL	DE3M1	16	TBA	TBA	TBA	TBA	TBA
20.5X8-10/10	TL	DE3M2	17	TBA	TBA	TBA	TBA	TBA
20.5X8-10/10	TL	DE3M7	19	6.0	10	2275	8.2	20.2
26/12-12/4	TL	FA3DW	29	10.5	12	1550	12.0	26.2
26/12-12/12	TL	FA3DY	35	10.5	12	2750	12.0	26.2
14L-16.1/8	TL	FA3Z5	51	11.0	12	3860	13.7	37.0
14L-16.1/12	TL	FA3Z9	57	11.0	12	4680	13.7	37.0
16.5L-16.1/10	TL	FA337	80	14.0	15	5200	16.6	40.5
16.5L-16.1/14	TL	FA33B	88	14.0	15	6400	16.6	40.5
16.5L-16.1/16	TL	FA33D	95	14.0	15	7003	16.6	40.5
19L-16.1/10	TL	FA347	96	16.0	16	6000	19.0	42.4
21.5L-16.1/10	TL	FA3AB	107	18.0	18	6600	21.5	44.5
21.5L-16.1/14	TL	FA3AC	133	18.0	18	7850	21.5	44.5
31/13.50-15/8	TL	FB3BN	52	13.0	12	2760	13.5	32.4



**MULTI RIB
IMPLEMENT I-1**



**INDUSTRIAL
RIB F-3**

TIRE SIZE	TYPE	ITEM CODE	TIRE WEIGHT	RIM WIDTH	TREAD DEPTH	MAX LOAD	SECTION WIDTH	DIAMETER	
AMERICAN FARMER MULTI RIB IMPLEMENT (I1) - TUBE TYPE									
5.90-15/4	TT	FA3AH	15	4.50	9	1140	6.30	26.60	
6.40-15/4	TT	FA3BE	18	4.50	8	1170	6.40	26.90	
6.70-15/4	TT	FC1X2	16	4.50	8	1280	7.30	28.00	
6.70-15/6	TT	FC1X4	19	4.50	8	1610	7.30	28.00	
7.60-15/6	TT	FC114	19	5.50	10	1760	7.60	T28.50	
7.60-15/8	TT	FC116	20	5.50	10	2090	7.60	28.50	
6.00-16/6	TT	FA3L6	18	4.00	7	1520	6.10	28.50	
6.50-16/6	TT	FA3M4	18	4.50	11	1710	7.10	28.80	
7.50-16/8*	TT	FA3N6	23	5.50	14	2710	7.50	30.00	
9.00-16/10	TT	FA3AW	35	6.00	11	3300	9.20	33.40	
4.00-18/4	TT	FA3AX	10	3.00	6	880	4.40	26.40	
7.50-18/6	TT	FA3W4	21	5.50	10	2040	8.00	32.90	
4.00-19/4	TT	FA3AE	12	3.00	18	940	4.50	29.00	
7.50-20/6	TT	FA3AM	26	5.50	11	2410	7.60	35.00	
9.5L-14/8	TT	FC1A6	23	7.00	11	2400	9.70	29.60	
11L-14/8	TT	FA3V6	25	8.00	11	2800	10.50	30.00	
11L-14/10	TT	FA3V8	29	8.00	11	3170	10.50	30.00	
9.5L-15/8	TT	FC1C6	24	7.00	11	2470	9.70	30.50	
9.5L-15/10	TT	FC1C8	25	7.00	11	3180	9.70	30.50	
9.5L-15/12	TT	FC1CA	28	7.00	11	3280	9.70	30.50	
11L-15/8	TT	FC1D6	26	8.00	10	2540	10.50	31.40	
11L-15/12	TT	FC1DA	33	8.00	10	3200	10.50	31.40	
12.5L-15/10	TT	FC1E8	36	10.00	12	3420	12.20	33.00	
12.5L-15/14	TT	FC1EC	38	10.00	12	4060	12.20	33.00	
11L-16/8	TT	FC1F6	27	8.00	10	2680	10.20	31.40	
11L-16/12	TT	FC1FA	34	8.00	10	3850	10.20	31.40	
12.5L-16/12	TT	FC1HA	41	10.00	12	3960	11.40	33.40	
12.5L-16/14	TT	FC1HC	41	10.00	12	4180	11.40	33.40	
AMERICAN FARMER MULTI RIB IMPLEMENT (I1) - TUBELESS (HIGHWAY SPEED RATED)									
9.5L-15	TL	FA3DB	32	7.00	9	2670	9.70	30.50	
11L-15	TL	FA3DC	35	8.00	8	3120	10.50	31.40	
11L-15	TL	FA3D9	42	TBA	TBA	TBA	TBA	TBA	
12.5L-15	TL	FA3DE	48	10.00	11	3740	12.20	33.00	
12.5L-15	TL	FA3DF	51	10.00	11	4680	12.20	33.00	
AMERICAN FARMER INDUSTRIAL RIB (F3) - TUBE TYPE									
9.00-10/8	TT	FA956	22	6.00	11	1570	9.20	26.30	
9.00-10/10	TT	FA958	25	6.00	11	1820	9.20	26.30	
11L-15/10	TL	FA9D7	40	8.00	16	2340	11.00	31.80	
11L-15/14	TL	FA9DB	49	8.00	16	2710	11.00	31.80	
11L-16SL/10	TL	FA4F7	44	8.00	16	2470	11.00	33.00	
11L-16SL/14	TL	FA4FB	51	8.00	16	2930	11.00	33.00	
11.00-16/12	TL	FA9T9	68	10.00	15	3420	12.40	38.10	
14.5/75-16.1/10	TL	FA46W	67	11.00	16	3200	15.50	36.80	



**FLOATATION IMPLEMENT
DIAMOND TREAD I-2**



**TRACTION
IMPLEMENT I-3**



TURF TRACTION R-3



**FARM FRONT
F2M FOUR RIB**




TIRE SIZE	TYPE	ITEM CODE	TIRE WEIGHT	RIM WIDTH	TREAD DEPTH	MAX LOAD	SECTION WIDTH	DIAMETER	
AMERICAN FARMER FLOTATION DIAMOND TREAD IMPLEMENT (I-2)									
13.50-16.1/10	TL	FA327	78	11	19	4940	14.00	40.00	
13.50-16.1/12	TL	FA329	78	11	19	5200	14.00	40.00	
16.5L-16.1/6	TL	FA833	81	14	18	3960	16.40	42.25	
16.5L-16.1/10	TL	FA837	87	14	18	5200	16.40	42.25	
AMERICAN FARMER TRACTION IMPLEMENT I-3									
5.00-15/4	TL	FA5J1	16	3	15	965	5.60	25.20	
7.60-15/6	TL	FA5I3	27	5.5	17	1930	7.90	30.00	
12.5L-15/6	TL	FA5E3	46	10	20	2540	12.30	34.30	
12.5L-15/12	TL	FA5E9	56	10	20	3860	12.30	34.30	
16.5L-16.1/6	TL	FA533	104	14	23	3960	16.10	41.50	
16.5L-16.1/10	TL	FA537	109	14	23	5200	16.10	41.50	
21.5L-16.1/10	TL	FA5AB	149	18	33	6600	21.50	45.25	
21.5L-16.1/14	TL	FA5AC	173	18	33	7850	21.50	45.25	
AMERICAN FARMER TURF TRACTION (R3)									
21.5L-16.1/6	TL	FA7BK	147	18	30	2760	20.69	44.16	
21.5L-16.1/10	TL	FA7AB	157	18	30	3900	20.69	44.16	
AMERICAN FARMER FARM FRONT (F2M FOUR RIB)									
11L-15/8	TT	FA6D6	43	8	29	2090	10.90	31.80	
10.00-16/8	TT	FA6P6	48	8.8	28	2340	11.30	34.90	
11.00-16/8	TT	FA6T6	66	10	31	2600	12.00	37.60	
14L-16.1/6	TT	FA3Z4	68	11	32	2540	13.90	38.40	
11L-15/8	TL	FA6D5	48	8	29	2090	10.90	31.80	
10.00-16/8	TL	FA6P5	53	8	28	2340	11.30	34.90	
11.00-16/8	TL	FA6T5	72	10	31	2600	12.00	37.60	
14L-16.1/6	TL	FA3Z3	74	11	32	2540	13.90	38.40	
14L-16.1/11	TL	FA3Z7	81	11	32	3420	13.90	38.40	



FARM FRONT F-2
TRIPLE RIB



TRACTOR R-1



FARM FRONT F-1
SINGLE RIB

TIRE SIZE	TYPE	ITEM CODE	TIRE WEIGHT	RIM WIDTH	TREAD DEPTH	MAX LOAD	SECTION WIDTH	DIAMETER
-----------	------	-----------	-------------	-----------	-------------	----------	---------------	----------

AMERICAN FARMER FARM FRONT (F2 TRIPLE RIB)

9.00-10/12	TT	FA45A	34	6.00	17	2695	9.20	27.40
4.00-12/4	TT	FA482	8	3.00	14	495	4.60	21.30
4.00-15/4	TT	FA4AK	9	3.00	6	585	4.80	24.20
5.00-15/4	TT	FC2J2	13	3.00	13	715	5.20	26.20
7.5L-15/6	TT	FC2B4	30	6.00	24	1430	8.00	29.90
9.5L-15/8	TT	FA4C6	37	7.00	30	1870	9.50	31.20
11L-15/8	TT	FC2D6	44	8.00	30	2090	10.40	33.40
5.50-16/4	TT	FC2K2	17	4.00	17	855	6.10	28.50
5.50-16/6	TT	FC2K4	19	4.00	17	1050	6.10	28.50
6.00-16/4	TT	FC2L2	19	4.00	15	910	6.50	29.10
6.00-16/6	TT	FC2L4	20	4.00	15	1140	6.50	29.10
6.50-16/6	TT	FC2M4	24	4.50	21	1230	7.00	30.30
7.50-16/6	TT	FC2N4	33	5.50	23	1480	7.90	32.10
7.50-16/8	TT	FC2N6	36	5.50	23	1710	7.90	32.10
10.00-16/8	TT	FC2P6	48	8.00	29	2340	10.30	35.20
11.00-16/8	TT	FC2T6	63	10.00	33	2600	12.20	38.40
7.50-18/4	TT	FC2W4	37	5.50	25	1610	7.90	33.90
4.00-19/4	TT	FA4AE	12	3.00	9	715	4.40	28.30
7.50-20/6	TT	FA4AM	43	5.50	23	1710	7.90	36.80
7.5L-15/6	TL	FA4B3	34	6.00	24	1430	8.00	29.90
9.5L-15/8	TL	FA4C5	46	7.00	30	1870	9.50	31.20
6.50-16/6	TL	FA4M3	27	4.50	21	1230	7.00	30.30
7.50-16/6	TL	FA4N3	39	5.50	23	1480	7.90	32.10
10.00-16/8	TL	FA4P5	54	8.00	29	2340	10.30	35.20
11.00-16/8	TL	FA4T5	73	10.00	33	2600	12.20	38.40

AMERICAN FARMER (R1)

7-16/6	TT	FA1BW	24	6.00	28	1135	7.01	29.20
7-16/6	TL	FA1EW	27	6.00	28	1135	7.01	29.20
18.4-16.1/6	TT	FA1DA	115	16.00	40	2810	18.40	44.80
18.4-16.1/8	TT	FA1AL	126	16.00	40	2910	18.40	44.80

AMERICAN FARMER FARM FRONT (F1 SINGLE RIB)

7.50-16/8	TT	FA2N4	27	5.50	32	1710	8.15	32.00
10.00-16/8	TT	FA2P6	34	8.00	24	2340	11.20	35.15
7.50-18/6	TT	FA2W4	35	5.50	32	1610	7.81	34.30
7.50-20 /6	TT	FA2AM	40	5.50	32	1710	8.48	37.50
7.50-20 /12	TT	FA2DJ	52	5.50	32	2280	8.34	37.50
11.00-16/8	TL	FA2T5	43	10.00	27	2600	13.24	38.41



**SKS H.D. TRAC LOADER
GRIPPER & XTRA WALL**



SKS HAULER



TIRE SIZE	TYPE	ITEM CODE	TIRE WEIGHT	RIM WIDTH	TREAD DEPTH	MAX LOAD	SECTION WIDTH	DIAMETER
SOLIDEAL SKS NATURAL RUBBER H.D. TRAC LOADERS AND SKS GRIPPER* AND XTRA WALL								
700X15/6	TL	104110311	43.4	5.50	18	3175	8.7	31
10X16.5/8*	TL	10G111461	42.0	8.25	20	4125	10.7	30.1
12X16.5/10*	TL	10G111541	59.0	9.25	23	5599	12.3	32.5
23X8.5-12/6	TL	10X111341	25.7	7.00	18	1819	8.5	22
26X12-12/10	TL	10X111361	47.3	10.50	30	3593	11.7	26
27X8.5-15/6	TL	10X111381	30.0	7.00	17	2480	8.4	27
12X16.5/8	TL	10X111461	49.0	8.25	20	3924	11.0	30
10X16.5/10	TL	10X111481	58.0	8.25	20	4718	10.9	30
12X16.5/10	TL	10X111541	67.0	9.75	20	5611	12.3	33
14X17.5/12	TL	10X111591	118.0	10.50	35	7826	13.7	36

SOLIDEAL SKS HAULER

23X8.5-12/6	TL	304111341	27.6	7.00	16	1819	8.3	23
27X8.5-15/6	TL	304111381	37.1	7.00	12	2480	8.3	27
27X10.50-15/8	TL	304111401	51.1	8.50	20	3064	9.9	28
31X15.5-15/8	TL	304111421	78.7	13.00	28	3726	15.2	31
10X16.5/8	TL	304111461-788	58.0	8.25	17	3924	10.8	31
10X16.5/10	TL	304111481-788	60.5	8.25	17	4718	10.8	31
31.5X13-16.5/10	TL	304111501	70.5	9.75	17	5368	13.9	31
12X16.5/10	TL	304111541	78.0	9.75	20	5357	12.8	32
33X15.5-16.5/14	TL	304111571	107.4	12.00	22	6944	15.2	33
14X17.5/14	TL	304111601	110.9	10.5	30	8543	13.9	37
15X19.5/14	TL	304111681	128.8	11.75	31	11177	15.7	40



EXTRA DEEP INDUSTRIAL PNEUMATICS



PNEUMATIC TGRADER & BACKHOE



LOADER L-2 AND L-3



SOLIDEAL®

TIRE SIZE	TYPE	ITEM CODE	TIRE WEIGHT	RIM WIDTH	TREAD DEPTH	MAX LOAD	SECTION WIDTH	DIAMETER
-----------	------	-----------	-------------	-----------	-------------	----------	---------------	----------

SOLIDEAL EXTRA DEEP INDUSTRIAL PNEUMATICS FORKLIFT TIRE

4.00-8/10	TL	102110041	10.0	3.00	8	1477	4.4	16
5.00-8/8	TL	102110061	14.4	3.00	9	2094	5.1	18
6.00-9/10	TL	102110101	21.0	4.00	10	2910	5.9	21
6.50-10/10	TL	102110141	27.1	5.00	12	3307	6.7	23
7.00-12/12	TL	102110221	32.0	5.00	11	4541	7.1	27
7.00-12/14	TL	102110241	32.0	5.00	11	4674	7.2	27
7.50-10/12	TL	102110201	47.0	5.50	11	5677	7.6	30
7.50-15/14	TL	102110381	48.0	6.00	25	6173	7.9	31
8.25-15/14	TL	102110461	74.2	6.50	25	7165	9.1	33

SOLIDEAL PNEUMATIC GRADER & BACKHOE

1300X24/12 TG	TL	104111801	180.0	8.00TGX24	33	6008	14.2	51
1400X24/12 TG	TL	104111841	188.0	8.00TGX24	33	7605	14.4	54
19.5L-24/12 IND	TL	104112501	218.0	DW16AX24	35	7606	19.1	52
21L-24/12 IND	TL	104112601	278.0	DW18AX24	48	8543	21.0	55
16.9-28/12 IND	TL	104112801	225.0	W15LX28	42	7826	17.9	56
18.4-28/12 IND	TL	104112901	272.7	W16LX28	49	9094	19.8	59

SOLIDEAL SKZ SKID STEER LIFEMASTER

31X15.5-15/8	TL	30Z111421	90.5	13.00	28	3726	15.2	31
10-16.5/8	TL	30Z111461	72.0	8.25	37	4134	10.8	31
10-16.5/10	TL	30Z111481	76.1	8.25	37	4718	10.8	31
12-16.5/10	TL	30Z111541	95.2	9.75	37	5611	12.4	33
12X16.5/12	TL	30Z111551	101.4	9.75	38	6349	12.6	33
33X15.5-16.5/14	TL	30Z111571	128.3	12.00	38	6944	15.2	31
14X17.5/14	TL	30Z111601	151.7	10.5	48	8543	13.9	37

SOLIDEAL PNEUMATIC LOADER AND GRADER TIRES

15.5X25/12	L2/G2/E2	10411400L1	171.6	12.00/1.3	31	5842	16.1	50
17.5X25/12	L2/G2/E2	10411410L1	194.1	14.00/1.5	33	6393	18.1	53
17.5X25/16	L2/G2/E2	10411415L1	220.4	14.00/1.5	33	7385	18.1	53
20.5X25/16	L2/G2/E2	10411425L1	289.8	17.00/2.0	38	8818	21.1	59
15.5X25/12	L3/G3/E3	10411400R1	196.0	12.00/1.3	33	5842	16.4	50
15.5X25/16	L3/G3/E3	10411405R1	204.7	12.00/1.3	33	6614	16.4	50
17.5X25/12	L3/G3/E3	10411410R1	259.2	14.00/1.5	35	6393	18.8	53
17.5X25/16	L3/G3/E3	10411415R1	279.9	14.00/1.5	35	7385	18.8	53
20.5X25/16	L3/G3/E3	10411425R1	346.4	17.00/2.0	40	8818	21.5	59
20.5X25/20	L3/G3/E3	10411430R1	352.7	17.00/2.0	40	12676	21.5	59
23.5X25/20	L3/G3/E3	10411438R1	497.7	19.5/2.5	47	16094	24.6	64
26.5X25/20	L3/G3/E3	10411520R1	608.5	22.00/3.0	50	18188	27.2	69