



M8008



POWER ST



SPORT TRAIL ST

TIRE SIZE	ITEM CODE	TIRE WEIGHT	RIM WIDTH	TREAD DEPTH	MAX LOAD	SECTION WIDTH	DIAMETER
-----------	-----------	-------------	-----------	-------------	----------	---------------	----------

**MAXXIS M8008 RADIAL ST TRAILER TIRE**

ST205/75R14/6	OWL	TL12461000	22.70	5.5	9.0	1760	8.0	26.1
ST205/75R15/6	OWL	TL15701000	23.96	5.5	9.0	1820	8.1	27.1
ST205/75R14/6	BSW	TL12460000	22.70	5.5	9.0	1760	8.0	26.1
ST215/75R14/6	BSW	TL12474000	24.25	6.0	9.0	1870	8.5	26.7
ST205/75R15/6	BSW	TL15700000	24.69	5.5	9.0	1820	8.1	27.1
ST225/75R15/8	BSW	TL15710000	29.98	6.0	9.0	2540	8.9	28.3
ST225/75R15/10	BSW	TL15713000	34.16	6.0	9.0	2830	8.9	28.3
ST175/80R13/6	BSW	TL08696000	17.53	5.0	9.0	1360	7.1	24.1
ST185/80R13/6	BSW	TL08896000	18.73	5.0	9.0	1480	7.4	24.7
ST235/80R16/10	BSW	TL30141000	43.43	6.5	9.0	3420	9.25	30.7

**HERCULES POWER ST TRAILER TIRE**

ST175/80R13/6	63958	18	4.5	10	1360	7	24.00
ST205/75R14/6	63959	21	5.5	10	1870	8	26.10
ST215/75R14/6	63960	23	6	10	1760	8.5	26.60
ST205/75R15/6	63961	24	5.5	10	1820	8	27.00
ST205/75R15/8	63962	24	5.5	10	2150	8	27.00
ST225/75R15/8	63963	29	6	10	2640	8.8	28.30
ST235/80R16/10	63964	37	6.5	10	3520	9.8	30.80

**CARLISLE SPORT TRAIL ST TRAILER TIRE**

4.80-8/4	5193171	5.8	3.75	7	585	4.7	16.2
4.80-8/6	5193181	6.4	3.75	7	760	4.9	16.3
5.70-8/4	5193191	9.2	3.75	10	715	5.9	18.1
5.70-8/6	5193201	9.9	3.75	10	910	6	18.4
16.5X6.5-8/4	5193421	8.15	5.38	7	615	6.7	16.6
16.5X6.5-8/6	5193461	9.45	5.38	7	785	6.8	16.6
16.5X6.5-8/8	5193481	10.3	5.38	7	910	6.8	16.6
18.5X8.5-8/4	5193431	12.2	7	11	760	8.6	18
18.5X8.5-8/6	5193451	13.36	7	11	935	8.7	17.9
20.5X8.0-10/4	5193441	14.35	6	11	910	8.1	20.8
20.5X8.0-10/6	5193471	16.14	6	11	1100	8	20.9
20.5X8.0-10/8	5193491	17.08	6	11	1320	8.3	20.7
20.5X8.0-10/10	5193501	17.88	6	11	1520	8.5	20.8
20.5X8.0-10/12	5193511	18.3	6	11	1650	8.5	21.2
4.80-12/4	5193211	9.7	4	7	785	5.1	20.7
4.80-12/6	5193221	10.1	4	7	990	5.1	21
5.30-12/4	5193231	9.3	4	7	855	5.4	21.4
5.30-12/6	5193241	10.9	4	7	1050	5.5	21.7
ST175/80D13/4	5193251	18.1	4.5	7	1100	6.8	24.2
ST175/80D13/6	5193261	20.4	4.5	7	1360	6.8	24
ST185/80D13/6	5193321	19.68	4.5	9	1480	7.3	24.7
ST185/80D13/8	5193531	22.12	4.5	9	1710	7.4	24.8
ST205/75D14/6	5193131	22.9	5.5	10	1760	7.8	26.3
ST215/75D14/6	5193281	24.2	5.5	10	1870	8	26.7
ST205/75D15/4	5193291	22.4	5	10	1480	7.9	26.9
ST205/75D15/6	5193381	23.2	5	10	1820	7.9	27
ST225/75D15/6	5193301	28.9	6	11	2150	8.7	27.7
ST225/75D15/8	5193311	30.7	6	11	2540	8.7	28.2
700-15LT/8	5193351	32.14	5.5	15	2040 - S	8.29	29.83
750-16LT/10	5193371	38.8	6	15	2755 - S	8.62	32.61
8-14.5LT/12	5193341	28.69	6	15	2835 - S	8.07	28.32



RADIAL TRAIL ST



MULTI-TRAC CS

TIRE SIZE	ITEM CODE	TIRE WEIGHT	RIM WIDTH	TREAD DEPTH	MAX LOAD	SECTION WIDTH	DIAMETER
-----------	-----------	-------------	-----------	-------------	----------	---------------	----------

**CARLISLE RADIAL TRAIL ST TRAILER TIRE**

ST145/R12/8	5151291	15.0	4.0	8.0	1220	5.8	21.1
ST175/80R13/6	5198121	16.5	4.5	10.0	1360	6.7	24.1
ST205/75R14/6	5198131	23.8	5.5	10.0	1760	8.0	26.1
ST205/75R15/6	5198081	26.0	5.0	10.0	2150	8.0	27.2
ST205/75R15/6	5198151	25.6	5.5	10.0	1820	8.0	27.2
ST215/75R14/8	5198141	25.1	6.0	10.0	1870	8.2	26.8
ST225/75R15/6	5198161	28.5	6.0	10.0	2150	8.8	28.2
ST225/75R15/8	5198171	29.6	6.0	10.0	2540	8.8	28.3
ST225/75R15/10	5198221	30.5	6.0	10.0	2830	9.0	28.2
ST235/85R16/10	5192991	39.5	6.0	16.0	3640	9.3	31.7
ST235/85R16/12	5193411	49.6	6.0	16.0	3960	9.0	31.9
ST245/75R16/8	5198241	42.3	6.0	16.0	3000	9.2	30.5

**CARLISLE USA TRAIL TRAILER TIRE**

480-8/4	519056	6.7	3.75	6	585	5.1	17.1
480-8/6	519058	8.1	3.75	6	760	5.1	17.4
570-8/4	519086	9.8	3.75	10	715	6.0	19.2
570-8/6	519087	11.3	3.75	10	910	6.0	18.8
570-8/8	519088	12.3	3.75	10	1070	6.1	18.9
16.5X6.5-8/6	519297	10.9	5.38	7	785	6.6	16.2
16.5X6.5-8/8	519298	10.7	5.38	7	910	6.7	16.3
18.5X8.5-8/4	519471	13.7	7.00	10	760	8.4	18.0
18.5X8.5-8/6	519472	15.4	7.00	10	935	8.5	17.7
690-9/6	519572	13.0	4.50	10	1100	7.1	22.0
20.5X8.0-10/4	519141	15.8	6.00	10	910	8.4	21.0
20.5X8.0-10/6	519142	17.6	6.00	10	1100	8.5	20.7
20.5X8.0-10/8	519143	17.8	6.00	10	1320	8.6	20.5
20.5X8.0-10/10	519144	18.7	6.00	10	1520	8.7	20.9
480-12/4	519062	9.6	4.00	8	785	5.0	21.0
480-12/6	519063	10.3	4.00	8	990	5.1	21.3
530-12/4	519076	10.3	4.00	8	855	5.3	21.8
530-12/6	519077	11.5	4.00	8	1050	5.3	22.1
ST175/80D13/6	519161	17.1	4.50	10	1360	6.7	25.0
ST205/75D14/6	519300	21.3	5.50	10	1760	8.3	26.0
ST215/75D14/6	519315	24.9	6.00	10	1870	8.5	26.3
ST205/75D15/6	519400	24.1	5.50	10	1820	8.0	27.1
ST225/75D15/6	519410	28.6	6.00	10	2150	8.9	28.1
ST225/75D15/8	519412	33.6	6.00	10	2540	9.0	28.6