



## AVALANCHE X-TREME™

Road Hazard Warranty

- Designed for harsh winter driving conditions.
- Studdable, providing a biting grip for better traction, responsiveness and safety.
- Provides a smooth quiet ride while delivering excellent handling.

TIRE SIZE	SPEED RATING	SIDE WALL	ITEM CODE	TIRE WEIGHT	RIM WIDTH	TREAD DEPTH	MAX LOAD	SECTION WIDTH	DIAMETER
<b>HERCULES AVALANCHE X-TREME - ROAD HAZARD WARRANTY</b>									
P185/75R14	89S	WSW	01049	18	5.0	13.5	1279	7.20	25.10
P195/75R14	92S	WSW	01051	19	5.5	13.5	1389	7.60	25.65
P205/75R14	95S	WSW	01055	21	5.5	14.0	1521	7.95	26.20
P205/75R15	97S	WSW	01057	22	5.5	14.0	1609	7.95	27.20
P215/75R15	100S	WSW	01059	24	6.0	14.0	1764	8.40	27.80
P225/75R15	102S	WSW	01061	25	6.0	14.0	1874	8.70	28.30
P235/75R15	105S	WSW	01063	27	6.5	14.5	2039	9.10	28.90
P205/70R15	96S	WSW	01065	21	6.0	13.0	1565	8.00	26.40
P215/70R15	98S	WSW	01067	23	6.5	13.0	1653	8.40	26.90
P225/70R15	100S	WSW	01069	25	6.5	13.0	1764	8.70	27.40
P185/70R14	88S	BLK	01001	18	5.5	13.0	1235	7.45	24.45
P195/70R14	91S	BLK	01003	18	6.0	13.0	1356	7.75	25.00
P175/65R14	82T	BLK	01005	16	5.0	13.0	1047	6.85	23.10
P185/65R14	86T	BLK	01007	17	5.5	13.0	1168	7.35	23.55
P185/65R15	88T	BLK	01009	19	5.5	13.0	1235	7.55	24.51
P195/65R15	91T	BLK	01011	20	6.0	13.0	1356	7.85	25.00
P205/65R15	94T	BLK	01013	22	6.0	13.0	1477	8.02	25.45
P215/65R15	96T	BLK	01017	24	6.5	13.0	1565	8.55	25.98
P205/65R16	95T	BLK	01004	23	6.0	13.0	1521	8.02	26.45
P215/65R16	98T	BLK	01029	26	6.5	13.0	1653	8.55	26.98
P185/60R15	91T	BLK	01023	22	6.0	13.0	1353	8.15	24.75
P195/60R15	88T	BLK	01021	21	5.5	13.0	1235	7.80	24.30
P205/60R15	91T	BLK	01023	22	6.0	13.0	1356	8.15	24.75
P215/60R15	94T	BLK	01027	23	6.5	13.0	1477	8.60	25.21
P205/60R16	92T	BLK	01031	23	6.0	13.0	1389	8.33	25.77
P215/60R16	95T	BLK	01033	24	6.5	13.0	1521	8.50	26.15
P225/60R16	98T	BLK	01035	25	6.5	13.0	1653	8.75	26.57
P235/60R16	100T	BLK	01006	28	7.0	13.0	1764	9.45	26.96
P225/60R17	99T	BLK	01075	27	6.5	13.0	1709	9.14	27.72
P225/60R18	100T	BLK	01048	29	TBA	TBA	TBA	TBA	TBA
P275/60R20	119S	BLK	01070	50	8.5	14.0	2998	12.69	33.08
P195/55R15	85T	BLK	01000	20	5.5	13.0	1135	7.91	23.75
P205/55R15	88T	BLK	01002	13	6.5	13.0	1235	8.38	24.14
P205/55R16	91T	BLK	01037	23	6.5	12.0	1356	8.35	24.80
P215/55R16	97T	BLK	01008	24	7.0	13.0	1609	8.90	25.35
P215/55R17	94T	BLK	01073	27	6.5	13.0	1709	8.93	27.30
P225/55R17	97T	BLK	01039	28	7.0	13.0	1609	9.20	26.88
P235/55R17	99T	BLK	01045	31	7.5	13.0	1709	9.79	27.22
P205/50R16	87T	BLK	01010	20	6.5	13.0	1201	8.34	24.27
P225/50R16	92T	BLK	01012	25	7.0	13.0	1389	9.17	25.10
P215/50R17	91T	BLK	01014	24	7.0	13.0	1356	8.82	25.69
P225/45R17	94T	BLK	01016	26	7.5	13.0	1477	9.03	25.09
P235/45R17	94T	BLK	01047	27	8.0	13.0	1477	9.30	25.53



## AVALANCHE X-TREME™

Road Hazard Warranty

- Designed for harsh winter driving conditions.
- Studdable, providing a biting grip for better traction, responsiveness and safety.
- Provides a smooth quiet ride while delivering excellent handling.

TIRE SIZE	SPEED RATING	SIDE WALL	ITEM CODE	TIRE WEIGHT	RIM WIDTH	TREAD DEPTH	MAX LOAD	SECTION WIDTH	DIAMETER
<b>HERCULES AVALANCHE X-TREME SUV &amp; LIGHT TRUCK - ROAD HAZARD WARRANTY</b>									
P255/65R16	109S	OWL	01020	36	7.5	14	2271	10.24	7.5
P235/65R17	104S	OWL	01022	33	7.0	14	1984	9.45	7.0
P245/65R17	107S	OWL	01024	36	7.0	14	2149	9.82	7.0
P275/60R17	110S	OWL	01026	39	8.0	14	2337	11.20	8.0
P245/75R16	111S	BLK	01050	35	7.0	15	2403	9.60	7.0
P265/75R16	116S	BLK	01052	39	7.5	15	2756	10.60	7.5
P265/70R15	112S	BLK	01018	35	8.0	15	2469	10.45	8.0
P215/70R16	100S	BLK	01054	30	6.5	15	1764	8.80	6.5
P225/70R16	102S	BLK	01056	30	6.5	15	1874	9.00	6.5
P235/70R16	106S	BLK	01058	32	7.0	15	2094	9.40	7.0
P245/70R16	107S	BLK	01060	34	7.0	15	2149	9.85	7.0
P255/70R16	111S	BLK	01062	35	7.5	15	2403	10.3	7.5
P265/70R16	112S	BLK	01064	39	8.0	15	2469	10.8	8.0
P265/70R17	115S	BLK	01066	41	8.0	15	2679	10.65	8.0
P185/60R15	84T	BLK	01019	19	5.5	13	1102	7.44	5.5
P235/60R16	100T	BLK	01006	28	7.0	13	1764	9.45	7.0
P255/55R18	109S	BLK	01068	41	8.0	14	2271	10.36	8.0
LT215/85R16/10	115/112Q	BLK	01040	38	6.0	17	2680	9.10	6.0
LT235/85R16/10	120/116Q	BLK	01032	42	6.5	17	3042	9.31	6.5
LT235/80R17/10	120/117Q	BLK	01076	45	6.5	18	3085	9.40	6.5
LT235/75R15/6	104/101Q	BLK	01028	40	8.5	19	2270	10.50	8.5
LT245/75R16/6	108/104Q	BLK	01036	40	7.0	17	2205	9.57	7.0
LT265/75R16/6	112/109Q	BLK	01042	44	7.5	17	2470	10.33	7.5
LT225/75R16/10	115/112Q	BLK	01034	39	6.0	17	2680	8.95	6.0
LT245/75R16/10	120/116W	BLK	01038	45	7.0	17	3042	9.57	7.0
LT265/75R16/10	123/120Q	BLK	01044	48	7.5	17	3415	10.50	7.5
LT275/70R17/6	114/110Q	BLK	01078	44	8.0	18	2600	11.32	8.0
LT245/70R17/10	119/116Q	BLK	01046	44	7.0	17	3000	10.70	7.0
LT265/70R17/10	121/118Q	BLK	01074	50	8.0	18	3195	11.03	8.0
LT31X10.50R15/6	109Q	BLK	01030	34	6.5	17	1985	9.00	6.5