



*Manufacturing Quality Tires In The USA Since 1915*

# SPECIALTY TIRES OF AMERICA, INC.

---

MANUFACTURING QUALITY TIRES IN THE USA SINCE 1915

---

C A T A L O G



---

**MANUFACTURING QUALITY TIRES IN THE USA SINCE 1915**

---

1600 Washington Street, Indiana, Pennsylvania 15701-2844

TOLL FREE: 1-800-622-7327  
SALES OFFICE: 724-349-9650  
FAX: 724-349-8192  
E-Mail: [info@stausaonline.com](mailto:info@stausaonline.com)  
WEBSITE: [www.stausaonline .com](http://www.stausaonline.com)

## TABLE OF CONTENTS

PAGE	2	AMERICAN CONTRACTOR <sup>®</sup> LOADER-GRADER G2/L2, INDUSTRIAL TRACTOR R4
	3	AMERICAN CARRIER, AMERICAN CONTRACTOR, STA ROCK SERVICE E/L3, XT3
	4	AMERICAN CONTRACTOR <sup>®</sup> ROCK TRAXION E/L4, BIG JAKE <sup>®</sup> L5 LUG
	5	AMERICAN CARRIER, <sup>®</sup> L3 TREADED, L4 SMOOTH
	6	AMERICAN CARRIER, <sup>®</sup> L4 TREADED, L5 SMOOTH
	7	BIG JAKE, <sup>®</sup> L5 SMOOTH
	8	AMERICAN LOGGER <sup>®</sup> LS2, LS1
	9	AMERICAN FARMER <sup>®</sup> IMPLEMENT I-1 RIB (LOW PROFILE)
	10	AMERICAN FARMER RIB IMPLEMENT I-1 (CONVENTIONAL TYPE)
	11	AMERICAN FARMER RIB IMPLEMENT I-1 16.1 (LOW PROFILE)
	12	AMERICAN FARMER IMPLEMENT (HF-1), FLOTATION IMPLEMENT I-2
	13	AMERICAN FARMER FARM FRONT (F1 SINGLE RIB)
	14	AMERICAN FARMER TRACTOR (R-1), TRACTION IMPLEMENT (I-3)
	15	AMERICAN FARMER REAR TRACTOR (R-1) <b>(NEW)</b>
	16	AMERICAN FARMER FARM FRONT (F2M)
	17	AMERICAN FARMER FARM FRONT (F2)
	18	AMERICAN FARMER INDUSTRIAL RIB F-3, TURF TRACTION R-3
	19	AMERICAN FARMER HF-3 TRACTION
	20	STA MINE SPECIAL, NEW MINE SPECIAL
	21	BIG JAKE MINER
	22	STA SUPERLUG <sup>®</sup> HEAVY DUTY
	23	STA SUPERLUG HEAVY DUTY, SUPERLUG <sup>®</sup> SMOOTH
	24	STA TRAXION, <sup>®</sup> LOADER, CHEVRON
	25	BIG JAKE SKID STEER
	26	STA SUPERLUG, INDUSTRIAL DEEP LUG <sup>®</sup>
	27	STA DYNA TRAC, <sup>®</sup> HEAVY DUTY
	28	FLAPS
	29	AMERICAN COMPACTOR C-1, BIG JAKE CHOCK HAULER
	30	STA SUPER TRANSPORT LIGHT TRUCK
	31	STA SUPER TRANSPORT LIGHT TRUCK
	32	STA SUPER TRAXION <sup>®</sup> LIGHT TRUCK
	33	STA MILITARY TIRES
	34	STA TRAILBREAKER <sup>®</sup> LIGHT TRUCK, SUPER TRANSPORT / SUPER TRAXION PASSENGER
	35	STA SUPERLUG LIGHT TRUCK, SUPERLUG SPECIAL <sup>®</sup>

**\*\*ALL PRODUCTS MANUFACTURED BY SPECIALTY TIRES OF AMERICA, INC. ARE MADE IN THE USA.  
OUR PLANTS ARE LOCATED IN INDIANA, PA AND UNICOI, TN.**

# AMERICAN CONTRACTOR<sup>®</sup> G2/L2 LOADER-GRADER

G2/L2

\* ROAD GRADERS  
\* FRONT END LOADERS  
\* DOZERS

\* FORKLIFT TRUCKS  
\* SCRAPERS



FIGURE A



FIGURE B



FIGURE C

SIZE	FIGURE	PLY RATING	PRODUCT CODE	DESCRIPTION	TREAD DEPTH	OVERALL DIAMETER	RIM WIDTH	OVERALL WIDTH	MAXIMUM INFLATION	MAXIMUM LOAD 25 MPH	WEIGHT
8.25-20TG	B	6	DEAPB	E2/G2	23/32	38.20	6.50	9.80	30	2260	66
13.00-24TG	A	12	NC5C7	E2/G2	28/32	50.80	8.00	13.10	44	6000	136
13.00-24TG	A	16	NC5CB	E2/G2	28/32	50.80	8.00	13.10	54	6760	150
14.00-24TG	A	12	NC5A7	E2/G2	34/32	53.10	8.00	14.25	36	6800	156
14.00-24TG	A	16	NC5AB	E2/G2	34/32	53.10	8.00	14.25	51	8050	171
16.00-24TG	A	12	NC5N7	E2/G2/L2	36/32	59.20	10.00	16.80	33	8050	250
16.00-24TG	A	16	NC5NB	E2/G2/L2	36/32	59.20	10.00	16.80	44	9900	271
15.5-25	A	12	NC5M7	E2/G2/L2	28/32	51.00	12.00	15.50	36	2650	147
15.5-25	A	16	NC5MB	E2/G2/L2	28/32	51.00	12.00	15.50	47	3100	163
17.5-25	A	12	NC5B7	E2/G2/L2	32/32	53.50	14.00	17.50	29	6400	184
17.5-25	A	16	NC5BB	E2/G2/L2	32/32	53.50	14.00	17.50	40	7400	190
17.5-25	A	20	NC5BF	E2/G2/L2	32/32	53.50	14.00	17.50	47	8050	207
18.00-25	C	12	NC5AC	E2/G2/L2	40/32	63.50	13.00	19.00	29	10500	371
18.00-25	C	16	NC5AD	E2/G2/L2	40/32	63.50	13.00	19.00	40	12300	409
20.5-25	A	12	NC5D7	E2/G2/L2	36/32	58.60	17.00	20.50	25	7850	246
20.5-25	A	16	NC5DB	E2/G2/L2	36/32	58.60	17.00	20.50	33	8800	266
20.5-25	A	20	NC5DF	E2/G2/L2	36/32	58.60	17.00	20.50	40	9900	287
23.5-25	C	12	NC557	E2/G2/L2	40/32	63.68	19.50	23.50	29	10500	410
23.5-25	C	16	NC55B	E2/G2/L2	40/32	63.68	19.50	23.50	36	12000	428

# AMERICAN CONTRACTOR<sup>®</sup> R4 INDUSTRIAL TRACTOR

\* BACKHOES  
\* INDUSTRIAL TRACTORS



FIGURE D



FIGURE E

SIZE	FIGURE	PLY RATING	PRODUCT CODE	DESCRIPTION	TREAD DEPTH	OVERALL DIAMETER	RIM WIDTH	OVERALL WIDTH	MAXIMUM INFLATION	MAXIMUM LOAD 25 MPH	WEIGHT
14.9-24	D	8	NC5E3	R4	33/32	48.60	13.00	14.90	30	5080	119
16.9-24	D	8	NC5F3	R4	35/32	51.50	15.00	16.90	28	5840	148
17.5L-24	D	8	NC5H3	R4	33/32	49.20	15.00	17.50	26	5360	139
17.5L-24	D	12	NC5H5	R4	33/32	49.20	15.00	17.50	34	4680	150
18.4-24	D	10	NC5J5	R4	36/32	54.20	16.00	18.40	30	7400	176
19.5L-24	D	10	NC5K5	R4	34/32	51.50	17.00	19.50	28	6600	186
19.5L-24	D	12	NC5K7	R4	34/32	51.50	17.00	19.50	34	7600	191
21L-24	D	12	NC5L7	R4	35/32	54.50	18.00	21.00	32	8550	236
16.9-28	E	10	NC575	R4	31/32	56.50	15.00	18.10	32	6800	172
16.9-28	E	12	NC577	R4	31/32	56.50	15.00	18.10	38	7550	174

# AMERICAN CONTRACTOR,<sup>®</sup> STA E/L3, XT-3 ROCK SERVICE



FIGURE A



FIGURE B



FIGURE C

SIZE	FIGURE	PLY RATING	PRODUCT CODE	DESCRIPTION	TREAD DEPTH	OVERALL DIAMETER	RIM WIDTH	OVERALL WIDTH	MAXIMUM INFLATION	MAXIMUM LOAD	WEIGHT
12.00-24	A	20	NA3PE	E3/L3 TT	28/32	48.10	8.50	12.50	80 (E3)	8050 (E3)	195
									120 (L3)	15210 (L3)	
14.00-24	A	20	NA3TE	E3/L3 TT	30/32	53.40	10.00	14.70	69 (E3)	10200 (E3)	269
									102 (L3)	18700 (L3)	
14.00-24	A	24	NA3TK	E3/L3 TT	30/32	53.40	10.00	14.70	83 (E3)	11400 (E3)	274
									116 (L3)	20390 (L3)	
16.00-24	B	16	NA3NB	E3/L3 TL	34/32	59.00	10.00	16.50	45 (E3)	10400 (E3)	339
									62 (L3)	18200 (L3)	
16.00-24	B	20	NA3NF	E3/L3 TL	34/32	59.00	10.00	16.50	60 (E3)	12300 (E3)	362
									77 (L3)	14250 (L3)	
15.5-25	B	12	NA3M7	E3/L3 TL	32/32	50.50	12.00	15.50	36 (E3)	7150 (E3)	176
									58 (L3)	12300 (L3)	
15.5-25	B	16	NA3MB	E3/L3 TL	32/32	50.50	12.00	15.50	47 (E3)	8350 (E3)	192
									76 (L3)	14400 (L3)	
16.00-25	B	24	NA3VL	E3/L3 TL	32/32	59.00	11.25	16.50	69 (E3)	8350 (E3)	394
									94 (L3)	14400 (L3)	
16.00-25	B	28	NA3VP	E3/L3 TL	32/32	59.00	11.25	16.50	47 (E3)	13200 (E3)	420
									76 (L3)	23400 (L3)	
17.5-25	B	12	NA3B7	E3/L3 TL	32/32	53.20	14.00	17.80	33 (E3)	8050 (E3)	228
									51 (L3)	13600 (L3)	
17.5-25	B	16	NA3BB	E3/L3 TL	32/32	53.20	14.00	17.80	44 (E3)	9350 (E3)	251
									69 (L3)	16100 (L3)	
17.5-25	B	16	NA3BF	E3/L3 TL	32/32	53.20	14.00	17.80	58 (E3)	11000 (E3)	266
									83 (L3)	18200 (L3)	
20.5-25	B	16	NA3DB	E3/L3 TL	38/32	59.20	17.00	20.20	40 (E3)	12000 (E3)	342
									51 (L3)	18200 (L3)	
20.5-25	B	20	NA3DF	E3/L3 TL	38/32	59.20	17.00	20.20	47 (E3)	13200 (E3)	365
									65 (L3)	20900 (L3)	
23.5-25	B	16	NA35B	E3/L3 TL	40/32	63.70	19.50	23.50	33 (E3)	13600 (E3)	483
									44 (L3)	20900 (L3)	
23.5-25	B	20	NA35F	E3/L3 TL	40/32	63.70	19.50	23.50	44 (E3)	16100 (E3)	507
									54 (L3)	24000 (L3)	
26.5-25 *	B	20	NA3UF	E3/L3 TL	44/32	69.00	22.00	26.80	36 (E3)	18200 (E3)	752
									51 (L3)	29100 (L3)	
26.5-25 *	B	26	NA3UN	E3/L3 TL	44/32	69.00	22.00	26.80	51 (E3)	22000 (E3)	783
									69 (L3)	34200 (L3)	
26.5-25 XT-3	C	20	NC1UF	E3/L3 TL	48/32	68.00	22.00	27.20	36 (E3)	18200 (E3)	800
									51 (L3)	29100 (L3)	
26.5-25 XT-3	C	26	NC1UN	E3/L3 TL	48/32	68.00	22.00	27.20	51 (E3)	22000 (E3)	825
									69 (L3)	34200 (L3)	
29.5-25	B	22	NA39J	E3/L3 TL	45/32	73.20	25.00	30.50	36 (E3)	22000 (E3)	911
									47 (L3)	33100 (L3)	
29.5-25	B	28	NA39P	E3/L3 TL	45/32	73.20	25.00	30.50	47 (E3)	26800 (E3)	943
									62 (L3)	38600 (L3)	

\* Denotes Non-stocking

\*LOADS E3 30 MPH  
\*LOADS L3 5 MPH

**IMPORTANT**  
TYPE E3: HAULING SERVICE ONLY  
TYPE E3/L3: HAULING & LOADER SERVICE

TT = TUBE TYPE  
TL = TUBELESS

**\*\*ALL PRODUCTS MANUFACTURED BY SPECIALTY TIRES OF AMERICA, INC. ARE MADE IN THE USA.  
OUR PLANTS ARE LOCATED IN INDIANA, PA AND UNICOI, TN.**

# AMERICAN CONTRACTOR<sup>®</sup> E/L4 - ROCK TRAXION

**HAULING**  
**LOADER SERVICE**



FIGURE A

SIZE	FIGURE	PLY RATING	PRODUCT CODE	DESCRIPTION	TREAD DEPTH	OVERALL DIAMETER	RIM WIDTH	OVERALL WIDTH	MAXIMUM INFLATION	MAXIMUM LOAD 30MPH	WEIGHT
16.00-25	A	28	NC2VP	E/L4	54/32	58.70	11.25	18.7	83	14800	521

IMPORTANT  
TYPE E/L4 HAULING & LOADER SERVICE

# BIG JAKE<sup>®</sup> L5

**MINING**  
**LOADER SERVICE**  
**SEVERE USE APPLICATIONS**



FIGURE A

**TUBELESS**

SIZE	FIGURE	PLY RATING	PRODUCT CODE	DESCRIPTION	TREAD DEPTH	OVERALL DIAMETER	RIM WIDTH	OVERALL WIDTH	MAXIMUM INFLATION	MAXIMUM LOAD 5MPH	WEIGHT
14.00-24 *	A	20	TBA	L5	48/32	54.60	10.00	24.6			
17.5-25	A	20	TBA	L5	48/32	55.20	14.00	24.9			
20.5-25	A	20	TBA	L5							
26.5-25	A	20	NDCUF	L5	110/32	69.70	22.00	25.7	51	29100	1328
26.5-25	A	26	NDCUN	L5	110/32	69.70	22.00	25.7	65	33100	1365
26.5-25	A	32	NDCUP	L5	110/32	69.70	22.00	25.7	80	37500	1428
29.5-25	A	28	NDC9P	L5	110/32	72.00	25.00	29.2	62	38600	1684

\* TUBE TYPE

## AMERICAN CARRIER<sup>®</sup> L3 TREADED



CONTAINER SERVICE

TUBELESS

FIGURE A

SIZE	FIGURE	PLY RATING	PRODUCT CODE	DESCRIPTION	TREAD DEPTH	OVERALL DIAMETER	RIM WIDTH	OVERALL WIDTH	MAXIMUM INFLATION	MAXIMUM LOAD 5MPH	WEIGHT
14.00-25	A	28	NA5TA	E/L3	40/32	54.00	10.00	14	141	22750	312

## AMERICAN CARRIER<sup>®</sup> L4S



CONTAINER SERVICE

FIGURE A

SIZE	FIGURE	PLY RATING	PRODUCT CODE	DESCRIPTION	TREAD DEPTH	OVERALL DIAMETER	RIM WIDTH	OVERALL WIDTH	MAXIMUM INFLATION	MAXIMUM LOAD 5 MPH	WEIGHT
16.00-25		32	TBA	L4S							
18.00-25	A	32	NE1LT	L4S	72/32	65.90	13.00	19.60	80	18810	888
18.00-25	A	40	NE1LW	L4S	72/32	65.90	13.00	19.60	138	37500	1017

## AMERICAN CARRIER<sup>®</sup> L4 - TREADED

CONTAINER SERVICE



FIGURE A



FIGURE B

SIZE	FIGURE	PLY RATING	PRODUCT CODE	DESCRIPTION	TREAD DEPTH	OVERALL DIAMETER	RIM WIDTH	OVERALL WIDTH	MAXIMUM INFLATION	MAXIMUM LOAD 5MPH	WEIGHT
16.00-25	A	36	NC2VT	E/L4	54	58.70	11.25	18.7	141	30000	570
18.00-25	B	40	NC2LW	E/L4	68	64.50	13.00	22.8	138	37500	793

## AMERICAN CARRIER<sup>®</sup> L5 S

CONTAINER SERVICE



FIGURE A

SIZE	FIGURE	PLY RATING	PRODUCT CODE	DESCRIPTION	TREAD DEPTH	OVERALL DIAMETER	RIM WIDTH	OVERALL WIDTH	MAXIMUM INFLATION	MAXIMUM LOAD 5MPH	WEIGHT
18.00-25	A	40	NA1LW	L5S	99/32	65.90	13.00	21.5	138	37480	1074

# BIG JAKE<sup>®</sup> L5 S

**MINING**

**LOADER SERVICE**

**SEVERE USE APPLICATIONS**



**TUBE TYPE**

FIGURE A

SIZE	FIGURE	PLY RATING	PRODUCT CODE	DESCRIPTION	TREAD DEPTH	OVERALL DIAMETER	RIM WIDTH	OVERALL WIDTH	MAXIMUM INFLATION	MAXIMUM LOAD 5MPH	WEIGHT
9.50-20	A	14	NDA1A	L5 S	32/32	41.33	7.00	10.97	75	8050	142
10.00-20	A	14	NDA2A	L5 S	32/32	41.58	7.50	10.99	75	9100	149
10.00-20	A	20	NDA2E	L5 S	32/32	41.58	7.50	10.99	145	12975	185
12.00-24	A	16	NDAPC	L5 S	86/32	50.50	8.50	12.4	98	13600	326
12.00-24	A	20	NDAPE	L5 S	86/32	50.50	8.50	12.4	120*	15210	341
14.00-24	A	20	NDATE	L5 S	67/32	55.80	10.00	14.8	102	18700	523
14.00-24	A	28	NDATL	L5 S	67/32	55.80	10.00	14.8	141	22700	539

**TUBELESS**

SIZE	FIGURE	PLY RATING	PRODUCT CODE	DESCRIPTION	TREAD DEPTH	OVERALL DIAMETER	RIM WIDTH	OVERALL WIDTH	MAXIMUM INFLATION	MAXIMUM LOAD 5MPH	WEIGHT
17.5-25	A	20	NDABF	L5 S	86/32	55.10	14.00	17.5	83	18200	526
18.00-25	A	24	NDAAT	L5 S	99/32	64.50	13.00	21.5	80	27600	920
18.00-25	A	32	NDALT	L5 S	99/32	64.50	13.00	21.5	109	33100	1031
18.00-25	A	40	NDALW	L5 S	99/32	64.50	13.00	21.5	138	37500	1058
20.5-25	A	20	TBA	L5 S							
21.00-25	A	28	TBA	L5 S							
21.00-25	A	32	TBA	L5 S							
23.5-25	A	20	NDA5B	L5 S	99/32	65.80	19.50	24.5	54	24000	1109
23.5-25	A	24	TBA	L5 S							
26.5-25	A	26	NDAUN	L5 S	110/32	70.00	22.00	28.7	65	33100	1448
26.5-25	A	32	NDAUP	L5 S	110/32	70.00	22.00	28.7	80	37500	1542
29.5-25	A	28	NDA9P	L5 S	110/32	71.70	22.00	29.5	62	38600	1669
29.5-25	A	34	NDA9T	L5 S	110/32	71.70	22.00	29.5	76	44100	1711

# AMERICAN LOGGER<sup>®</sup>

## STEEL BELTED TIRES FOR FORESTRY APPLICATIONS



FIGURE A



FIGURE B

- \* Advanced rubber compounds provide maximum resistance to cutting, chipping and punctures.
- \* Proven tread angles direct snags away from tire reducing penetrations.
- \* Deep self cleaning lugs for maximum traction and pulling power.
- \* Four steel belts for maximum protection.
- \* 25% deeper tread than LS1 standard tires.
- \* Rim protection to protect rim and bead area.
- \* Tube type.

SIZE	FIGURE	PLY RATING	PRODUCT CODE	DESCRIPTION	TREAD DEPTH	OVERALL DIAMETER	RIM WIDTH	MAXIMUM INFLATION	MAXIMUM LOAD 5 MPH	WEIGHT
23.1-26	A	10	NF146	LS2	67/32	64.80	20	25	10000	573
23.1-26	A	16	NF14C	LS2	67/32	64.80	20	40	13750	600
28L26	A	12	NF168	LS2	72/32	64.72	25	25	11600	658
28L26	A	14	NF16A	LS2	72/32	64.72	25	30	13100	658
28L26	A	16	NF16C	LS2	72/32	64.72	25	35	14325	658
24.5-32	A	16	NF18C	LS2	68/32	72.00	21	35	15400	639
30.5L32	A	16	NF1CB	LS2	70/32	72.50	27	30	16400	788
30.5L32	A	20	NF1AA	LS2	70/32	72.50	27	35	17950	821
18.4-34	A	10	NF1N6	LS2	64/32	66.80	16	30	8950	414
18.4-34	A	16	NF1H2	LS2	64/32	66.80	16			418
18.4-26	B	10	NF2A6	LS1	51/32	58.80	16	30	7950	264

**\*\*ALL PRODUCTS MANUFACTURED BY SPECIALTY TIRES OF AMERICA, INC. ARE MADE IN THE USA.**

**OUR PLANTS ARE LOCATED IN INDIANA, PA AND UNICO, TN.**

# IMPLEMENT(I-1 RIB) - TUBELESS

## LOW COST HIGH FLOTATION FARM WAGON TIRE

- \* A wide tire for broad load distribution and maximum flotation.
- \* For free rolling wheels on all kinds of farm equipment.
- \* High flotation reduces soil compaction and crop damage.
- \* Multi-rib tread guards against side slippage and enables the tire to grip in any terrain and maintain directional stability.
- \* Smooth ribs eliminate stone drilling which can cause tire failure when under load.



SIZE	LOAD RANGE PR	PRODUCT CODE	TREAD DEPTH	SECTION WIDTH	OVERALL DIAMETER	RIM WIDTH	MAXIMUM INFLATION	MAXIMUM LOAD	WEIGHT
9.5L-14SL	D/8	FC1A5	11/32	9.70	29.60	7.00	44	2400	26
11L-14SL	D/8	FA3V5	11/32	10.50	30.00	8.00	36	2800	29
9.5L-15SL	C/6	FC1C3	11/32	9.70	30.50	7.00	32	2320	25
9.5L-15SL	D/8	FC1C5	11/32	9.70	30.50	7.00	44	2470	27
9.5L-15SL	F/12	FA3C9	11/32	9.70	30.50	7.00	64	3200	32
*9.5L-15FI	D/8	FA3DB	9/32	9.70	30.50	7.00	44	2670	32
11L-15SL	D/8	FC1D5	10/32	10.50	31.40	8.00	36	2540	30
11L-15SL	E/10	FC1D7	10/32	10.50	31.40	8.00	44	2910	34
11L-15SL	F/12	FC1D9	10/32	10.50	31.40	8.00	52	3200	37
*11L-15FI	D/8	FA3DC	8/32	10.50	31.40	8.00	60	3120	38
12.5L-15SL	D/8	FC1E5	12/32	12.20	33.00	10.00	36	3000	38
12.5L-15SL	E/10	FC1E7	12/32	12.20	33.00	10.00	44	3420	40
12.5L-15SL	F/12	FC1E9	12/32	12.20	33.00	10.00	52	3860	42
12.5L-15SL	H/16	FC1ED	12/32	12.20	33.00	10.00	60	4200	49
12.5L-15SL	L/20	FC1CT	12/32	12.20	33.00	10.00	68	4515	52
*12.5L-15FI	D/8	FA3DE	11/32	12.20	33.00	10.00	60	3740	48
*12.5L-15FI	F/12	FA3DF	11/32	12.20	33.00	10.00	90	4680	51
11L-16SL	D/8	FC1F5	10/32	10.20	31.40	8.00	36	2680	31
12.5L-16SL	F/12	FC1H9	12/32	11.40	33.40	10.00	52	3960	45
12.5L-16SL	G/14	FC1HB	12/32	11.40	33.40	10.00	56	4180	45

MAX SPEED 25 MPH

\* MAXIMUM SPEED 55 MPH

# IMPLEMENT (I-1 RIB) - TUBE TYPE

SIZE	LOAD RANGE PR	PRODUCT CODE	TREAD DEPTH	SECTION WIDTH	OVERALL DIAMETER	RIM WIDTH	MAXIMUM INFLATION	MAXIMUM LOAD	WEIGHT
9.5L-14SL	D/8	FC1A6	11/32	9.70	29.60	7.00	44	2400	23
11L-14SL	C/6	FA3V4	11/32	10.50	30.00	8.00	28	2040	25
11L-14SL	D/8	FA3V6	11/32	10.50	30.00	8.00	36	2800	25
11L-14SL	E/10	FA3V8	11/32	10.50	30.00	8.00	44	3170	29
9.5L-15SL	D/8	FC1C6	11/32	9.70	30.50	7.00	44	2470	24
9.5L-15SL	E/10	FC1C8	11/32	9.70	30.50	7.00	52	3180	26
9.5L-15SL	F/12	FC1CA	11/32	9.70	30.50	7.00	56	3280	28
11L-15SL	D/8	FC1D6	10/32	10.50	31.40	8.00	36	2540	26
11L-15SL	F/12	FC1DA	10/32	10.50	31.40	8.00	52	3200	33
12.5L-15SL	D/8	FC1E6	12/32	12.20	33.00	10.00	36	3000	34
12.5L-15SL	E/10	FC1E8	12/32	12.20	33.00	10.00	44	3420	36
12.5L-15SL	G/14	FC1EC	12/32	12.20	33.00	10.00	56	4060	38
11L-16SL	D/8	FC1F6	10/32	10.20	31.40	8.00	36	2680	27
11L-16SL	F/12	FC1FA	10/32	10.20	31.40	8.00	52	3850	34
12.5L-16SL	E/10	FC1H8	12/32	11.40	33.40	10.00	44	3520	38
12.5L-16SL	F/12	FC1HA	12/32	11.40	33.40	10.00	52	3960	41
12.5L-16SL	G/14	FC1HC	12/32	11.40	33.40	10.00	56	4180	41

MAX SPEED 25 MPH

TYPE FI TIRES : LOADS CAN BE INCREASED BY 20% FOR SPEEDS UNDER 30 MPH.



# RIB IMPLEMENT(I-1) - TUBELESS

## LOW COST FARM WAGON TIRE



FIGURE A

- \* A conventional size tire for many applications.
- \* For free rolling wheels on all kinds of farm equipment.
- \* Multi-rib tread guards against side slippage and enables the tire to grip in any terrain and maintain directional stability.
- \* Smooth ribs eliminate stone drilling which can cause tire failure when under load.



FIGURE B



FIGURE C



FIGURE D



FIGURE E



FIGURE F

SIZE	FIGURE	LOAD RANGE PR	PRODUCT CODE	TREAD DEPTH	SECTION WIDTH	OVERALL DIAMETER	RIM WIDTH	MAXIMUM INFLATION	MAXIMUM LOAD	WEIGHT
20.5/8-10	E	F/12	DE3M7	10/32	8.20	20.20	6.00	105	2275	20
26/12-12	D	B/4	FA3DW	12/32	12.00	26.20	10.50	20	1550	26
26/12-12	D	F/12	FA3DY	12/32	12.00	26.20	10.50	75	2750	35
7.50-14SL	B	B/4	FB1Y1	10/32	7.60	26.80	5.50	28	1360	18
4.00-15SL	A	B/4	FA3EA	6/32	4.00	23.50	3.00	44	785	10
5.00-15SL	A	B/4	FA3J1	7/32	5.10	24.90	3.00	36	965	13
6.40-15SL	A	B/4	FA3BE	8/32	6.40	26.90	4.50	32	1170	18
6.70-15SL	A	B/4	FC1X1	8/32	7.30	28.00	4.50	32	1280	19
7.60-15SL	A	C/6	FC113	10/32	7.60	28.50	5.50	40	1760	22
7.60-15SL	A	D/8	FC115	10/32	7.60	28.50	5.50	52	2090	22
10.00-15SL	C	D/8	FA395	13/32	11.00	33.70	8.00	40	3000	41
10.00-15SL	C	F/12	FA399	13/32	11.00	33.70	8.00	56	3960	47
7.50-16SL	F	D/8	FA3N5	13/32	7.98	29.89	5.50	44	2200	27
7.50-20SL	A	E/10	FA3BF	11/32	7.60	35.00	5.50	52	2600	33

MAX SPEED 25 MPH

# IMPLEMENT (I-1 RIB) - TUBE TYPE

SIZE	FIGURE	LOAD RANGE PR	PRODUCT CODE	TREAD DEPTH	SECTION WIDTH	OVERALL DIAMETER	RIM WIDTH	MAXIMUM INFLATION	MAXIMUM LOAD	WEIGHT
5.90-15SL	A	B/4	FA3AH	9/32	6.30	26.60	4.50	36	1140	15
6.70-15SL	A	B/4	FC1X2	8/32	7.30	28.00	4.50	32	1280	16
6.70-15SL	A	C/6	FC1X4	8/32	7.30	28.00	4.50	44	1610	19
7.60-15SL	A	C/6	FC114	10/32	7.60	28.50	5.50	40	1760	19
7.60-15SL	A	D/8	FC116	10/32	7.60	28.50	5.50	52	2090	20
6.00-16SL	A	C/6	FA3L6	7/32	6.10	28.50	4.00	44	1520	18
6.50-16SL	A	C/6	FA3M4	11/32	7.10	28.80	4.50	44	1710	20
7.50-16SL	F	D/8	FA3N6	14/32	7.50	30.00	5.50	48	2710	24
9.00-16SL	A	E/10	FA3AW	11/32	9.20	33.40	6.00	52	3300	35
4.00-18SL	A	B/4	FA3AX	6/32	4.40	26.40	3.00	44	880	11
7.50-18SL	A	C/6	FA3W4	10/32	8.00	32.90	5.50	36	2040	23
4.00-19SL	A	B/4	FA3AE	18/32	4.50	29.00	3.00	44	940	13
7.50-20SL	A	C/6	FA3AM	11/32	7.60	35.00	5.50	36	2410	27

MAX SPEED 25 MPH



## RIB IMPLEMENT (I-1) - TUBELESS

### LOW COST-HIGH FLOTATION-FARM WAGON TIRE

- \* Multi-rib tread guards against side slippage and enables the tire to grip in any terrain and maintain directional stability.
- \* Smooth ribs eliminate stone drilling which can cause tire failure when under load.
- \* Tubeless-Bias Construction.
- \* A wide tire for broad load distribution and maximum flotation.
- \* High flotation reduces soil compaction and crop damage.



## RIB IMPLEMENT (I-1) - TUBELESS

SIZE	LOAD RANGE PR	PRODUCT CODE	TREAD DEPTH	SECTION WIDTH	OVERALL DIAMETER	RIM WIDTH	MAXIMUM INFLATION	MAXIMUM LOAD	WEIGHT
14L16.1SL	D/8	FA3Z5	12/32	13.70	37.00	11.00	32	3860	52
14L16.1SL	F/12	FA3Z9	12/32	13.70	37.00	11.00	44	4680	58
16.5L16.1SL	D/8	FA335	15/32	16.60	40.50	14.00	28	4400	74
16.5L16.1SL	E/10	FA337	15/32	16.60	40.50	14.00	36	5200	83
16.5L16.1SL	G/14	FA33B	15/32	16.60	40.50	14.00	48	6400	89
16.5L16.1SL	H/16	FA33D	15/32	16.60	40.50	14.00	56	7003	102
19L16.1SL	E/10	FA347	16/32	19.00	42.40	16.00	32	6000	102
21.5L16.1SL	E/10	FA3AB	18/32	21.50	44.50	18.00	28	6600	111
21.5L16.1SL	G/14	FA3AC	18/32	21.50	44.50	18.00	36	7850	133

MAX SPEED 25 MPH

## RIB IMPLEMENT (I-1) - TUBE TYPE

SIZE	LOAD RANGE PR	PRODUCT CODE	TREAD DEPTH	SECTION WIDTH	OVERALL DIAMETER	RIM WIDTH	MAXIMUM INFLATION	MAXIMUM LOAD	WEIGHT
14L16.1SL	F/12	FA3ZA	12/32	13.70	37.00	11.00	44	4680	53

MAX SPEED 25 MPH



### WARNING

There is a danger of serious injury or death if a tire of one bead diameter is installed on a rim or wheel of a different rim diameter. Always replace a tire with another tire of exactly the same bead diameter designation and suffix letters. For example: A 16" tire goes on a 16" rim. **NEVER** mount a 16" tire on 16.1" or 16.5" rim. A 16.1 tire goes on a 16.1" rim. **NEVER** mount a 16.1" tire on a 16" or 16.5" rim. A 16.5" tire goes on a 16.5" rim. **NEVER** mount a 16.5" tire on a 16" or 16.1" rim.



## IMPLEMENT (HF-1) - TUBELESS



SIZE	LOAD RANGE PR	PRODUCT CODE	TREAD DEPTH	SECTION WIDTH	OVERALL DIAMETER	RIM WIDTH	MAXIMUM INFLATION	MAXIMUM LOAD	WEIGHT
25/7.50-15	C/6	TBA				5.50	45	1230	
27/9.50-15	C/6	TBA				7.00	45	1610	
27/9.50-15	D/8	TBA				7.00	60	1870	
31/13.50-15	D/8	FB3BN	12/32	13.50	32.40	13.00	45	2760	52

## FLOTATION IMPLEMENT(I-2) - TUBELESS



SIZE	LOAD RANGE PR	PRODUCT CODE	TREAD DEPTH	SECTION WIDTH	OVERALL DIAMETER	RIM WIDTH	MAXIMUM INFLATION	MAXIMUM LOAD	WEIGHT
13.50-16.1SL	E/10	FA327	19/32	14.00	40.00	11.00	40	4940	79
13.50-16.1SL	F/12	FA329	19/32	14.00	40.00	11.00	44	5200	80
16.5L-16.1SL	C/6	FA833	18/32	16.40	42.25	14.00	24	3960	79
16.5L-16.1SL	E/10	FA837	18/32	16.40	42.25	14.00	36	5200	87

MAX SPEED 25 MPH



### WARNING

There is a danger of serious injury or death if a tire of one bead diameter is installed on a rim or wheel of a different rim diameter. Always replace a tire with another tire of exactly the same bead diameter designation and suffix letters. For example: A 16" tire goes on a 16" rim. **NEVER** mount a 16" tire on 16.1" or 16.5" rim. A 16.1 tire goes on a 16.1" rim. **NEVER** mount a 16.1" tire on a 16" or 16.5" rim. A 16.5" tire goes on a 16.5" rim. **NEVER** mount a 16.5" tire on a 16" or 16.1" rim.



## FARM FRONT (F1 SINGLE RIB)



### TUBE TYPE

SIZE	LOAD RANGE PR	PRODUCT CODE	TREAD DEPTH	SECTION WIDTH	OVERALL DIAMETER	RIM WIDTH	MAXIMUM INFLATION	MAXIMUM LOAD	WEIGHT
7.50-16SL	D/8	FA2N4	32/32	8.15	32.00	5.50	56	1710	29
10.00-16SL	D/8	FA2P6	24/32	11.20	35.15	8.00	44	2340	48
7.50-18SL	C/6	FA2W4	32/32	7.81	34.30	5.50	44	1610	32
7.50-20SL	C/6	FA2AM	32/32	8.48	37.50	5.50	44	1710	40
7.50-20SL	F/12	FA2DJ	32/32	8.34	37.50	5.50	72	2280	52

### TUBELESS

SIZE	LOAD RANGE PR	PRODUCT CODE	TREAD DEPTH	SECTION WIDTH	OVERALL DIAMETER	RIM WIDTH	MAXIMUM INFLATION	MAXIMUM LOAD	WEIGHT
11.00-16SL	D/8	FA2T5	27/32	13.24	38.41	10.00	40	2600	47

### "AMERICAN FARMER" FARM TIRE SCHOLARSHIP

Each year Specialty Tires of America awards the "American Farmer" Farm Tire Scholarship to a student with a declared major in Agricultural Engineering at Penn State University. Preference is given to students with interests in engineering design, analysis and field testing of agricultural machinery.



# TRACTOR (R-1)



FIGURE A



FIGURE B



FIGURE C

\* MAXIMUM TRACTION

\* CONSTRUCTED FOR DURABILITY

\* NYLON CORD FOR LONG SERVICE LIFE

SIZE	FIGURE	LOAD RANGE PR	PRODUCT CODE	TREAD DEPTH	SECTION WIDTH	OVERALL DIAMETER	RIM WIDTH	MAXIMUM INFLATION	MAXIMUM LOAD	WEIGHT
6-12		B/4	TBA				5.00	28	600	
7-16	A	B/4	FA1BL	28/32	7.01	29.20	6.00	26	893	22
7-16	A	C/6	FA1BW	28/32	7.01	29.20	6.00	40	1135	24
7-16 *	A	C/6	FA1EW	28/32	7.01	29.20	6.00	40	1135	24

\* Tubeless

## DRIVE WHEEL (R-1) - TUBE TYPE

SIZE	FIGURE	LOAD RANGE PR	PRODUCT CODE	TREAD DEPTH	SECTION WIDTH	OVERALL DIAMETER	RIM WIDTH	MAXIMUM INFLATION	MAXIMUM LOAD	WEIGHT
18.4-16.1	C	C/6	FA1DA	40/32	18.40	44.80	16.00	16	2810	115
18.4-16.1*	C	D/8	FA1AL	40/32	18.40	44.80	16.00	20	2910	126
18.4-38	B	D/8	FA1DH	43/32	18.82	68.25	16.00	20	5360	235

MAXIMUM SPEED 25 MPH

\* Tubeless

# TRACTION IMPLEMENT (I-3) - TUBELESS

\* OPEN CURVED DESIGN FOR EXCELLENT SELF CLEANING

\* DEEP TREAD PATTERN FOR MAXIMUM TRACTION

\* NYLON CONSTRUCTION FOR DURABILITY AND LONG SERVICE LIFE



FIGURE D



FIGURE E



FIGURE F

SIZE	FIGURE	LOAD RANGE PR	PRODUCT CODE	TREAD DEPTH	SECTION WIDTH	OVERALL DIAMETER	RIM WIDTH	MAXIMUM INFLATION	MAXIMUM LOAD	WEIGHT
5.00-15SL	D	B/4	FA5J1	15/32	5.60	25.20	3.00	36	965	16
5.90-15SL	D	B/4	TBA				4.50	36	1140	
*7.60-15SL	D	B/4	FA512	17/32	7.90	30.00	5.50	28	1390	22
7.60-15SL	D	C/6	FA513	17/32	7.90	30.00	5.50	40	1930	27
12.5L-15SL	E	C/6	FA5E3	20/32	12.30	34.30	10.00	28	2540	46
12.5L-15SL	E	F/12	FA5E9	20/32	12.30	34.30	10.00	52	3860	53
16.5L-16.1SL	F	C/6	FA533	23/32	16.10	41.50	14.00	24	3960	105
16.5L-16.1SL	F	E/10	FA537	23/32	16.10	41.50	14.00	36	5200	108
21.5-16.1 SL	F	E/10	FA5AB	33/32	21.50	45.25	18.00	28	6600	154
21.5-16.1 SL	F	G/14	FA5AC	33/32	21.50	45.25	18.00	36	7850	172
*7.50-20 SL		C/6	TBA				5.50	36	2090	

\* Tube type



# SPECIALTY TIRES OF AMERICA INC.

MANUFACTURING QUALITY TIRES IN THE USA SINCE 1915

ANNOUNCES A NEW LINE OF TIRES AVAILABLE 2008  
TO ORDER CALL 1-800-622-7327

## REAR TIRE R-1

Size	P/R	TL/TT
9.5-24	6	TT
11.2-24	6	TL
12.4-24	6	TL
14.9-24	6	TL
14.9-24	8	TL
18.4-26	6	TT
11.2-28	6	TL
12.4-28	6	TL
13.6-28	6	TL
14.9-28	6	TL
16.9-28	8	TL
16.9-30	8	TL
18.4-30	8	TL
9.5-32	6	TT
12.4-32	6	TL
16.9-34	8	TL
18.4-34	8	TL
9.5-36	6	TT
13.6-36	6	TT
13.6-38	6	TT
15.5-38	8	TL
16.9-38	8	TL
18.4-38	8	TL
20.8-38	8	TL
9.5-42	6	TT
12.4-42	10	TL



**\*\*ALL PRODUCTS MANUFACTURED BY SPECIALTY TIRES OF AMERICA, INC. ARE MADE IN THE USA.**

# FARM FRONT (F2M)

DESIGN TO MEET SPECIAL FARM USE  
FOR FRONT STEER POSITIONS ON  
AGRICULTURE EQUIPMENT.



## FARM FRONT (F-2 M FOUR RIB) - TUBELESS

SIZE	LOAD RANGE PR	PRODUCT CODE	TREAD DEPTH	SECTION WIDTH	OVERALL DIAMETER	RIM WIDTH	MAXIMUM INFLATION	MAXIMUM LOAD	WEIGHT
11L-15L	D/8	FA6D5	29/32	10.90	31.80	8.00	44	2090	51
10.00-16SL	D/8	FA6P5	28/32	11.30	34.90	8.00	44	2340	54
11.00-16SL	D/8	FA6T5	31/32	12.00	37.60	10.00	40	2600	61
14L-16.1SL	C/6	FA3Z3	32/32	13.90	38.40	11.00	28	2540	82
14L-16.1SL	E/10	FA3Z7	32/32	13.90	38.90	11.00	44	3420	89

## FARM FRONT (F2 M FOUR RIB) TUBE TYPE

SIZE	LOAD RANGE PR	PRODUCT CODE	TREAD DEPTH	SECTION WIDTH	OVERALL DIAMETER	RIM WIDTH	MAXIMUM INFLATION	MAXIMUM LOAD	WEIGHT
11L-15L	D/8	FA6D6	29/32	10.90	31.80	8.00	44	2090	51
10.00-16SL	D/8	FA6P6	28/32	11.30	34.90	8.80	44	2340	54
11.00-16SL	D/8	FA6T6	31/32	12.00	37.60	10.00	40	2600	61
14L-16.1SL	C/6	FA3Z4	32/32	13.90	38.40	11.00	28	2540	75



# FARM FRONT ( F 2 )



FIGURE A



FIGURE B

## FARM FRONT (F-2 TRIPLE RIB) TUBELESS

SIZE	FIGURE	LOAD RANGE PR	PRODUCT CODE	TREAD DEPTH	SECTION WIDTH	OVERALL DIAMETER	RIM WIDTH	MAXIMUM INFLATION	MAXIMUM LOAD	WEIGHT
7.5L15SL	A	C/6	FA4B3	24/32	8.00	29.90	6.00	44	1430	32
9.5L15SL	A	D/8	FA4C5	30/32	9.50	31.20	7.00	48	1870	37
6.50-16SL	A	C/6	FA4M3	21/32	7.00	30.30	4.50	48	1230	26
7.50-16SL	A	C/6	FA4N3	23/32	7.90	32.10	5.50	44	1480	35
10.00-16SL	A	C/6	FA4P3	29/32	10.30	35.20	8.00	32	1930	49
10.00-16SL	A	D/8	FA4P5	29/32	10.30	35.20	8.00	44	2340	49
11.00-16SL	A	D/8	FA4T5	33/32	12.20	38.40	10.00	40	2600	68

## FARM FRONT(F-2 TRIPLE RIB) TUBE TYPE

SIZE	FIGURE	LOAD RANGE PR	PRODUCT CODE	TREAD DEPTH	SECTION WIDTH	OVERALL DIAMETER	RIM WIDTH	MAXIMUM INFLATION	MAXIMUM LOAD	WEIGHT
9.00-10SL	B	F/12	FA45A	17/32	9.20	27.40	6.00	60	2695	30
4.00-12SL	A	B/4	FA482	14/32	4.60	21.30	3.00	52	495	8
4.00-15SL	A	B/4	FA4AK	6/32	4.80	24.20	3.00	52	585	8
5.00-15SL	A	B/4	FC2J2	13/32	5.20	26.20	3.00	44	715	13
7.5L-15SL	A	C/6	FC2B4	24/32	8.00	29.90	6.00	44	1430	32
9.5L-15SL	A	D/8	FA4C6	30/32	9.50	31.20	7.00	48	1870	37
11L-15SL	A	D/8	FC2D6	30/32	10.40	33.40	8.00	44	2090	46
5.50-16SL	A	B/4	FC2K2	17/32	6.10	28.50	4.00	40	855	18
5.50-16SL	A	C/6	FC2K4	17/32	6.10	28.50	4.00	56	1050	19
6.00-16SL	A	B/4	FC2L2	15/32	6.50	29.10	4.00	36	910	20
6.00-16SL	A	C/6	FC2L4	15/32	6.50	29.10	4.00	52	1140	21
6.50-16SL	A	C/6	FC2M4	21/32	7.00	30.30	4.50	48	1230	26
7.50-16SL	A	C/6	FC2N4	23/32	7.90	32.10	5.50	44	1480	35
7.50-16SL	A	D/8	FC2N6	23/32	7.90	32.10	5.50	56	1710	36
10.00-16SL	A	C/6	FC2P4	29/32	10.30	35.20	8.00	32	1930	49
10.00-16SL	A	D/8	FC2P6	29/32	10.30	35.20	8.00	44	2340	49
11.00-16SL	A	D/8	FC2T6	33/32	12.20	38.40	10.00	40	2600	68
7.50-18SL	A	C/6	FC2W4	25/32	7.90	33.90	5.50	44	1610	38
4.00-19SL	A	B/4	FA4AE	9/32	4.40	28.30	3.00	52	715	12
7.50-20SL	A	C/6	FA4AM	23/32	7.90	36.80	5.50	44	1710	44

MAXIMUM SPEED 25 MPH



# INDUSTRIAL RIB F-3



FIGURE A



FIGURE B



FIGURE C



FIGURE D



FIGURE E

\*STEERING AXLE SERVICE ON TRACTORS AND BACKHOES IN INDUSTRIAL SERVICE

\* 5 RIB TREAD

\* DEEP SAWTOOTH GROOVES

\* WIDE FOOTPRINT

\* 14-PLY RATING AVAILABLE

SIZE	FIGURE	LOAD RANGE PR	PRODUCT CODE	TREAD DEPTH	SECTION WIDTH	OVERALL DIAMETER	RIM WIDTH	MAXIMUM INFLATION	MAXIMUM LOAD	WEIGHT
9.00-10SL	A	8	FA956	11/32	9.20	26.30	6.00	48	1570	22
9.00-10SL	A	10	FA958	11/32	9.20	26.30	6.00	60	1820	25
11L-15SL	D	10	FA9D7	16/32	11.00	31.80	8.00	52	2340	40
11L-15SL	D	14	FA9DB	16/32	11.00	31.80	8.00	68	2710	49
11L-16SL	E	10	FA4F7	16/32	11.00	33.00	8.00	52	2470	42
11L-16SL	E	14	FA4FB	16/32	11.00	33.00	8.00	72	2930	53
11.00-16SL	C	12	FA9T9	15/32	12.40	38.10	10.00	60	3420	53
14.5/75-16.1SL	B	10	FA46W	16/32	15.50	36.80	11.00	40	3200	65

MAXIMUM SPEED 25 MPH

# TURF TRACTION R-3 TUBELESS



\* EXCELLENT FLOTATION

\* LIMITED SOIL COMPACTION

\* DEPENDABLE TRACTION

SIZE	LOAD RANGE PR	PRODUCT CODE	TREAD DEPTH	SECTION WIDTH	OVERALL DIAMETER	RIM WIDTH	MAXIMUM INFLATION	MAXIMUM LOAD	WEIGHT
21.5L-16.1SL	C/6	FA7BK	30/32	20.69	44.16	18.00	12	2760	147
21.5L-16.1SL	E/10	FA7AB	30/32	20.69	44.16	18.00	22	3900	157

MAXIMUM SPEED 25 MPH



# HF-3 TRACTION



FIGURE A



FIGURE B

SIZE	FIGURE	LOAD RANGE PR	PRODUCT CODE	TREAD DEPTH	SECTION WIDTH	OVERALL DIAMETER	RIM WIDTH	MAXIMUM INFLATION	MAXIMUM LOAD	WEIGHT
48/25.00-20	A	E/10	FB2DM	40/32	24.40	52.00	20.50	35	6150	307
48/31.00-20	B	F/12	FB2DN	40/32	30.00	52.50	26.00	40	6950	360



## WARNING

There is a danger of serious injury or death if a tire of one bead diameter is installed on a rim or wheel of a different rim diameter. Always replace a tire with another tire of exactly the same bead diameter designation and suffix letters. For example: A 16" tire goes on a 16" rim. **NEVER** mount a 16" tire on 16.1" or 16.5" rim. A 16.1 tire goes on a 16.1" rim. **NEVER** mount a 16.1" tire on a 16" or 16.5" rim. A 16.5" tire goes on a 16.5" rim. **NEVER** mount a 16.5" tire on a 16" or 16.1" rim.



# MINING SPECIAL



**\*CONSTRUCTION AND COMPOUNDS SPECIFICALLY DESIGNED FOR THE MINING AND MATERIAL HANDLING INDUSTRIES**

SIZE	PLY RATING	PRODUCT CODE	TREAD DEPTH	SECTION WIDTH	OVERALL DIAMETER	RIM WIDTH	WEIGHT
10.00-20NHS	14	DP5H6	25/32	11.40	42.00	7.50	131
10.00-20NHS	16	DP5H7	25/32	11.40	42.00	7.50	138
12.00-20NHS	16	DP5H8	28/32	12.00	44.20	8.50	175
12.00-20NHS	20	DP5H9	28/32	12.00	44.20	8.50	189
12.00-20 NHS	28	DP5HJ	28/32	12.00	44.20	8.50	206
42X13-20NHS	28	DP5KE	25/32	13.00	42.00	9.50	176
42X13-20NHS	32	DP5KF	25/32	13.00	42.00	9.50	193

# NEW MINE SPECIAL



**\*RUGGED DESIGN AND CONSTRUCTION WITH COMPOUNDING FOR SUPERIOR PERFORMANCE ON MINING EQUIPMENT**

SIZE	PLY RATING	PRODUCT CODE	TREAD DEPTH	SECTION WIDTH	OVERALL DIAMETER	RIM WIDTH	WEIGHT
36x11-15 NHS	14	DP5CX	24/32	10.90	36.00	7.50	115
36x11-15 NHS	16	DP5EL	24/32	10.90	36.00	7.50	124
36x11-15 NHS	24	DP5EM	24/32	10.90	36.00	7.50	133
32X15-15 NHS	24	DP5DW	24/32	13.30	32.00	11.50	136
32X15-15 NHS	32	DP5D5	24/32	13.30	32.00	11.50	144
*36X15-15 NHS	16	DP5MA	24/32	13.30	36.00	11.50	
36X15-15 NHS	24	DP5MC	24/32	13.30	36.00	11.50	184
11.00-15 NHS	16	DP5FA	29/32	11.60	38.00	11.50	140
38X16-15 NHS	28	DP5ME	29/32	16.50	38.00	11.50	194
38X16-15 NHS	32	DP5CW	29/32	16.50	38.00	11.50	205
44X18-20 NHS	24	DP5HL	38/32	18.30	43.90	15.00	304
44X18-20 NHS	32	DP5HY	38/32	18.30	43.90	15.00	328
*44X21-20 NHS	32	DP2M5	38/32	21.30	43.90	18.00	365
14.00-20 NHS	24	DP5MF	32/32	15.80	49.50	10.00	278
14.00-20 NHS	32	DP5MK	32/32	15.80	49.50	10.00	305
50X20-20 NHS	32	DP5KD	32/32	19.80	51.40	15.00	313
50X20-20 NHS	36	DP5KN	32/32	19.80	51.40	15.00	414

# BIG JAKE<sup>®</sup> MINER



FIGURE A



FIGURE B



FIGURE C

SIZE	FIGURE	PLY RATING	PRODUCT CODE	TREAD DEPTH	SECTION WIDTH	OVERALL DIAMETER	RIM WIDTH	WEIGHT
12-16.5 NHS	A	12	DB6DP	40/32	13.00	32.90	9.75	95
33/15.50-16.5 NHS	B	12	DB6F8	33/32	15.10	33.20	9.75	114
35/15-15 NHS	B	24	DB6HP	33/32	14.60	35.40	10.50	180
35/15-15 NHS	B	32	DB6K8	33/32	14.60	35.40	10.50	204
9.00-20 NHS	C	16	DB6B9	26/32	10.07	40.90	7.00	128

# SUPERLUG<sup>®</sup> HEAVY DUTY



SIZE	PLY RATING	PRODUCT CODE	TREAD DEPTH	SECTION WIDTH	OVERALL DIAMETER	RIM WIDTH	WEIGHT
*18X7-8 NHS	8	DP2A5	18/32	6.60	18.00	4.33	20
18X7-8 NHS	12	DP2A6	18/32	6.60	18.00	4.33	21
18X7-8 NHS	16	DP2A7	18/32	6.60	18.00	4.33	23
*18X8-8 NHS	14	DP2AD	18/32	8.10	18.00	5.50	24
18X9-8 NHS	16	DP2AA	18/32	9.10	18.10	7.00	27
6.90-9 NHS	10	DP2B3	19/32	6.30	21.40	5.50	23
21X8-9 NHS	12	DP2BD	19/32	8.20	21.10	6.00	28
21X9-9 NHS	12	DP2B8	19/32	9.00	21.10	7.00	30
6.50-10 NHS	10	DP2C3	20/32	7.00	23.40	5.00	27
6.50-10 NHS	12	DP2L4	20/32	7.00	23.40	5.00	27
*7.50-10 NHS	14	DP2DE	25/32	8.20	25.00	5.50	53
7.50-10 NHS	16	DP2FC	25/32	8.20	25.00	5.50	53
21X8-10 NHS	14	DP2CM	32/32	8.10	20.80	6.50	45
23X8-10 NHS	10	DP2CL	20/32	7.80	23.40	6.50	31
23X9-10 NHS	16	DP2BF	20/32	8.30	23.40	6.50	40
27X9-10 NHS	16	DP2DD	25/32	9.50	26.70	6.50	73
27X15-10 NHS	20	DP2AP	34/32	14.50	27.70	14.50	164
7.00-12 NHS	12	DP2D1	30/32	7.20	26.60	7.20	50
23X10-12 NHS	14	DP2AL	25/32	10.10	23.00	10.10	51
23X10-12 NHS	18	DP2AN	25/32	10.10	23.00	10.10	63
24X12-12 NHS	24	DP2M9	25/32	11.50	23.50	11.50	76
27X10-12 NHS	12	DP2AJ	30/32	9.80	27.00	9.80	77
250-15 NHS	20	DP2BH	30/32	9.50	28.70	7.50	88
29X8-15 NHS	12	DP2E4	30/32	7.80	28.70	5.50	62
7.50-15 NHS "32"	12	DP2EA	29/32	8.60	32.00	6.00	76
*7.50-15 NHS "32"	16	DP2D6	29/32	8.60	32.00	6.00	90
*8.25-15 NHS	12	DP2ED	25/32	9.40	33.30	6.50	92
8.25-15 NHS	16	DP2FD	25/32	9.40	33.30	6.50	102
27X12-15 NHS	16	DP2K5	29/32	12.00	26.80	10.00	88
*27X15-15 NHS	24	DP2J5	29/32	15.00	26.80	13.00	114
28X9-15 NHS	12	DP2EW	29/32	9.00	28.00	7.00	74
28X12-15 NHS	20	DP2K3	29/32	12.00	28.00	9.75	98

\* Non-stocking items

# SUPERLUG® HEAVY DUTY (CONTINUED)



FIGURE A



FIGURE B

SIZE	FIGURE	PLY RATING	PRODUCT CODE	TREAD DEPTH	SECTION WIDTH	OVERALL DIAMETER	RIM WIDTH	WEIGHT
28X13-15 NHS	A	20	DP2JA	29/32	13.00	28.00	11.50	103
28X13-15 NHS	A	28	DP2JC	29/32	13.00	28.00	11.50	105
*28X15-15 NHS	A	24	DP2JD	29/32	15.00	28.00	13.00	120
*32X10.5-15 NHS	A	20	DP2JE	28/32	10.40	32.10	8.00	113
32X12.5-15 NHS	A	20	DP2JH	28/32	12.30	32.50	10.00	133
33X11-15 NHS	A	20	DP2K1	25/32	11.00	33.70	8.00	110
*36X11-15 NHS	A	14	DP2FT	34/32	10.90	36.00	7.50	137
*36X11-15 NHS	A	16	DP2EL	34/32	10.90	36.00	7.50	146
36X11-15 NHS	A	22	DP2FX	34/32	10.90	36.00	7.50	154
35X15-15 NHS	A	16	DP2EN	33/32	14.60	35.40	10.50	179
35X15-15 NHS	A	24	DP2HP	33/32	14.60	35.40	10.50	207
35X15-15 NHS	A	32	DP2K8	33/32	14.60	35.40	10.50	218
8.25-20 NHS	A	12	DP2H2	32/32	9.70	39.00	6.50	126
*10.00-20 NHS	A	14	DP2H6	32/32	11.50	42.90	7.50	167
10.00-20 NHS	A	16	DP2H7	32/32	11.50	42.90	7.50	172
12.00-20 NHS	A	16	DP2H8	34/32	12.40	45.00	8.50	211
*12.00-20 NHS	A	24	DP2HH	34/32	12.40	45.00	8.50	240
39X11.5-20 NHS	A	20	DP2D7	31/32	10.60	39.30	8.00	161
44X18-20 NHS	A	24	DP2HL	33/32	18.00	44.20	15.00	297
44X18-20 NHS	A	32	DP2HY	33/32	18.00	44.20	15.00	317
12.00-24 NHS	B	20	DF8BM	30/32	13.00	49.60	8.50	204
12.00-24 NHS	B	24	DF8HW	30/32	13.00	49.60	8.50	206

\* Non-stocking items

# SUPERLUG® SMOOTH



FIGURE C

SIZE	FIGURE	PLY RATING	PRODUCT CODE	TREAD DEPTH	SECTION WIDTH	OVERALL DIAMETER	RIM WIDTH	WEIGHT
*36X11-15 NHS	C	14	DP4FT	34/32	10.90	36.00	7.50	137
12.00-20 NHS	C	16	DP4H8	34/32	12.40	45.00	8.50	205
*12.00-20 NHS	C	24	DP4HH	34/32	12.40	45.00	8.50	258

\* Non-stocking items

# STA TRAXION<sup>®</sup>



FIGURE A



FIGURE B



FIGURE C



FIGURE D

SIZE	FIGURE	PLY RATING	PRODUCT CODE	TREAD DEPTH	SECTION WIDTH	OVERALL DIAMETER	RIM WIDTH	WEIGHT
26X12-12 NHS	A	4	DE1DM	23/32	12.00	25.80	10.50	27
26X12-12 NHS	A	8	DE1DP	23/32	12.00	25.80	10.50	31
26X12-12 NHS	A	12	DE1DT	23/32	12.00	25.80	10.50	33
31X15.50-15 NHS	A	8	DJ1F4	23/32	14.70	31.00	13.00	58
31X15.50-15 NHS	A	12	DJ1M6	23/32	14.70	31.00	13.00	60
33X12.50-15 NHS	C	8	DE1M3	21/32	13.00	32.60	10.00	51

## LOADER

SIZE	FIGURE	PLY RATING	PRODUCT CODE	TREAD DEPTH	SECTION WIDTH	OVERALL DIAMETER	RIM WIDTH	WEIGHT
27X8.50-15 NHS	D	4	DP7FR	16/32	8.10	26.70	7.00	28
27X8.50-15 NHS	D	6	DP7MB	16/32	8.10	26.70	7.00	30
27X10.50-15 NHS	D	6	DP7MR	16/32	10.00	27.00	8.00	36
10-16.5 NHS	D	6	DP7D4	20/32	10.00	30.40	8.25	41
*10-16.5 NHS	D	6	DP8D4	20/32	10.00	30.40	8.25	46
10-16.5 NHS	D	8	DP7DM	20/32	10.00	30.40	8.25	42
10-16.5 NHS	D	10	DP7DN	20/32	10.00	30.40	8.25	43
12-16.5 NHS	D	8	DP7DJ	23/32	12.10	32.70	9.75	54
*12-16.5 NHS	D	8	DP8DJ	23/32	12.10	32.70	9.75	63
12-16.5 NHS	D	10	DP7DL	23/32	12.10	32.70	9.75	56

\* STEEL BELTED

## CHEVRON

SIZE	FIGURE	PLY RATING	PRODUCT CODE	TREAD DEPTH	SECTION WIDTH	OVERALL DIAMETER	RIM WIDTH	WEIGHT
7.00-15SS	B	6	DD1E1	20/32	7.80	29.00	5.50	28
*7.00-15SS	B	6	DD2E1	20/32	7.80	29.00	5.50	33

\* STEEL BELTED

# BIG JAKE<sup>®</sup> SKID STEER

- \* HEAVY DUTY CONSTRUCTION
- \* SIDEWALL GUARDS

- \* EXTRA DEEP TREAD
- \* TUBELESS



FIGURE A  
SKID STEER



FIGURE B  
DEEP TRACTION

SIZE	FIGURE	PLY RATING	PRODUCT CODE	TREAD DEPTH	SECTION WIDTH	OVERALL DIAMETER	RIM WIDTH	WEIGHT
10-16.5NHS *	A	6	DB3D4	32/32	10.66	30.59	7.25	66
10-16.5NHS *	A	8	DB3DM	32/32	10.66	30.59	7.25	67
10-16.5NHS +	A	10	DB3DN	32/32	10.66	30.59	7.25	69
12-16.5NHS *	A	8	DB3DJ	40/32	13.00	32.90	9.75	91
12-16.5 NHS	A	10	DB3DL	40/32	13.00	32.90	9.75	93
12-16.5 NHS	A	12	DB3DP	40/32	13.00	32.90	9.75	96
10-16.5 NHS	B	10	TBA	26/32				
12-16.5 NHS	B	12	TBA	29/32				
33/15.5-16.5 NHS	B	12	DHDF8	29/32	14.46	32.90	9.75	91

- \* *Non-stocking item*
- + *Steel Belted Available*

**\*\*ALL PRODUCTS MANUFACTURED BY SPECIALTY TIRES OF AMERICA, INC. ARE MADE IN THE USA.  
OUR PLANTS ARE LOCATED IN INDIANA, PA AND UNICOI, TN.**

# STA SUPERLUG<sup>®</sup>



SIZE	PLY RATING	PRODUCT CODE	TREAD DEPTH	SECTION WIDTH	OVERALL DIAMETER	RIM WIDTH	WEIGHT
*14-17.5 NHS	8	DB1ML	25/32	13.50	36.30	10.50	78
14-17.5 NHS	10	DB1MM	25/32	13.50	36.30	10.50	84
15-19.5 NHS	8	DB1MP	25/32	15.30	40.00	12.00	108
15-19.5 NHS	12	DB1MT	25/32	15.30	40.00	12.00	119
15-19.5 NHS	14	DB1NL	25/32	15.30	40.00	12.00	135

\*Non-stocking items

# INDUSTRIAL DEEP LUG<sup>®</sup>



LUG DESIGN FOR INDUSTRIAL VEHICLES AND COUNTER-BALANCED FORKLIFT TRUCKS

SIZE	PLY RATING	PRODUCT CODE	TREAD DEPTH	SECTION WIDTH	OVERALL DIAMETER	RIM WIDTH	WEIGHT
5.70-8 NHS	8	DF9A4	17/32	5.70	18.50	4.50	13
*5.70-8 NHS	10	DF9AV	17/32	5.70	18.50	4.50	14
*6.90-9 NHS	6	DF9B1	19/32	6.50	21.50	5.50	21
6.90-9 NHS	10	DF9B3	19/32	6.50	21.50	5.50	20
6.90-9 NHS	12	DF9BE	19/32	6.50	21.50	5.00	22
6.50-10 NHS	10	DF9C3	20/32	7.00	23.60	5.50	25
7.50-10 NHS	10	DF9C5	21/32	7.90	25.50	5.50	31
7.50-10 NHS	12	DF9C6	21/32	7.90	25.50	5.50	35
*7.50-10 NHS	16	DF9DF	21/32	7.90	25.50	5.50	44
7.00-12 NHS	12	DF9D1	20/32	7.40	27.00	5.00	36
*7.00L-15 NHS	10	DF9DX	20/32	7.30	29.10	5.50	38
7.00L-15 NHS	12	DF9E4	20/32	7.30	29.10	5.50	43
*7.50-15 NHS "30"	10	DF9E7	21/32	7.60	30.60	6.00	48
7.50-15 NHS "30"	12	DF9E8	21/32	7.60	30.60	6.00	48
*7.50-15 NHS "32"	10	DF9E9	20/32	8.10	31.70	6.00	51
7.50-15 NHS "32"	12	DF9EA	20/32	8.10	31.70	6.00	52
28X9-15 NHS	12	DF9EC	20/32	8.60	27.30	7.00	41
*8.25-15 NHS	8	DF9BM	21/32	9.30	33.20	6.50	57
8.25-15 NHS	12	DF9EE	21/32	9.30	33.20	6.50	63

\*Non-stocking items

# DYNA TRAC<sup>®</sup>



FIGURE A



FIGURE B

## RIB DESIGN FOR INDUSTRIAL VEHICLES ON SMOOTH FLOORS AND RUNWAYS

SIZE	FIGURE	PLY RATING	PRODUCT CODE	TREAD DEPTH	SECTION WIDTH	OVERALL DIAMETER	RIM WIDTH	WEIGHT
**4.80-8 NHS	A	4	DC3AX	6/32	4.80	16.10	3.75	7
4.80-8 NHS	A	6	DC3A1	6/32	4.80	16.10	3.75	6
5.70-8 NHS	A	6	DC3A3	7/32	5.80	18.20	4.50	9
5.70-8 NHS	A	8	DC3A4	7/32	5.80	18.20	4.50	9
5.70-8 NHS	A	12	DC3AY	7/32	5.80	18.20	4.50	14
6.90-9 NHS	A	4	DC3BL	11/32	6.90	21.40	5.50	12
6.90-9 NHS	A	6	DC3B1	11/32	6.90	21.40	5.50	14
6.90-9 NHS	A	8	DC3B2	11/32	6.90	21.40	5.50	15
6.90-9 NHS	A	10	DC3B3	11/32	6.90	21.40	5.50	17
6.50-10 NHS	A	4	DC5BN	12/32	7.00	23.50	5.00	15
6.50-10 NHS	A	6	DC5C1	12/32	7.00	23.50	5.00	18
**6.50-10 NHS	A	6	DC5NM	12/32	7.00	23.50	5.00	18
6.50-10 NHS	A	8	DC5C2	12/32	7.00	23.50	5.00	18
**6.50-10 NHS	A	8	DC5NP	12/32	7.00	23.50	5.00	19
6.50-10 NHS	A	10	DC5C3	12/32	7.00	23.50	5.00	20
9.00-10 NHS	B	10	DC3NB	10/32	9.40	27.00	6.00	30
9.00-10 NHS	B	12	DC3LA	10/32	9.40	27.00	6.00	36

\*\* Tubeless

## HEAVY DUTY



FIGURE C



FIGURE D

SIZE	FIGURE	PLY RATING	PRODUCT CODE	TREAD DEPTH	SECTION WIDTH	OVERALL DIAMETER	RIM WIDTH	WEIGHT
*5.70-8 NHS	C	8	DC1A4	7/32	5.80	18.20	4.50	13
*6.90-9 NHS	D	10	DC1B3	11/32	6.40	21.30	5.50	18
*6.50-10 NHS	D	10	DC1C3	12/32	7.20	23.90	5.00	22
*7.00-12 NHS	D	12	DC1D1	21/32	7.50	27.10	5.00	35

\* Non-stocking item

**\*\*ALL PRODUCTS MANUFACTURED BY SPECIALTY TIRES OF AMERICA, INC. ARE MADE IN THE USA. OUR PLANTS ARE LOCATED IN INDIANA, PA AND UNICOI, TN.**

# FLAPS

PRODUCT CODE	SIZE	WEIGHT	
ZF500	8-5.7	1.0	
ZF501	9-6.7	2.0	
ZF502	10-6.7	2.0	
ZF503	12-6.0	2.0	
ZF504	15-12.0	6.0	
ZF505	15-8.0	3.0	
ZF506	16-6.7 LT		
ZF507	16-7.1 LT		
ZF508	16-7.0	3.1	
ZF509	17-7.0		
ZF510	20-7.0	4.0	
ZF512	20-8.0	5.0	
ZF513	22-8.0		
ZF514	24-8.0	6.0	
ZF515	8-4.0		
ZF516	8-7.0	2.0	
ZF517	9-8.0	2.0	
ZF518	15-10.0	5.0	
ZF519	15-8.3		
ZF521	20-14.0	11.0	
ZF522	10-11.5	3.0	
ZF524	24-9.0	7.0	
ZF525	18-7.0		
ZF526	15-7.1		
ZF527	12-8.2	3.0	
ZF528	22-15.0		
ZF529	20-10.0		

# AMERICAN COMPACTOR C-1



SIZE	PLY RATING	PRODUCT CODE	TREAD DEPTH	SECTION WIDTH	OVERALL DIAMETER	RIM WIDTH	WEIGHT
7.50-15	6	DECD8	11/32	9.40	30.50	6.00	37
7.50-15	12	DECE3	11/32	9.40	30.50	6.00	46
9.00-20	16	DHCB9	16/32	10.75	39.60	7.00	103
11.00-20	16	DHCFE	16/32	11.60	41.61	8.00	151
13.00-24	14	DHCC8	64/32	11.90	49.80	10.00	206

# BIG JAKE<sup>®</sup> CHOCK HAULER



SIZE	PLY RATING	PRODUCT CODE	TREAD DEPTH	SECTION WIDTH	OVERALL DIAMETER	RIM WIDTH	WEIGHT
48/25-22	32	DCBJN	48/32	25.00	48.00	18.00	552
48/25-22	50	DCBJP	48/32	25.00	48.00	18.00	613

**\*\*ALL PRODUCTS MANUFACTURED BY SPECIALTY TIRES OF AMERICA, INC. ARE MADE IN THE USA. OUR PLANTS ARE LOCATED IN INDIANA, PA AND UNICOI, TN.**

# STA SUPER TRANSPORT

\* Light truck tire for pick-ups, vans, campers and motor homes.

\* Five-rib design for long mileage.

\* Cool running for over the highway light truck use.

\* Wide profile for flotation and traction.



FIGURE A



FIGURE B



FIGURE C



FIGURE D



FIGURE E



FIGURE F

## SUPER TRANSPORT WB - TUBELESS

SIZE	FIGURE	RANGE PLY RATING	PRODUCT CODE	TREAD DEPTH	SECTION WIDTH	OVERALL DIAMETER	RIM WIDTH	MAXIMUM LOAD AND INFLATION				WEIGHT
								DUAL LOAD	INFLATION	SINGLE LOAD	INFLATION	
8.00-16.5LT	A	D/8	LA4A5	16/32	7.90	28.60	6.00	1800	60	2045	60	33
8.75-16.5LT	A	D/8	LA4B5	16/32	9.00	29.80	6.75	2070	60	2350	60	37
8.75-16.5LT	A	E/10	LA4B7	16/32	9.00	29.80	6.75	2360	75	2680	75	40
9.50-16.5LT	A	D/8	LA4C5	17/32	9.30	30.60	6.75	2445	60	2780	60	41
9.50-16.5LT	A	E/10	LA4C7	17/32	9.30	30.60	6.75	2790	75	3170	75	44
10-16.5LT	A	D/8	LA4D5	17/32	10.20	30.40	8.25	2420	60	2750	60	42
12-16.5LT	A	D/8	LA4E5	18/32	11.90	32.20	9.75	2640	45	3000	45	52
12-16.5LT	D	E/10	LC3E7	18/32	11.90	32.20	9.75	3120	60	3550	60	58
12-16.5LT	D	F/12	LC3EL	18/32	11.90	32.20	9.75	3560	75	4045	75	59
8-17.5LT	A	D/8	LA565	14/32	8.00	31.40	6.00	2155	60	2455	60	36

SIZE	FIGURE	RANGE PLY RATING	PRODUCT CODE	TREAD DEPTH	SECTION WIDTH	OVERALL DIAMETER	RIM WIDTH	MAXIMUM LOAD AND INFLATION				WEIGHT
								DUAL LOAD	INFLATION	SINGLE LOAD	INFLATION	
E78-14LT	A	D/8	LA3A5	15/32	7.70	26.50	5.50	1500	60	1710	60	28
G78-15LT	A	C/6	LA3B3	15/32	8.20	28.20	6.00	1460	45	1660	45	32
H78-15LT	A	C/6	LA3C3	16/32	8.60	29.00	6.00	1610	45	1830	45	34
L78-15LT	C	C/6	LF8H3	16/32	9.10	29.90	6.50	1790	45	2030	45	37

## SUPER TRANSPORT LT - TUBELESS

SIZE	FIGURE	RANGE PLY RATING	PRODUCT CODE	TREAD DEPTH	SECTION WIDTH	OVERALL DIAMETER	RIM WIDTH	MAXIMUM LOAD AND INFLATION				WEIGHT
								DUAL LOAD	INFLATION	SINGLE LOAD	INFLATION	
8-14.5 LT	A	F/12	LA5TH	14/32	8.50	28.20	6.00	NA	NA	2790	100	40
8-14.5 LT	A	G/14	LA5TJ	14/32	8.50	28.20	6.00	NA	NA	3020	115	41
9-14.5LT	B	G/14	LA5J6	12/32	9.20	28.00	7.00	3080	115	3505	115	42
6.70-15LT	E	C/6	LA113	15/32	7.40	28.50	5.00	1355	45	1530	45	27
7.00-15LT	A	C/6	LA223	15/32	7.90	29.60	5.50	1520	45	1720	45	32
7.00-15LT	A	D/8	LA225	15/32	7.90	29.60	5.50	1800	60	2040	60	32
6.50-16LT	E	C/6	LA133	12/32	7.40	29.90	4.50	1420	45	1610	45	28
7.50-16LT	A	D/8	LA245	15/32	8.70	32.00	6.00	2140	60	2440	60	37
7.50-16LT	A	E/10	LA247	15/32	8.70	32.00	6.00	2440	75	2780	75	45

Specialty Tires of America produced tires are designed to be used with rims having the dimensions of those shown as "approved rims" for the tire size in the Tire and Rim Association Yearbook, current at the time of tire manufacture. Use of other rims must be specifically approved by Specialty Tires of America, 1600 Washington Street, Indiana, PA 15701

# STA SUPER TRANSPORT

\* Light truck tire for pick-ups, vans, campers and motor homes.

\* Cool running for over the highway light truck use.

\* Five-rib design for long mileage.

\* Wide profile for flotation and traction.



FIGURE A



FIGURE B



FIGURE C



FIGURE D

## SUPER TRANSPORT LT - TUBE TYPE

SIZE	FIGURE	RANGE PLY RATING	PRODUCT CODE	TREAD DEPTH	SECTION WIDTH	OVERALL DIAMETER	RIM WIDTH	MAXIMUM LOAD AND INFLATION				WEIGHT
								DUAL LOAD	INFLATION	SINGLE LOAD	INFLATION	
7.00-15LT	A	C/6	LA224	15/32	7.90	29.60	5.50	1520	45	1720	45	29
7.00-15LT	A	D/8	LA226	15/32	7.90	29.60	5.50	1800	60	2040	60	29
6.50-16LT	D	C/6	LA134	12/32	7.40	29.90	4.50	1420	45	1610	45	24
7.50-16LT	A	D/8	LA246	15/32	8.70	32.00	6.00	2140	60	2440	60	34
7.50-17LT	B	D/8	LA5J7	16/32	8.50	34.50	6.00	2460	65	2800	75	39
7.00-18LT	C	D/8	LA5J9	16/32	7.90	33.80	5.50	2270	65	2350	65	37
7.50-20	D	E/10	MA2A2	13/32	8.90	37.40	6.00	3100	80	3530	90	54

Specialty Tires of America produced tires are designed to be used with rims having the dimensions of those shown as "approved rims" for the tire size in the Tire and Rim Association Yearbook, current at the time of tire manufacture. Use of other rims must be specifically approved by Specialty Tires of America, 1600 Washington Street, Indiana, PA 15701.

# STA SUPER TRAXION<sup>®</sup>

- \* Light truck tire for pick-ups, vans, campers and motor homes.
- \* Great traction with husky lugs.
- \* Pinned for studs.
- \* Minimum stone retention.
- \* Cool running with deep vented shoulders.
- \* Wide profile for flotation and traction.



FIGURE A



FIGURE B



FIGURE C

## SUPER TRAXION<sup>®</sup> WB - TUBELESS

SIZE	FIGURE	RANGE PLY RATING	PRODUCT CODE	TREAD DEPTH	SECTION WIDTH	OVERALL DIAMETER	RIM WIDTH	MAXIMUM LOAD AND INFLATION				WEIGHT
								DUAL LOAD	INFLATION	SINGLE LOAD	INFLATION	
8.00-16.5LT	A	D/8	LB4A5	17/32	8.10	28.90	6.00	1800	60	2045	60	31
8.75-16.5LT	A	D/8	LB4B5	18/32	8.80	29.90	6.75	2070	60	2350	60	38
8.75-16.5LT	A	E/10	LB4B7	18/32	8.80	29.90	6.75	2360	75	2680	75	38
9.50-16.5LT	A	D/8	LB4C5	18/32	9.50	31.10	6.75	2445	60	2780	60	40
10-16.5LT	A	D/8	LB4D5	20/32	10.20	30.70	8.25	2420	60	2750	60	44
12-16.5LT	A	D/8	LB4E5	21/32	11.90	32.80	9.75	2640	45	3000	45	53
12-16.5LT	A	E/10	LB4E7	21/32	11.90	32.80	9.75	3120	60	3550	60	57
8-17.5LT	B	D/8	LB565	14/32	8.00	31.40	6.00	2155	60	2455	60	45

## SUPER TRAXION<sup>®</sup> LT(78 SERIES) - TUBELESS

SIZE	FIGURE	RANGE PLY RATING	PRODUCT CODE	TREAD DEPTH	SECTION WIDTH	OVERALL DIAMETER	RIM WIDTH	MAXIMUM LOAD AND INFLATION				WEIGHT
								DUAL LOAD	INFLATION	SINGLE LOAD	INFLATION	
E78-14LT	A	D/8	LB3A5	16/32	7.60	26.60	5.50	1500	60	1710	60	28.0
G78-15LT	A	C/6	LB3B3	17/32	8.20	28.50	6.00	4650	45	1660	45	32.0
H78-15LT	A	C/6	LB3C3	18/32	8.50	29.20	6.00	1610	45	1830	45	35.0
L78-15LT	A	D/8	LB3H5	18/32	9.00	30.00	6.50	2120	65	2400	65	37.0

## SUPER TRAXION<sup>®</sup> LT - TUBELESS

SIZE	FIGURE	RANGE PLY RATING	PRODUCT CODE	TREAD DEPTH	SECTION WIDTH	OVERALL DIAMETER	RIM WIDTH	MAXIMUM LOAD AND INFLATION				WEIGHT
								DUAL LOAD	INFLATION	SINGLE LOAD	INFLATION	
7.00-15LT	A	C/6	LB223	18/32	7.9	30.00	5.50	1520	45	1720	45	30
7.50-16LT	A	D/8	LB245	18/32	8.7	32.20	6.00	2140	60	2440	60	37

## SUPER TRAXION<sup>®</sup> LT - TUBE TYPE

SIZE	FIGURE	RANGE PLY RATING	PRODUCT CODE	TREAD DEPTH	SECTION WIDTH	OVERALL DIAMETER	RIM WIDTH	MAXIMUM LOAD AND INFLATION				WEIGHT
								DUAL LOAD	INFLATION	SINGLE LOAD	INFLATION	
7.00-15LT	A	C/6	LB224	18/32	7.90	29.60	5.50	1520	45	1720	45	30
7.00-15LT	A	D/8	LB226	18/32	7.90	30.00	5.50	1800	60	2040	60	31
6.50-16LT	C	C/6	LB134	19/32	7.20	30.20	4.50	1420	45	1610	45	32
7.50-16LT	A	D/8	LB246	18/32	8.70	32.20	6.00	2140	60	2440	60	37
7.50-18LT		D/8					6.00	2550	65	2800	75	

Specialty Tires of America produced tires are designed to be used with rims having the dimensions of those shown as "approved rims" for the tire size in the Tire and Rim Association Yearbook, current at the time of tire manufacture. Use of other rims must be specifically approved by Specialty Tires of America, 1600 Washington Street, Indiana, PA 15101

**\*\*ALL PRODUCTS MANUFACTURED BY SPECIALTY TIRES OF AMERICA, INC. ARE MADE IN THE USA.  
OUR PLANTS ARE LOCATED IN INDIANA, PA AND UNICOI, TN.**

# STA MILITARY TIRES

\* Jeeps and military vehicles.

\* Non-directional tread design provides equal traction in either side.

\* General purpose tire for cranes, shovels and dump trucks.



NDT



NDCC



DIRECTIONAL

## NON-DIRECTIONAL NDT SERIES

SIZE	LOAD RANGE PR	PRODUCT CODE	TREAD DEPTH	RIM WIDTH	SECTION WIDTH	OVERALL DIAMETER	MAXIMUM INFLATION	MAXIMUM LOAD	WEIGHT
7.50-10NHS	B/4	DN1L2	9/32	6.00	8.30	24.80	40	2260	21
6.00-16	B/4	LN1W2	16/32	4.50	6.70	28.60	30	1130	21
6.00-16	C/6	LN1W4	16/32	4.50	6.70	28.60	45	1430	22
7.00-16	C/6	LN174	17/32	5.50	7.60	31.80	45	1800	29
7.50-16	D/8	LN146	17/32	6.00	8.50	32.50	60	2440	32
7.50-16	E/10	LN148	17/32	6.00	8.50	32.50	75	2780	37
9.00-16	D/8	LN18E	18/32	7.00	10.20	35.50	50	2665	48
7.50-20	D/8	ML4AB	17/32	6.00	9.00	38.50	60	3330	49
8.25-20	F/12	ML4B4	19/32	6.50	9.50	39.50	100	2060	60
9.00-20	F/12	ML4C4	20/32	7.00	10.60	40.70	95	5150	72
11.00-20	G/14	ML4E6	20/32	8.00	11.90	43.00	100	6590	110
12.00-20	G/14	HL4F6	20/32	8.50	12.50	44.80	90	7000	113
12.00-20	H/16	HL4F8	20/32	8.50	12.50	44.80	105	7740	114
12.00-20	J/18	HL4FA	20/32	8.50	12.50	44.80	115	8210	128

## NON-DIRECTIONAL NDCC SERIES

SIZE	LOAD RANGE PR	PRODUCT CODE	TREAD DEPTH	RIM WIDTH	SECTION WIDTH	OVERALL DIAMETER	MAXIMUM INFLATION	MAXIMUM LOAD	WEIGHT
7.00-15	C/6	LN124	16/32	5.50	7.80	29.50	45	1720	25
7.00-16	C/6	LN27C	17/32	5.50	7.60	31.10	45	1800	29
9.00-20	D/8	ML5CB	19/32	7.00	9.80	41.20	65	4000	63
11.00-20	F/12	ML5E4	22/32	8.00	10.00	43.50	85	5920	93
14.00-20	G/14	HL5M6	24/32	10.00	15.00	49.50	50	6410	121
14.00-20	L/20	HL5MC	24/32	10.00	15.00	49.50	95	9960	173
14.00-20NHS	G/14	DN2LY	24/32	10.00	15.20	49.50	54	11435	113
14.00-20NHS	L/20	DN2LX	24/32	10.00	15.20	49.50	102	16500	146

## DIRECTIONAL SERIES

SIZE	LOAD RANGE PR	PRODUCT CODE	TREAD DEPTH	RIM WIDTH	SECTION WIDTH	OVERALL DIAMETER	MAXIMUM INFLATION	MAXIMUM LOAD	WEIGHT
10.50-16	D/8	LA7TA	20/32	6.50	10.50	38.20	50	3030	59

# STA TRAILBREAKER®

BUILT SPECIFICALLY TO PERFORM ON:

- \* 4 X 4'S
- \* VANS
- \* PICK-UPS

- \* Bold aggressive tread for on-off road use.
- \* Deep cleats for extra mileage and greater traction in rough going.
- \* Raised white outline letters.
- \* Heavy sipes for extra traction.
- \* Tubeless.



SIZE	LOAD RANGE PR	PRODUCT CODE	TREAD DEPTH	RIM WIDTH	SECTION WIDTH	OVERALL DIAMETER	MAXIMUM INFLATION	MAXIMUM LOAD	WEIGHT
L78-15LT	C/6	LF3HC	17/32	6.50	9.10	29.90	45	2030	37
10-15LT	C/6	LF2HC	21/32	8.00	10.60	30.40	45	2230	41
11-15LT	C/6	LF2JC	21/32	8.00	11.40	30.70	45	2410	45
12-15LT	C/6	LF2KC	21/32	10.00	13.00	32.10	30	2250	52
35X14.5-15LT	C/6	LF2PC	23/32	11.50	13.70	34.80	30	2725	60
35X14.5-16.5LT	C/6	LF2TC	23/32	11.25	13.20	34.80	30	2845	62
12-16.5LT	D/8	LF2EE	21/32	9.75	12.70	32.60	45	3000	55

## SUPER TRANSPORT / SUPER TRAXION



SUPER TRANSPORT



SUPER TRAXION

SIZE	LOAD RANGE PR	PRODUCT CODE	TREAD DEPTH	RIM WIDTH	SECTION WIDTH	OVERALL DIAMETER	MAXIMUM INFLATION	MAXIMUM LOAD	WEIGHT
<b>SUPER TRANSPORT</b>									
P185/75D14	B	PA1H2	11/32	5.00	6.80	25.50	32	1235	17
P205/75D15	B	PA1Y6	11/32	5.50	7.70	27.10	32	1532	22
<b>SUPER TRAXION</b>									
P185/75D14	B	PA2H2	11/32	5.00	6.80	25.50	32	1235	18
P205/75D15	B	PA2Y6	11/32	5.50	7.70	27.20	32	1532	25

**\*\*ALL PRODUCTS MANUFACTURED BY SPECIALTY TIRES OF AMERICA, INC. ARE MADE IN THE USA. OUR PLANTS ARE LOCATED IN INDIANA, PA AND UNICOI, TN.**

# STA SUPERLUG<sup>®</sup>



## SUPERLUG<sup>®</sup> - Tubeless - Nylon Construction - Raised White Outline Letters

SIZE	LOAD RANGE PR	PRODUCT CODE	TREAD DEPTH	RIM WIDTH	SECTION WIDTH	OVERALL DIAMETER	MAX INFLATION PSI	MAX LOAD	WEIGHT
9.00-16LT	D/8	LT28E	21/32	6.50	10.38	36.30	50	2665(D) 3030(S)	58

(D) = DUAL

(S) = SINGLE

## SUPERLUG<sup>®</sup> - Tube Type - Nylon Construction - Blackwall

SIZE	LOAD RANGE PR	PRODUCT CODE	TREAD DEPTH	RIM WIDTH	SECTION WIDTH	OVERALL DIAMETER	MAX INFLATION PSI	MAX LOAD	WEIGHT
9.00-16LT	D/8	LT286	21/32	6.50	10.38	36.30	50	2665(D) 3030(S)	58
9.00-16LT **	G/14	LT28M	21/32	6.50	10.38	36.30	90	3760(D) 4275 (S)	66

(D) = DUAL

(S) = SINGLE

\*\* TUBELESS

## SUPERLUG<sup>®</sup> SPECIAL ML\*\*

- \* Drive wheel tire for on and off the road service.
- \* Strong carcass - extra ply construction.
- \* Resists cuts and bruises.



SIZE	LOAD RANGE PR	PRODUCT CODE	TREAD DEPTH	RIM WIDTH	SECTION WIDTH	OVERALL DIAMETER	MAXIMUM LOAD AND INFLATION				WEIGHT
							DUAL LOAD	INFLATION	SINGLE LOAD	INFLATION	
12.00-20ML	G/14	HD8A6	26/32	8.50	12.90	45.50	6140	80	6140	80	137
12.00-20ML	H/16	HD2A8	26/32	8.50	12.90	45.50	6790	95	6790	95	138
12.00-20ML	J/18	HD2AA	26/32	8.50	12.90	45.50	7200	105	7200	105	163
11.00-24ML	G/14	MD2M6	26/32	8.00	12.30	47.80	6520	90	6520	90	135
12.00-24ML	H/16	HD2B8	26/32	8.50	13.00	49.60	7640	95	7640	95	168
12.00-24ML	J/18	HD2BA	26/32	8.50	13.00	49.60	7870	100	7870	100	187

\*\* For mining and logging operations. May be used for intermittent highway service where the distance traveled in any 1 1/2 hour period does not exceed 50 miles. Speed should never exceed 50 mph.

Superlug<sup>®</sup> Special ML Tires are available in mold run quantities for the export market only.

**\*\*ALL PRODUCTS MANUFACTURED BY SPECIALTY TIRES OF AMERICA, INC. ARE MADE IN THE USA.  
OUR PLANTS ARE LOCATED IN INDIANA, PA AND UNICOI, TN.**

## WARNING

- **DO NOT, UNDER ANY CIRCUMSTANCES, MOUNT ANY SPECIALTY TIRES OF AMERICA PRODUCED TIRE (“*STA TIRE*”) ON A WHEEL THAT DOES NOT MEET TIRE & RIM ASSOCIATION STANDARDS.**
- **USE OF *STA TIRES* ON WHEELS THAT DO NOT MEET TIRE & RIM ASSOCIATION STANDARDS CAN CAUSE THE ASSEMBLY TO FAIL AND BURST WITH EXPLOSIVE FORCE SUFFICIENT TO CAUSE SERIOUS PERSONAL INJURY OR DEATH.**
- ***STA TIRES* ARE INTENDED TO BE USED EXCLUSIVELY ON TIRE RIMS DESIGNED AND MANUFACTURED TO COMPLY WITH TIRE & RIM ASSOCIATION (“T & RA”) STANDARDS AND SPECIFICATIONS. ANY PERSON USING *STA TIRES* ON WHEELS THAT DO NOT MEET T & RA STANDARDS AND SPECIFICATIONS OR ON DAMAGED WHEELS ASSUMES RESPONSIBILITY FOR THESE DANGEROUS ACTIONS AND AGREES TO REIMBURSE SPECIALTY TIRES OF AMERICA ( AND ITS AFFILIATED COMPANIES) FOR ALL LOSS, DAMAGE, OR COST IT MAY SUFFER BECAUSE OF SUCH ACTIONS.**
- **WHEEL STANDARDS AND SPECIFICATIONS CAN BE OBTAINED BY WRITING TO: TIRE & RIM ASSOCIATION, 175 MONTROSE WEST AVENUE, SUITE 150, COPLEY OHIO 44321 OR BY CONSULTING YOUR RIM MANUFACTURER. CONSULT YOUR RIM MANUFACTURER TO DETERMINE IF YOUR RIM CAN BE USED WITH THE TIRE SELECTED FOR YOUR APPLICATION.**
- **TIRE MOUNTING INSTRUCTIONS –**
  - ✓ **IT IS ABSOLUTELY IMPORTANT THAT TIRE MOUNTING BE PREFORMED BY SPECIALLY TRAINED PERSONNEL USING PROPER TOOLS AND PROCEDURES.**
  - ✓ **FAILURE TO FOLLOW SAFE MOUNTING PROCEDURES CAN RESULT IN FAULTY POSITIONING OF THE TIRE AND CAUSE THE ASSEMBLY TO BURST WITH EXPLOSIVE FORCE SUFFICIENT TO CAUSE SERIOUS PERSONAL INJURY OR DEATH.**
  - ✓ **CLEAN RIM AND LUBRICATE BEADS WITH RUBBER LUBRICANT.**
  - ✓ **ALWAYS LOCK RIM ON MOUNTING MACHINE OR PLACE ASSEMBLY IN SAFETY CAGE. USE AIR HOSE WITH CLIP ON CHUCK AND EXTENSION AIR GAUGE.**
  - ✓ **NEVER EXCEED 40 PSI TO SEAT BEADS ON RIM. EXCESSIVE AIR PRESSURE CAN DAMAGE THE TIRE AND CAUSE IT TO VIOLENTLY BLOW OFF THE WHEEL.**
  - ✓ **THERE IS A DANGER OF SERIOUS INJURY OR DEATH IF A TIRE OF ONE BEAD DIAMETER IS INSTALLED ON A RIM OR WHEEL OF A DIFFERENT RIM DIAMETER. ALWAYS REPLACE A TIRE WITH ANOTHER TIRE OF EXACTLY THE SAME BEAD DIAMETER DESIGNATION AND SUFFIX LETTERS. FOR EXAMPLE, A 16" TIRE MOUNTS ON A 16" RIM. NEVER MOUNT A 16" TIRE ON A 16.1" OR 16.5" RIM. A 16.1" TIRE MOUNTS ON A 16.1" RIM. NEVER MOUNT A 16.1" TIRE ON A 16" OR 16.5" RIM. A 16.5" TIRE MOUNTS ON A 16.5" RIM. NEVER MOUNT A 16.5" TIRE ON A 16" OR 16.1" RIM.**



## STANDARD LIMITED WARRANTY

Every first quality tire of our manufacture bearing our name and serial number and not branded "na" is warranted to be free of defects in workmanship and material during the life of the original tread. Original tread life is completed when the tire is worn to 2 remaining 32nds on highway and 10% remaining 32nds on farm, mining, and industrial tires.

This limited warranty does not cover damage resulting from misuse, improper mounting, misapplication, use of non-approved rims, improper inflation, overloading, running flat, misalignment or imbalance of wheels, rims, defective brakes or shock absorbers, abuse, willful damage, oil, chemical action, fire, or other externally generated heat, use of studs, water or other material entrapped inside the tire, vehicle damage or road hazards (such as rock cuts, punctures, cut separations, impacts, flex breaks.)

If, upon presentation of the tire, our examination shows such a tire is eligible for adjustment credit under the terms of this warranty, we will make a reasonable allowance on the purchase of a new tire based on the current "Specialty Tire Price." Any such allowance will be based on the tread-wear remaining.

The warranty is made for the exclusive benefit of the owner actually using these products and is not assignable. No claim will be recognized unless assigned a returned goods authorization issued by the commercial operations department of Specialty Tires of America and the tire is returned to Specialty Tires of America.

**ALL OTHER WARRANTIES, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, ARE EXPRESSLY DISCLAIMED TO THE EXTENT PERMITTED BY LAW. ALL OBLIGATIONS OR LIABILITIES FOR INDIRECT, INCIDENTAL, PUNITIVE OR CONSEQUENTIAL DAMAGE ARE HEREBY EXCLUDED, INCLUDING ECONOMIC LOSS, LOSS OF PROFIT, LOSS OF USE OF VEHICLE, LOSS OF TIME, PERSONAL INJURY OR DEATH. NO REPRESENTATIVE HAS THE AUTHORITY TO MAKE REPRESENTATIONS, PROMISES OR AGREEMENTS VARYING THE TERMS OF THIS LIMITED WARRANTY.**

Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply.

This warranty gives you specific legal rights, and you may also have other rights that vary from state to state.

Revised August 20, 2007

Unicoi, Tennessee



Specialty Tires of America, Inc., Unicoi, Tennessee — Manufacturing Facility  
Specialty Tires of America, Inc., Indiana, Pennsylvania — General Offices and Factory



---

**MANUFACTURING QUALITY TIRES IN THE USA SINCE 1915**

---

1600 Washington Street, Indiana, Pennsylvania 15701-2844

TOLL FREE: 1-800-622-7327

SALES OFFICE: 724-349-9650

FAX: 724-349-8192

E-Mail: [info@stausaonline.com](mailto:info@stausaonline.com)

WEBSITE: [www.stausaonline.com](http://www.stausaonline.com)