

# RADIAL H107

## High Performance All-Season



### M+S

The H107 is a high performance tire designed for excellent handling in wet and dry conditions. This H-rated tire features tread sipes and an endless center rib which offers solid all-season performance and superior steering response.

- UTQG : 340/A/A



INCH	S-CODE	SIZE	L/I & S/S	MEASURING RIM	RIM WIDTH RANGE	MAXIMUM		OVERALL DIAMETER	SECTION WIDTH	TREAD WIDTH	TREAD DEPTH	REVS/MILE	SIDEWALL TYPE	PRICE
						AIR (PSI)	LOAD (LBS)							
14	1007426	P185/60R14	82H	5.5	5.0 - 6.5	44	1,047	22.7	7.4	5.8	10.0	915	VSB	102.22
	1007424	P195/60R14	85H	6.0	5.5 - 7.0	44	1,168	23.2	7.8	5.4	10.0	895	VSB	105.24
15	1007272	195/55R15	85H	6.0	5.5 - 7.0	44	1,135	23.5	7.9	6.1	10.0	884	VSB	132.88
	1007422	P195/60R15	87H	6.0	5.5 - 7.0	44	1,190	24.2	7.8	5.5	10.0	858	VSB	114.68
	1007427	P205/60R15	90H	6.0	5.5 - 7.5	44	1,301	24.6	8.1	6.5	10.0	844	VSB	120.25
	1007428	P215/60R15	93H	6.5	6.0 - 7.5	44	1,411	25.1	8.6	6.8	10.0	828	VSB	135.40
	1007429	P195/65R15	89H	6.0	5.5 - 7.0	44	1,279	25.0	7.9	5.9	10.0	831	VSB	114.20
	1007423	P205/65R15	92H	6.0	5.5 - 7.5	44	1,400	25.4	8.1	6.3	10.0	818	VSB	119.91
16	1006141	205/45R16 XL	87H	7.0	6.5 - 7.5	50	1,201	23.2	8.2	7.0	10.0	895	VSB	147.56
	1005742	205/50R16	87H	6.5	5.5 - 7.5	51	1,202	24.1	8.3	6.7	10.0	862	VSB	146.00
	1005743	225/50R16	92H	7.0	6.0 - 8.0	51	1,389	24.9	9.0	7.1	10.0	834	VSB	155.16
	1005744	245/50R16	97H	7.5	7.0 - 8.5	51	1,609	25.7	9.8	8.1	10.0	808	VSB	164.48
	1005739	205/55R16	91H	6.5	5.5 - 7.5	51	1,356	24.9	8.4	6.5	10.0	834	VSB	145.66
	1005740	215/55R16	93H	7.0	6.0 - 7.5	51	1,433	25.3	8.9	6.8	10.0	821	VSB	151.51
	1005741	225/55R16	95H	7.0	6.0 - 8.0	51	1,521	25.7	9.1	7.1	10.0	808	VSB	153.72
	1007430	P205/60R16	91H	6.0	5.5 - 7.5	44	1,356	25.7	8.1	6.5	10.0	808	VSB	135.30
	1009727	P215/60R16	94H	6.5	6.0 - 7.5	44	1,477	26.2	8.6	7.4	11.5	792	VSB	141.65
	1007425	P225/60R16	97H	6.5	6.0 - 8.0	44	1,609	26.7	9.0	6.7	10.0	778	VSB	145.32
	1007431	P235/60R16	99H	7.0	6.5 - 8.5	44	1,709	27.2	9.3	7.4	10.0	764	VSB	151.83
	17	1007307	205/45R17 XL	88H	7.0	6.5 - 7.5	50	1,235	24.3	8.1	7.0	10.0	855	VSB
1006137		215/45R17 XL	91H	7.0	7.0 - 8.0	50	1,356	24.6	8.4	7.4	10.0	844	VSB	165.44
1005943		225/45R17 XL	94H	7.5	7.0 - 8.5	50	1,477	24.8	9.1	7.7	10.0	838	VSB	170.27
1006142		235/45R17 XL	97H	8.0	7.5 - 9.0	50	1,609	25.2	9.3	8.0	10.0	824	VSB	177.29
1006143		245/45R17 XL	99H	8.0	7.5 - 9.0	50	1,709	25.7	9.6	8.4	10.0	808	VSB	187.36
1007308		205/50R17 XL	93H	6.5	5.5 - 7.5	50	1,433	25.2	8.3	7.2	10.0	824	VSB	151.33
1005748		215/50R17	91H	7.0	6.0 - 7.5	51	1,356	25.3	9.3	6.8	10.0	821	VSB	171.34
1007309		225/50R17 XL	98H	8.0	6.0 - 8.0	50	1,819	27.1	10.4	8.7	10.0	767	VSB	178.20
1009728		215/55R17	94H	7.0	6.0 - 7.5	51	1,477	26.3	8.9	7.4	10.5	790	VSB	173.10
1005747		225/55R17	97H	7.0	6.0 - 8.0	51	1,609	26.6	9.6	7.1	10.0	781	VSB	178.45
1009729	235/55R17	99H	7.5	6.5 - 8.5	51	1,709	23.2	9.6	8.0	10.5	895	VSB	172.41	
18	1006139	215/35R18 XL	84H	7.5	7.0 - 8.5	50	1,102	23.9	8.6	8.4	10.0	869	VSB	203.27
	1006135	225/40R18 XL	92H	8.0	7.5 - 9.0	50	1,389	25.1	9.1	7.7	10.0	828	VSB	213.98
	1006140	245/40R18 XL	97H	8.5	8.0 - 9.5	50	1,609	25.7	9.6	8.4	11.0	808	VSB	244.05

VSB - Vertical Serrated Band

# RADIAL H715

## Passenger Standard Touring All-Season



**M+S** **80K**  
warranty

H715 provides year-round comfort from highway to drive-way. Footprint Shape Optimization (FSO) technology improves traction and resists uneven treadwear. Carbon Compounding Technology (CCT) provides superior traction while radial kerfs ensure improved performance in rain and snow. Advanced tread design not only ensures superior grip, but a smooth quiet ride as well.

- UTQG : 600/A/B




INCH	S-CODE	SIZE	L/I & S/S	MEASURING RIM	RIM WIDTH RANGE	MAXIMUM		OVERALL DIAMETER	SECTION WIDTH	TREAD WIDTH	TREAD DEPTH	REVS/MILE	SIDEWALL TYPE	PRICE
						AIR (PSI)	LOAD (LBS)							
14	1002780	P175/65R14	81T	5.0	5.0 - 6.0	44	1,019	23.1	7.0	5.9	10.5	899	VSB	99.86
	1002781	P185/65R14	85T	5.5	5.0 - 6.5	44	1,124	23.6	7.3	6.2	10.5	880	VSB	103.26
	1002788	P185/70R14	87T	5.5	4.5 - 6.0	44	1,201	24.4	7.4	6.2	11.0	851	VSB	97.81
	1002789	P195/70R14	90T	6.0	5.0 - 6.5	44	1,312	24.9	8.0	6.5	11.0	834	VSB	112.74
	1002795	P195/75R14	92S	5.5	5.0 - 6.5	44	1,400	25.6	8.0	6.4	11.0	812	WSW	108.21
15	1002782	P185/65R15	86T	5.5	5.0 - 6.5	44	1,168	24.6	7.3	6.2	10.5	844	VSB	111.05
	1002911	P205/70R15	95T	6.0	5.0 - 7.0	44	1,499	26.3	8.3	6.9	11.0	790	WSW	124.53
	1002912	P215/70R15	97T	6.5	5.5 - 7.0	44	1,620	26.9	8.1	7.2	11.5	772	WSW	131.85
	1002797	P205/75R15	97S	5.5	5.0 - 7.0	44	1,598	27.1	8.2	6.7	11.0	767	WSW	121.34
	1002798	P215/75R15	100S	6.0	5.5 - 7.0	44	1,742	27.7	8.6	7.0	11.5	750	WSW	130.92
	1002799	P225/75R15	102S	6.0	6.0 - 7.5	44	1,874	28.3	8.9	7.4	11.5	734	WSW	141.12
	1002800	P235/75R15	105S	6.5	6.0 - 8.0	44	2,028	28.9	9.4	7.7	11.5	719	WSW	145.53
	16	1009755	P205/60R16	91T	6.0	5.5-7.5	44	1,356	25.7	8.1	7.1	11.5	807	VSB
1002778		P215/60R16	94T	6.5	6.0 - 7.5	44	1,477	26.2	8.6	7.4	11.0	793	VSB	152.24
1002779		P225/60R16	97T	6.5	6.0 - 8.0	44	1,609	26.7	8.9	7.8	11.0	778	VSB	160.59
1009756		P205/65R16	94T	6.0	5.5-7.5	44	1,477	26.5	8.2	6.9	12.0	785	VSB	145.77
1002786		P215/65R16	96T	6.5	6.0 - 7.5	44	1,565	27.0	8.7	7.2	11.0	769	VSB	147.24
1009757		P235/65R16	101T	7.0	6.5-8.5	44	1,819	28.1	9.5	7.9	12.5	739	VSB	164.08
17		1009758	P215/60R17	95T	6.5	6.0-7.5	44	1,521	27.2	8.7	7.2	12.0	764	VSB
	1009759	P225/60R17	98T	6.5	6.0-8.0	44	1,653	27.6	9.0	7.8	12.0	752	VSB	183.53
	1009760	P215/65R17	98T	6.5	6.0-7.5	44	1,653	28.0	8.7	7.2	12.0	741	VSB	180.92

VSB : Vertical Serrated Band  
WSW : White Sidewall

# RADIAL RH08

## SUV / Light Truck Sport Performance



### M+S

The Aurora RH08 targets high performance SUVs and sport trucks. Its aggressive tread pattern and sidewall design lend a sporty look. The W-shaped tread is designed for all-season performance and delivers a comfortable ride, superior traction and responsive handling.

- UTQG : 420/A/A




INCH	S-CODE	SIZE	L/I & S/S	MEASURING RIM	RIM WIDTH RANGE	MAXIMUM		OVERALL DIAMETER	SECTION WIDTH	TREAD WIDTH	TREAD DEPTH	REVS/MILE	SIDEWALL TYPE	PRICE
						AIR (PSI)	LOAD (LBS)							
18	1006369	255/55R18 XL	109V	8.0	7.0 - 9.0	50	2,271	29.0	10.3	8.5	11.0	716	VSB	227.75
	1007310	265/60R18	110V	8.0	7.0 - 9.5	44	2,998	30.5	10.7	9.1	11.0	630	VSB	229.99
20	1006372	275/40R20 XL	106V	9.5	9.0 - 11.0	50	2,094	28.7	10.8	9.5	11.0	724	VSB	231.44
	1006374	275/45R20 XL	110V	9.0	8.5 - 10.0	50	2,271	29.8	10.6	9.2	11.0	697	VSB	212.31
	1007298	265/50R20 XL	112V	8.5	7.5 - 9.5	50	2,469	30.5	10.8	8.8	11.0	681	VSB	258.35
	1006371	285/50R20 XL	116V	9.0	8.0 - 10.0	50	2,756	31.3	11.2	9.5	11.0	664	VSB	245.28
	1006367	275/55R20 XL	117V	8.5	7.5 - 9.5	50	2,833	31.9	11.1	9.2	11.0	651	VSB	219.99
22	1006370	265/35R22 XL	102V	9.5	9.0 - 10.5	50	1,874	29.3	10.6	8.8	11.0	709	VSB	232.95
	1006134	305/40R22 XL	114V	11.0	10.0 - 12.0	50	2,601	31.6	12.2	10.5	11.0	657	VSB	276.35
	1007299	285/45R22 XL	114V	9.5	9.0 - 11.0	50	2,601	32.1	11.2	9.5	11.0	647	VSB	306.87
	1006366	305/45R22 XL	118V	10.0	9.5 - 11.0	50	2,910	32.8	11.8	10.6	11.0	633	VSB	268.10

VSB : Vertical Serrated Band

# RADIAL RH04

## SUV / Light Truck Highway All-Season



Intended for highway use on light trucks and SUV's RH04's computer designed tread pattern delivers superb wet traction, while its unique casing profile ensures a smooth, quiet ride.

- UTQG : 440/A/B (P-Metric)



### P-Metric

INCH	S-CODE	SIZE	L/I & S/S	MEASURING RIM	RIM WIDTH RANGE	MAXIMUM		OVERALL DIAMETER	SECTION WIDTH	TREAD WIDTH	TREAD DEPTH	REVS/MILE	SIDEWALL TYPE	PRICE
						AIR (PSI)	LOAD (LBS)							
15	1003441	P235/70R15	102S	7.0	6.0 - 8.0	44	1,896	28.0	9.3	7.0	12.0	742	OWL	176.52
	1003422	P235/75R15	105S	6.5	6.0 - 8.0	44	2,028	28.8	9.2	6.8	12.0	721	OWL	165.19
16	1003423	P225/70R16	101S	6.5	6.0 - 7.5	44	2,271	28.5	8.9	6.7	12.0	729	OWL	186.38
	1003424	P235/70R16	104S	7.0	6.0 - 8.0	44	2,403	29.0	9.3	7.0	12.0	716	OWL	192.75
	1003425	P245/70R16	106S	7.0	6.5 - 8.0	44	2,094	29.5	9.7	7.3	12.0	704	OWL	204.61
	1003426	P255/70R16	109S	7.5	6.5 - 8.5	44	2,271	30.1	10.2	7.6	12.5	690	OWL	213.16
	1003427	P265/70R16	111S	8.0	7.0 - 9.0	44	2,094	30.6	10.7	7.9	12.5	679	OWL	221.93
	1003428	P245/75R16	109S	7.0	6.5 - 8.0	44	1,819	30.5	9.8	7.1	12.0	681	OWL	196.50
	1007595	P265/75R16	114S	7.5	7.0 - 9.0	44	2,601	31.6	10.6	7.6	12.0	657	OWL	214.60
17	1007596	P245/65R17	105S	7.0	7.0 - 8.5	44	2,039	29.5	9.9	7.5	12.0	704	OWL	228.91
	1007597	P235/70R17 XL	108S	7.0	6.0 - 8.0	50	2,205	30.0	9.4	7.2	12.0	692	OWL	225.06
	1007598	P245/70R17	108S	7.0	6.5 - 8.0	44	2,205	30.5	9.7	7.3	12.0	681	OWL	235.19
	1003429	P265/70R17	113S	8.0	7.0 - 9.0	44	1,984	31.9	10.7	8.0	12.5	651	OWL	246.46

OWL : Outline White Letters


### LT-Metric

INCH	S-CODE	SIZE	PLY RATING	MEASURING RIM	RIM WIDTH RANGE	MAXIMUM		OVERALL DIAMETER	SECTION WIDTH	TREAD WIDTH	TREAD DEPTH	REVS/MILE	SIDEWALL TYPE	PRICE
						AIR (PSI)	LOAD (LBS)							
15	2000271	LT235/75R15	6	6.5	6.0-7.0	S 50	1,985	28.8	9.3	6.9	15.0	721	OWL	201.68
						D 50	1,820							
16	2000939	LT225/75R16	10	6.0	6.0-7.0	S 80	2,680	29.3	8.8	6.7	14.5	709	OWL	218.08
						D 80	2,470							
	2000273	LT245/75R16	10	7.0	6.5 - 7.5	S 80	3,042	30.4	9.8	7.2	15.0	683	SBL	235.83
						D 80	2,778							
	2000940	LT265/75R16	10	7.5	7.0 - 8.0	S 80	3,415	31.6	10.5	7.9	15.0	657	OWL	254.86
				D 80	3,085									
2000938	LT215/85R16	10	6.0	5.5 - 7.0	S 80	2,680	30.3	8.5	6.1	14.5	686	OWL	215.43	
				D 80	2,470									
2000275	LT235/85R16	10	6.5	6.0 - 7.5	S 80	3,042	31.7	9.4	6.7	15.0	655	OWL	226.71	
				D 80	2,778									

OWL : Outline White Letters  
SBL : Serrated Black Letters

# ROUTE MASTER AT

## SUV / Light Truck All-Terrain



**M+S** **40K**  
warranty

Standard warranty for P-Metric only.

Route Master AT offers exceptional traction and durability without compromising comfort.

- UTQG : 520/A/B (P-Metric)



### P-Metric

INCH	S-CODE	SIZE	L/I & S/S	MEASURING RIM	RIM WIDTH RANGE	MAXIMUM		OVERALL DIAMETER	SECTION WIDTH	TREAD WIDTH	TREAD DEPTH	REVS/ MILE	SIDEWALL TYPE	PRICE	
						AIR (PSI)	LOAD (LBS)								
15	1012060	P235/75R15 XL	108T	6.5	6-8	50	2,183	28.9	9.3	6.9	12.0	718.85	OWL	190.33	
	16	1012061	P235/70R16	104T	7.0	6-8	51	1,984	29.0	9.5	7.2	12.5	716.81	OWL	207.76
		1012062	P245/70R16	106T	7.0	6-8	51	2,094	29.5	9.8	7.3	12.5	703.46	OWL	220.56
		1012063	P255/70R16	109T	7.5	6.5-8.5	51	2,271	30.1	10.7	7.6	12.5	690.60	OWL	231.88
		1012064	P265/70R16	111T	8.0	7-9	51	2,403	30.6	10.7	8.0	12.5	678.20	OWL	241.43
		1012065	P245/75R16	109T	7.0	6.5-8	51	2,271	30.5	9.8	7.3	12.5	680.82	OWL	217.78
		1012066	P265/75R16	114T	7.5	7-9	51	2,601	31.6	10.5	8.0	12.5	656.34	OWL	233.48
17	1012067	P245/65R17	105T	7.0	7-8.5	51	2,039	29.5	9.8	7.6	12.5	703.46	OWL	246.77	
	1012068	P265/65R17	110T	8.0	7.5-9.5	51	2,337	30.6	10.7	8.1	12.5	679.07	SBL	262.23	
	1012069	P245/70R17	108T	7.0	6.5-8	51	2,205	30.6	9.8	7.3	12.5	679.97	OWL	256.64	
	1012070	P255/70R17	110T	7.5	6.5-8.5	51	2,337	31.1	10.2	7.6	12.5	667.95	OWL	264.34	
	1012071	P265/70R17	113T	8.0	7-9	51	2,535	31.6	10.7	8.0	12.5	656.34	OWL	273.10	
18	1012072	P275/65R18	114T	8.0	7.5-9.5	51	2,601	32.1	11.0	8.4	12.5	646.62	SBL	278.56	

OWL : Outline White Letters  
SBL : Serrated Black Letters

### LT-Metric

INCH	S-CODE	SIZE	PLY RATING	L/I & S/S	MEASURING RIM	RIM WIDTH RANGE	MAXIMUM		OVERALL DIAMETER	SECTION WIDTH	TREAD WIDTH	TREAD DEPTH	REVS/ MILE	SIDEWALL TYPE	PRICE	F.E.T
							AIR (PSI)	LOAD (LBS)								
15	2001796	LT235/75R15	6	104/101R	6.5	6-7	S 50 D 50	1985 1820	28.9	9.3	7.1	16.0	720	OWL	203.02	
	2001809	31X10.50R15	6	109R	8.5	7-9	S 50 D 50	2270 -	30.5	10.5	8.1	16.0	681	OWL	252.80	
16	2001797	LT225/75R16	10	115/112S	6.0	6-7	S 80 D 80	2680 2470	29.3	8.8	6.9	15.5	709	SBL	241.97	
	2001798	LT245/75R16	10	120/116S	7.0	6.5-8	S 80 D 80	3042 2778	30.5	9.8	7.4	16.0	682	SBL	268.76	
	2001799	LT265/75R16	10	123/120R	7.5	7-8	S 80 D 80	3415 3085	31.6	10.5	8.3	16.0	656	SBL	282.29	
	2001800	LT285/75R16	10	126/123R	8.0	7.5-9	S 80 D 80	3750 415	32.8	11.3	8.6	16.0	633	OWL	301.58	2.36
	2001801	LT235/85R16	10	120/116R	6.5	6-7.5	S 80 D 80	3415 3085	31.7	9.3	7.0	16.0	655	SBL	259.63	
17	2001802	LT245/70R17	10	119/116R	7.0	6.5-8	S 80 D 80	3000 2755	30.6	9.8	7.4	16.0	680	SBL	293.41	
	2001803	LT265/70R17	10	121/118S	8.0	7-8.5	S 80 D 80	3195 2910	31.6	10.7	8.1	15.5	656	OWL	306.61	
	2001805	LT245/75R17	10	121/118S	7.0	6.5-7.5	S 80 D 80	3195 2910	31.5	9.8	7.4	15.5	660	OWL	304.24	
	2001806	LT235/80R17	10	120/117R	6.5	6-7.5	S 80 D 80	3085 2835	31.8	9.3	7.1	16.0	653	SBL	295.04	
	2001815	LT285/70R17	10	121/118S	8.5	7.5-9	S 80 D 80	3195 2910	32.8	11.5	8.7	16.0	634	OWL	331.14	
18	2001817	LT275/65R18	10	123/120S	8.0	7.5-9.5	S 80 D 80	3415 3085	32.1	11.0	8.3	16.0	647	SBL	314.71	
	2001818	LT275/70R18	10	125/122S	8.0	7-8.5	S 80 D 80	3640 3305	33.2	11.0	8.3	15.5	626	SBL	317.89	1.32

OWL : Outline White Letters  
OBL : Outline Black Letters

# RADIAL UF03

## Long Haul Steer



Designed with UMS (Ultra Mileage And Safety) technology, the UF03 revolutionizes long-haul applications. UMS optimizes the tire's plyline, yielding the lowest possible belt-edge stress. This advanced construction also provides outstanding footprint pressure distribution – the key to long and even wear.

INCH	S-CODE	SIZE	PLY RATING	MEASURING RIM	RIM WIDTH RANGE	MAXIMUM		OVERALL DIAMETER	SECTION WIDTH	TREAD WIDTH	TREAD DEPTH	REVS/MILE	SIDEWALL TYPE	PRICE	F.E.T.
						AIR (PSI)	LOAD (LBS)								
<b>Tubeless</b>															
	3001336	11R22.5	16	8.25	7.5 - 8.25	S 120 D 120	6,610 6,005	41.3	11.1	8.7	18.0	501.0	SBL	590.30	29.39
	3001338	11R24.5	16	8.25	7.5 - 8.25	S 120 D 120	7,160 6,610	43.4	11.0	8.7	18.0	479.0	SBL	642.03	34.59
<b>75</b>	3001340	295/75R22.5	14	9.0	8.25 - 9.0	S 110 D 100	6,175 5,675	40.2	11.6	8.6	18.0	520.0	SBL	573.11	25.23
	3001339	285/75R24.5	14	8.25	8.25	S 110 D 100	6,175 5,675	41.3	11.0	8.7	18.0	504.0	SBL	623.33	25.23

SBL : Serrated Black Letters

### Recommended Vehicle Types & Position



# RADIAL UF04

## Regional Steer / All-Position



A bold tread provides UF04 excellent driving stability. Asymmetric groove angles help to reduce groove cracks. Uneven abrasion is diminished by the insertion of sipes on the shoulder area. Four straight grooves channel water away for superior traction.

INCH	S-CODE	SIZE	PLY RATING	MEASURING RIM	RIM WIDTH RANGE	MAXIMUM		OVERALL DIAMETER	SECTION WIDTH	TREAD WIDTH	TREAD DEPTH	REVS/MILE	SIDEWALL TYPE	PRICE	F.E.T.
						AIR (PSI)	LOAD (LBS)								

### Tubeless

70	3001345	255/70R22.5	16	7.50	7.5 - 8.25	S 120 D 120	5,510 5,070	36.6	9.8	7.8	17	563	SBL	457.72	18.99
	3001341	11R22.5	14	8.25	7.5 - 8.25	S 105 D 105	6,175 5,840	41.3	11.1	8.7	19	501	SBL	537.84	25.23
	3001343	11R22.5	16	8.25	7.5 - 8.25	S 120 D 120	6,610 6,005	41.3	11.1	8.7	19	503	SBL	553.97	29.39
	3001353	11R24.5	14	8.25	7.5 - 8.25	S 105 D 105	6,610 6,005	43.4	11.0	8.7	18	479	SBL	588.51	29.39
	3001344	11R24.5	16	8.25	7.5 - 8.25	S 120 D 120	7,160 6,610	43.4	11.0	8.7	18	478	SBL	606.18	34.59
75	3001347	295/75R22.5	14	9.00	8.25 - 9.0	S 110 D 110	6,175 5,675	40.1	11.6	8.4	18	520	SBL	537.84	25.23
	3001346	285/75R24.5	14	8.25	8.25	S 110 D 110	6,175 5,675	41.3	10.9	8.5	18	504	SBL	588.51	25.23

SBL : Serrated Black Letters  
\* 11R22.5 14 PLY and 11R24.5 14 PLY

### Recommended Vehicle Types & Position



# RADIAL UZ02

## Closed Shoulder Drive Position




UZ02 is a drive axle position radial tire developed for trucks and buses. A wide and extra deep block tread pattern provide longer tread life, while the varied tread pitch reduces road noise.

INCH	S-CODE	SIZE	PLY RATING	MEASURING RIM	RIM WIDTH RANGE	MAXIMUM		OVERALL DIAMETER	SECTION WIDTH	TREAD WIDTH	TREAD DEPTH	REVS/MILE	SIDEWALL TYPE	PRICE	F.E.T.
						AIR (PSI)	LOAD (LBS)								
<b>Tubeless</b>															
	3001357	11R22.5	14	8.25	7.5 - 8.25	S 105 D 105	6,175 5,840	41.9	10.9	8.0	28	496	SBL	573.85	25.23
	3001358	11R22.5	16	8.25	7.5 - 8.25	S 120 D 120	6,610 6,005	41.9	10.9	8.0	28	496	SBL	591.60	29.39
	3001359	11R24.5	14	8.25	7.5 - 8.25	S 105 D 105	6,610 6,005	43.9	10.8	8.0	27	474	SBL	624.80	29.39
	3001360	11R24.5	16	8.25	7.5 - 8.25	S 120 D 120	7,160 6,610	43.9	10.8	8.0	27	474	SBL	644.14	34.59
<b>75</b>	3001361	285/75R24.5	14	8.25	8.25	S 110 D 110	6,175 5,675	42.0	11.0	7.8	27	509	SBL	624.80	25.23
	3001362	295/75R22.5	14	9.00	8.25 - 9.0	S 110 D 110	6,175 5,675	40.8	11.3	7.8	27	509	SBL	573.85	25.23

SBL : Serrated Black Letters  
\* 11R22.5 14 PLY and 11R24.5 14 PLY

### Recommended Vehicle Types & Position



# RADIAL UF05

## Regional All-Position

INCH	S-CODE	SIZE	PLY RATING	MEASURING RIM	RIM WIDTH RANGE	MAXIMUM		OVERALL DIAMETER	SECTION WIDTH	TREAD WIDTH	TREAD DEPTH	REVS/MILE	SIDEWALL TYPE	PRICE	F.E.T.
						AIR (PSI)	LOAD (LBS)								
19.5	3001351	8R19.5	12	6.00	5.25 - 6.75	S 110 D 110	3,525 3,305	33.7	8.0	5.4	17	616	SBL	349.21	0.19
	3001348	225/70R19.5	12	6.75	6.0 - 6.75	S 95 D 95	3,640 3,415	32.3	8.7	7.0	17	646	SBL	378.74	1.32
	3001349	245/70R19.5	14	7.50	6.75 - 7.5	S 110 D 110	4,940 4,375	33.2	9.7	7.6	17	619	SBL	429.39	9.83
	3001350	265/70R19.5	14	7.50	7.5 - 8.5	S 110 D 110	5,510 5,205	34.3	10.2	8.2	17	607	SBL	479.94	14.84

Tubeless

SBL : Serrated Black Letters

### Recommended Vehicle Types & Position



UF05's overall design fights the elements, prevents uneven treadwear and enhances overall durability. Two-tiered tapered shoulders prevent wandering and deter wear. Multiple sipes and large angle groove walls improve handling and stability. Broad tread design provides outstanding traction in wet driving conditions.

# RADIAL UZ01

## Regional Drive Position

INCH	S-CODE	SIZE	PLY RATING	MEASURING RIM	RIM WIDTH RANGE	MAXIMUM		OVERALL DIAMETER	SECTION WIDTH	TREAD WIDTH	TREAD DEPTH	REVS/MILE	SIDEWALL TYPE	PRICE	F.E.T.
						AIR (PSI)	LOAD (LBS)								
<b>Tubeless</b>															
70	3001207	225/70R19.5	12	6.75	6.0 - 6.75	S 95 D 95	3,640 3,415	32.4	8.8	7.1	19	641	SBL	394.59	1.32
	3001208	245/70R19.5	14	7.50	6.75 - 7.5	S 110 D 110	4,940 4,375	33.4	9.6	7.5	20	622	SBL	447.39	9.83
	3001209	265/70R19.5	14	7.50	7.5 - 8.5	S 110 D 110	5,510 5,205	34.5	10.2	8.1	20	602	SBL	500.06	14.84

SBL : Serrated Black Letters

### Recommended Vehicle Types & Position



A mid- to long-distance radial tire for drive axle position applications. The wide tread pattern design enhances mileage, while the large tread radius improves wear resistance. Grip and wet traction are improved by the use of a wide lug pattern design.

# RADIAL UZ03

## Open Shoulder Drive Position




UZ03's extra-rugged deep tread utilizes a special long-wearing compound that is resistant to cuts, abrasions and stone retention. Its large footprint and aggressive tread design ensure outstanding traction and braking in all weather conditions.

INCH	S-CODE	SIZE	PLY RATING	MEASURING RIM	RIM WIDTH RANGE	MAXIMUM		OVERALL DIAMETER	SECTION WIDTH	TREAD WIDTH	TREAD DEPTH	REVS/MILE	SIDEWALL TYPE	PRICE	F.E.T.
						AIR (PSI)	LOAD (LBS)								
<b>Tubeless</b>															
	3001364	11R22.5	16	8.25	7.5 - 8.25	S 120 D 120	6,610 6,005	41.8	10.9	8.3	26	497	SBL	602.49	29.39
	3001379	11R24.5	16	8.25	7.5 - 8.25	S 120 D 120	7,160 6,610	43.9	10.9	8.3	26	474	SBL	656.07	34.59
<b>75</b>	3001382	295/75R22.5	14	9.00	8.25 - 9.0	S 110 D 110	6,175 5,675	40.6	11.2	7.9	26	511	SBL	584.92	25.23
	3001381	285/75R24.5	14	8.25	8.25	S 110 D 110	6,175 5,675	42.0	10.9	7.9	26	495	SBL	636.96	25.23

SBL : Serrated Black Letters

### Recommended Vehicle Types & Position



# RADIAL UF02

## Low Platform Trailer

INCH	S-CODE	SIZE	PLY RATING	MEASURING RIM	RIM WIDTH RANGE	MAXIMUM		OVERALL DIAMETER	SECTION WIDTH	TREAD WIDTH	TREAD DEPTH	REVS/MILE	SIDEWALL TYPE	PRICE	F.E.T.
						AIR (PSI)	LOAD (LBS)								
17.5	3001384	215/75R17.5	16	6.00	6.0 - 6.75	S 125 D 125	4,805 4,540	30.4	8.3	6.6	16	679	SBL	315.08	12.29
	3001385	235/75R17.5	16	6.75	6.75 - 7.5	S 125 D 125	6,005 5,675	31.5	9.8	7.6	17	670	SBL	371.79	23.63
	3001386	245/70R17.5	16	7.50	6.75 - 7.5	S 125 D 125	6,005 5,675	31.5	9.8	7.6	17	670	SBL	393.94	23.63

Tubeless

SBL : Serrated Black Letters

### Recommended Vehicle Types & Position



Developed for trailers, the UF02 has wide angle grooves in the belt area to reduce stone retention. The 4-groove wide base tread design results in greater durability and performance.

# RADIAL UFO6

## Wide Base Highway


INCH	S-CODE	SIZE	PLY RATING	MEASURING RIM	RIM WIDTH RANGE	MAXIMUM		OVERALL DIAMETER	SECTION WIDTH	TREAD WIDTH	TREAD DEPTH	REVS/MILE	SIDEWALL TYPE	PRICE	F.E.T.
						AIR (PSI)	LOAD (LBS)								

**Tubeless**

<b>65</b>	3001401	385/65R22.5	18	11.75	11.75 - 12.25	S 120	9,370	42.4	15.0	11.0	20	491	SBL	872.04	27.74
	3001388	425/65R22.5	20	13.00	11.75 - 13.00	S 125	11,400	44.3	16.5	12.2	20	465	SBL	1004.51	37.33

SBL : Serrated Black Letters

**Recommended Vehicle Types & Position**



A mid- to long-distance, wide base all-position super single tire. The wide base 4-groove pattern design offers exceptional driving stability and durability. Wide and deep grooves effectively channel away water and the low heat emitting compound boosts tire resilience.

# RADIAL UFO7

## Long Haul Trailer



Five-rib tread design and 4 straight grooves provide straight line stability and superior drainage on wet roads. Advanced construction significantly reduces rolling resistance, minimizes rubber distortion, uneven wear and prevents cracking. Dual tapered shoulder and buttress grooves prevent wandering and irregular wear.

INCH	S-CODE	SIZE	PLY RATING	MEASURING RIM	RIM WIDTH RANGE	MAXIMUM		OVERALL DIAMETER	SECTION WIDTH	TREAD WIDTH	TREAD DEPTH	REVS/MILE	SIDEWALL TYPE	PRICE	F.E.T.
						AIR (PSI)	LOAD (LBS)								
<b>Tubeless</b>															
	3001352	11R22.5	14	8.25	7.5 - 8.25	S 105 D 105	6,175 5,840	41.5	10.9	7.7	13	501	SBL	478.41	25.23
	3001354	11R24.5	14	8.25	7.5 - 8.25	S 105 D 105	6,610 6,005	43.0	10.8	7.7	13	483	SBL	527.22	29.39
<b>75</b>	3001356	295/75R22.5	14	8.25	8.25 - 9.0	S 110 D 110	6,175 5,675	39.9	11.2	7.9	13	520	SBL	478.41	25.23
	3001355	285/75R24.5	14	8.25	8.25	S 110 D 110	6,175 5,675	41.2	10.9	7.9	13	504	SBL	527.22	25.23

SBL : Serrated Black Letters

### Recommended Vehicle Types & Position

