

CARLISLE

TIRE & WHEEL PRODUCT CATALOG



CARLISLE

Carlisle Tire & Wheel Company

SPECIAL TIRES FOR SPECIAL PURPOSES



PRODUCT INDEX – at a glance

Product	Page
A·C·T. All Conditions Tire	.28
A·C·T HD	.29
All Trail/All Trail II	.25
AT101 Chevron	.15
AT489	.23
AT489 X/L	.24
Badlands A/R	.27
Badlands XTR	.27
Fairway Pro	.12
Farm Specialist	.42-46
Fast Trax	.5
Ground Force GSE	.38
Guard Dog/Guard Dog HD	.35
HD Field Trax	.25
Industrial Deep Traction	.40
Inner Tubes	.50-55
Knobby	.26
Links	.12
Mud Wolf	.21
Multi Trac C/S	.4
Multi Trac C/S R-3	.47
Power Trac	.14
Premium Wide Trac	.39
Radial Industrial Flaps	.50-52
Radial Trail	.31
Road Roller	.41

Product	Page
Sawtooth	.7-8
Smooth	.9
Sport Trail	.33
Sport Trail LT	.33
Straight Rib	.10
Stryker	.22
Stud	.8
Super Lug	.13-14
Tour Max	.11
Trac Chief I-3	.47
Trac Chief	.36
Trail Wolf Sport	.19
Trail Wolf	.20
Tru Power	.15
Tubeless Valve Stems	.52
Turf CTR	.6
Turf Glide	.11
Turf Master	.4
Turf Pro	.47
Turf Saver	.2-3
Turf Saver II	.6
Turf Tamer	.26
Turf Trac R/S	.6
Ultra Guard	.34
Ultra Guard LVT	.34
Ultra Sport Radial	.30
Ultra Trac	.4-5
USA Loader	.37
USA Trail	.32
Wheelbarrow	.9
Wheels-Agriculture	.49
Wheels-Trailer	.48

CONTENTS

TURF HANDLERS	2 - 6
GRIPPING PERFORMERS	7 - 8
SMOOTH OPERATORS	9 - 10
GOLF GLIDERS	11 - 12
BIG BITERS	13 - 15
INDUSTRIAL UTILITY VEHICLE	16
ATV/UTV	17 - 29
TRAILER	30 - 33
CONSTRUCTION	34 - 37
INDUSTRIAL	38 - 41
AGRICULTURAL	42 - 47
WHEELS	48 - 49
TUBES, FLAPS & VALVES	50 - 55
WARRANTY	56 - 57

23 Windham Boulevard
Aiken, South Carolina 29805
1-800-827-1001

www.carlisletire.com



QUALITY COMMERCIAL, RECREATIONAL & UTILITY TIRES:

At Carlisle, we make special tires for special purposes. From all-terrain vehicles to farm equipment, highway trailers to golf cars, riding mowers to forklifts, our tires and wheels are backed by American technology and quality control and offer superior performance.



Consumer, Commercial Turf Equipment, Golf Cars & Utility Vehicles

TURF SAVER®



All Turf Handlers are Non-Highway Service Tires

TURF HANDLERS:

Turf Saver, Multi-Trac C/S, Turf Master, Ultra Trac, Turf CTR, Turf Trac R/S, Turf Saver II, Fast Trax

At Carlisle we, understand the need for protecting the turf without sacrificing traction. Our Turf Handlers provide options for all applications. The commercial grade compounds and proven tread designs of Multi Trac C/S and Turf Master will keep the professionals busy all day. Homeowners often choose the versatile Turf Saver or Turf Saver II to care for their weekly yard work. Whatever the job, we've got a Turf tire to handle it.

Size	Product Code	Ply	MTD Diameter	MTD Width	Rim Width	Max Load Capacity @ 10 MPH	Max PSI	Tire Weight
9 x 3.50 - 4	5110111	4	8.8	3.6	2.50	260	50	2.2
4.10 - 4	5110251	2	10.8	3.8	2.50	230	24	2.7
11 x 4.00 - 4	5110271	2	11.2	4.2	2.50	215	22	3.0
11 x 4.00 - 5	5110101	2	10.8	4.0	3.00	210	22	2.8
13 x 5.00 - 6	5110201	2	12.9	4.7	3.50	295	20	4.2
13 x 5.00 - 6	5110211	4	12.9	4.8	3.50	440	40	3.4
13 x 6.50 - 6	5111851	2	13.2	6.5	4.50	305	14	4.2
13 x 6.50 - 6	5111861	4	13.4	6.3	4.50	460	28	5.9
15 x 6.00 - 6	5110301	2	14.5	6.2	4.50	365	14	5.6
16 x 6.50 - 8	5110951	2	16.1	6.5	5.38	380	12	6.3
16 x 6.50 - 8	5110961	4	16.3	6.4	5.38	620	28	5.7
16 x 7.50 - 8	5112001	2	16.5	7.1	5.38	475	12	7.6
4.80 - 8	5112501	2	16.5	4.8	3.75	435	20	4.9
18 x 6.50 - 8	5110981	2	17.2	6.5	5.38	515	14	7.6
18 x 6.50 - 8	5110991	4	17.6	6.7	5.38	770	28	6.6
18 x 7.50 - 8	5111021	4	18.0	7.5	5.38	835	26	8.7
18 x 8.50 - 8	5110701	2	17.8	8.3	7.00	515	10	9.0
18 x 9.50 - 8	5110841	2	17.7	9.5	7.00	695	12	9.8
18 x 8.50 - 8	5110711	4	18.0	8.2	7.00	815	22	10.3
18 x 9.50 - 8	511081	4	18.1	9.6	7.00	1040	24	10.7
18 x 9.50 - 8	511082	6	18.5	9.5	7.00	1320	36	11.7
20 x 8.00 - 8	5110801	2	19.1	9.1	7.00	600	10	9.6
20 x 10.00 - 8	5111011	2	19.6	10.1	7.00	750	10	13.0
20 x 8.00 - 10	511111	4	20.0	7.9	6.00	895	24	11.7
20 x 10.00 - 10	511116	4	20.8	8.8	6.00	1225	24	12.7
21 x 7.00 - 10	511140	2	20.2	6.9	5.38	685	12	10.1
22 x 9.50 - 12	511051	2	21.3	8.9	7.00	870	12	13.0
23 x 8.50 - 12	511090	2	23.1	8.5	7.00	705	10	12.9
23 x 9.50 - 12	511100	2	23.2	9.5	7.00	920	12	14.2
23 x 10.50 - 12	511120	2	22.6	10.5	8.50	890	10	15.2
23 x 10.50 - 12	511121	4	22.8	10.3	8.50	1340	20	16.5
24 x 12.00 - 12	511075	2	23.0	11.6	8.50	1135	10	18.7

TURF HANDLERS

Consumer, Commercial Turf Equipment, Golf Cars & Utility Vehicles

MULTI-TRAC C/S

TURF MASTER®

ULTRA TRAC



MULTI-TRAC C/S

Size	Product Code	Ply	MTD Diameter	MTD Width	Rim Width	Max Load Capacity @ 10 MPH	Max PSI	Tire Weight
18 x 7.00 - 8	574351	4	17.9	6.9	5.38	785	26	8.7
18 x 8.50 - 8	574365	8	17.7	8.3	7.00	1220	44	13.2
18 x 9.50 - 8	574399	6	18.2	9.0	7.00	1320	36	11.9
20 x 8.00 - 8	574359	2	19.4	8.8	6.50	625	12	11.0
18 x 8.50 - 10	5743U1	4	18.1	8.3	7.00	795	22	9.8
18 x 10.50 - 10	5743E5	4	17.8	10.1	8.00	990	20	12.2
20 x 10.00 - 10	5743C2	6	19.6	9.6	8.00	1450	32	17.2
23 x 8.50 - 12	574372	6	22.6	8.3	7.00	1440	34	18.4
23 x 10.50 - 12	574353	6	22.6	10.4	8.50	1760	32	21.7
25 x 9.00 - 12	574368	4	24.9	9.5	8.00	1520	24	18.3
25 x 11.00 - 12	574369	4	25.2	10.8	8.00	1820	24	21.9
26 x 12.00 - 12	574361	4	25.2	12.2	8.50	1780	20	26.1
26 x 12.00 - 12	574377	6	25.2	12.2	8.50	2250	30	29.2
24 x 8.50 - 14	574324	4	24.0	8.5	7.00	1230	22	17.9
25 x 8.50 - 14	574339	4	25.0	8.5	7.00	1320	22	20.1
25 x 8.50 - 14	574371	6	25.0	8.5	7.00	1640	32	23.5
27 x 8.50 - 15	574348	4	26.6	8.5	7.00	1230	30	25.3
27 x 8.50 - 15	574356	6	26.6	8.6	7.00	1570	45	25.6
27 x 10.50 - 15	5743H6	4	26.9	10.2	8.50	1320	30	29.0
29 x 12.50 - 15	560478	10	29.0	12.7	10.00	3300	20	39.1
31 x 13.50 - 15	560362	4	31.5	13.2	10.50	2150	20	46.0

TURF MASTER®

5

Size	Product Code	Ply	MTD Diameter	MTD Width	Rim Width	Max Load Capacity @ 10 MPH	Max PSI	Tire Weight
13 x 6.50 - 6	5112491	4	13.1	6.3	4.50	460	28	5.4
15 x 6.00 - 6	5112521	4	14.5	6.0	4.50	570	30	4.7
15 x 6.50 - 8	5112531	2	15.0	6.3	5.38	415	14	6.2
16 x 6.50 - 8	5114011	4	16.5	6.3	5.38	620	28	7.0
16 x 7.50 - 8	5114021	4	16.5	7.0	5.38	680	24	8.4
18 x 6.50 - 8	5114171	4	17.5	6.4	5.38	770	28	7.2
18 x 8.50 - 8	5114041	4	18.4	8.1	7.00	815	22	10.6
18 x 9.50 - 8	5114131	4	18.1	9.2	7.00	1040	24	10.7
20 x 8.00 - 10	5114281	4	20.3	8.2	6.00	910	24	14.1
20 x 10.00 - 8	511405	4	19.6	10.4	7.00	1190	22	14.1
20 x 10.00 - 10	511416	4	20.0	8.8	7.00	1160	22	13.6
20 x 12 - 10	511257	4	20.1	10.3	8.00	1320	20	15.1
22 x 11.00 - 10	511255	4	21.4	10.4	7.00	1485	20	16.1
22 x 9.50 - 12	511433	4	21.8	9.1	7.00	1310	24	14.8
23 x 8.50 - 12	511419	4	22.9	8.4	7.00	1120	22	15.9
23 x 9.50 - 12	511406	4	23.6	9.8	7.00	1380	24	19.3
23 x 10.50 - 12	511408	4	22.8	10.0	8.50	1340	20	16.8
24 x 9.50 - 12	511434	4	23.6	9.6	7.00	1500	24	19.9
24 x 12.00 - 12	511409	4	23.3	11.4	8.50	1700	20	19.7

ULTRA TRAC

24 x 13.00 - 12	529368	4	23.2	13.0	10.5	1730	18	26.3
24 x 13.00 - 12	529387	6	22.7	13.0	10.5	2240	28	28.3
26.5 x 14.00 - 12	529386	4	26.5	14.4	11.0	2170	18	30.6
29 x 14.00 - 15	5293E6	6	29.0	14.0	11.0	1710	30	44.5

FAST TRAX**FAST TRAX**

18 x 11.00-10 NHS	501043	4	17.7	9.7	8.5	1120	22	13.1
-------------------	--------	---	------	-----	-----	------	----	------

TURF HANDLERS

TURF HANDLERS

Consumer, Commercial Turf Equipment, Golf Cars & Utility Vehicles

TURF CTR

TURF TRAC R/S

TURF SAVER II



TURF CTR

Size	Product Code	Ply	MTD Diameter	MTD Width	Rim Width	Max Load Capacity @ 10 MPH	Max PSI	Tire Weight
22 x 11.00 - 8	511501	4	22.4	10.8	9.00	955	10	12.8

TURF TRAC R/S

11 x 4.00 - 5	5753331	2	10.6	4.0	3.00	210	22	2.4
15 x 6.00 - 6	5753191	4	14.4	6.3	4.50	570	30	4.6
16 x 6.50 - 8	575304	4	16.0	6.8	5.38	620	28	6.9
18 x 8.50 - 8	5753311	4	17.7	8.1	7.00	815	22	7.3
20 x 10.00 - 8	575341	4	19.5	9.9	8.00	1190	22	10.5
22.5 x 10.50 - 8	560385	2	22.2	10.5	8.00	880	10	14.7
25 x 12.00 - 9	50D3T7	4	25.7	11.6	9.50	1820	20	17.9
20 x 10.00 - 10	50D362	4	19.6	9.3	8.00	1160	22	10.1
20 x 12.00 - 10	575315	4	19.6	11.7	8.00	1320	20	13.9
22 x 9.50 - 10	5753N1	4	21.7	9.5	7.00	980	14	14.3
24 x 9.50 - 10	5753P2	4	24.3	9.8	7.00	1410	22	16.1
24 x 12.00 - 10	5753A6	4	24.5	11.5	7.75	1740	20	20.7
23 x 10.50 - 12	575367	4	22.4	10.1	8.50	1340	20	13.0
24 x 12.00 - 12	575390	6	23.5	11.0	8.50	2240	32	21.3
26 x 12.00 - 12	50D363	10	25.3	12.4	8.5	3100	52	24.4

TURF SAVER II

13 x 5.00 - 6	5112201	2	12.3	4.6	3.50	295	20	3.8
15 x 6.00 - 6	5112301	2	14.3	6.0	4.50	365	14	5.3
16 x 6.50 - 8	5112951	2	16.0	6.2	5.38	415	14	5.9
18 x 8.50 - 8	5112701	2	17.5	8.2	7.00	515	10	6.3
18 x 9.50 - 8	511284	2	17.8	9.1	7.00	695	12	6.5
20 x 8.00 - 8	5112801	2	19.0	8.9	7.00	600	10	7.7

Utility Carts, Wheelbarrows, Pressure Washers, Generators, Hand Trucks, Lawn Equipment & Fun Carts

STUD

SAWTOOTH



All Gripping Performers are Non-Highway Service Tires



GRIPPING PERFORMERS: Stud, Sawtooth

These specially designed tread patterns with two-way traction perform well on drive and free wheels.

GRIPPING PERFORMERS

Utility Carts, Wheelbarrows, Pressure Washers, Generators, Hand Trucks, Lawn Equipment & Fun Carts

STUD



STUD

Size	Product Code	Ply	MTD Diameter	MTD Width	Rim Width	Max Load Capacity @ 10 MPH	Max PSI	Tire Weight
4.10 - 4	5160251	2	10.6	3.6	2.50	230	24	2.6
4.10 - 5	5160301	2	11.6	3.8	3.00	260	24	2.4
4.10 - 6	5160351	2	12.5	3.9	3.25	290	24	3.2
4.80 - 8	5160501	2	16.4	4.7	3.75	435	20	4.8
4.80 - 8	5164291	4	16.3	5.4	3.75	670	42	5.8

SAWTOOTH



SAWTOOTH

2.80 - 4	5190011	4	9.0	2.9	2.50	180	50	1.7
4.10 - 4	5190251	2	10.6	3.6	2.50	230	24	2.5
4.10 - 4	5190261	4	10.5	3.8	2.50	350	50	2.2
4.10/3.50 - 6	5190361	4	13.0	4.2	3.25	495	85	3.3
5.30/4.50 - 6	519067	6	14.6	5.3	3.50	885	95	5.1
4.80/4.00 - 8	5190501	2	16.0	4.6	3.75	510	35	5.1

Wheelbarrows, Transport Vehicles, Riding Mowers, Garden Tractors & Farm Equipment

Smooth, Wheelbarrow, Straight Rib

Our ribbed and smooth tires make optimum contact with various work surfaces for easy-flowing traction and a smooth roll. They also work as wide-flotation tires for on-site transportation.



SMOOTH



SMOOTH

Size	Product Code	Ply	MTD Diameter	MTD Width	Rim Width	Max Load Capacity @ 10 MPH	Max PSI	Tire Weight
8 x 3.00 - 4	5120081	4	8.2	2.9	2.50	120	30	1.7
9 x 3.50 - 4	5120101	4	8.7	3.7	2.50	260	50	2.3
11 x 4.00 - 5	5120111	4	11.0	4.0	3.00	325	46	3.2
13 x 5.00 - 6	5120211	4	12.7	4.8	3.50	440	40	4.1
13 x 6.50 - 6	5121861	4	12.9	5.9	4.50	460	28	4.0
4.80 - 8	5120511	4	16.8	4.8	3.75	760	70	4.1
18 x 9.50 - 8	510981	4	17.7	9.3	7.00	1040	24	9.3
18 x 10.50 - 10	586310	2	18.1	10.0	8.50	730	12	11.2
20 x 10.00 - 10	586325	2	19.6	9.5	8.00	815	12	11.9



WHEELBARROW



WHEELBARROW

4.00 - 6	5134371	2	13.6	3.9	2.50	330	30	2.0
4.80 - 8	5134511	2	15.8	3.9	2.50	550	30	2.5
4.80 - 8	5130511	4	16.3	4.5	3.75	765	70	3.4

Wheelbarrows, Transport Vehicles, Riding Mowers, Garden Tractors & Farm Equipment

STRAIGHT RIB



STRAIGHT RIB

Size	Product Code	Ply	MTD Diameter	MTD Width	Rim Width	Max Load Capacity @ 10 MPH	Max PSI	Tire Weight
11 x 4.00 - 4	5110921	4	10.4	4.1	2.50	350	50	3.2
11 x 4.00 - 5	5180111	4	11.1	4.2	3.00	325	46	3.2
13 x 5.00 - 6	5180211	4	12.9	4.7	3.50	440	40	4.1
13 x 6.50 - 6	5181861	4	13.0	6.0	4.50	460	28	4.0
15 x 6.00 - 6	5180311	4	14.5	6.1	4.50	570	30	3.9
16 x 6.50 - 8	5180961	4	16.0	6.4	5.38	620	28	5.2
18 x 9.50 - 8	518081	4	17.7	9.3	7.00	1040	24	9.4
20 x 10.00 - 10	518116	4	20.0	8.7	6.00	1160	22	12.8
26 x 12.00 - 12	518711	4	25.0	11.7	10.50	1780	20	22.3

Golf Cars & Utility Vehicles



TOUR MAX™

TURF GLIDE

GOLF GLIDERS

TOUR MAX™

Size	Product Code	Ply	MTD Diameter	MTD Width	Rim Width	Max Load Capacity @ 10 MPH	Max PSI	Tire Weight
18.5 x 8.5 R8	519148	LRB	18.2	8.1	7.00	675	35	12.3
205/50 - 10 †	519146	LRB	18.3	7.8	6.00	675	30	12.0

TURF GLIDE

8.00 - 6 *	508040	4	17.6	7.1	3.25	410	20	8.7
------------	--------	---	------	-----	------	-----	----	-----

† DOT Approved *Tube Type



GOLF GLIDERS:

Tour Max, Turf Glide, Links, Fairway Pro

Our line of tubeless golf and utility tires carry their loads without wear and tear on the fairway and ride smoothly on paved paths. They also work well as a wide-flotation tire for on-site transport on heavy duty jobs.

GOLF GLIDERS

LINKS



LINKS

GOLF GLIDER

Size	Product Code	Ply	MTD Diameter	MTD Width	Rim Width	Max Load Capacity @ 10 MPH	Max PSI	Tire Weight
18 x 8.50 - 8	5192711	4	17.4	8.5	7.00	815	22	13.2

FAIRWAY PRO



FAIRWAY PRO**

18 x 8.50 - 8	5189761	4	18.2	8.4	7.00	815	22	11.8
---------------	---------	---	------	-----	------	-----	----	------

**One Year Warranty

Riding Mowers, Garden Tractors, Snowthrowers, Tillers, ATVs & Utility Vehicles



BIG BITERS:

Super Lug, Power Trac, Tru Power, AT101 Chevron, Fast Trax

These All-Americans with their bar tread design put power to the ground for equipment that demands pure traction in hard and loose soil as well as snow.

Size	Product Code	Ply	MTD Diameter	MTD Width	Rim Width	Max Load Capacity @ 10 MPH	Max PSI	Tire Weight
13 x 5.00 - 6	5100201	2	13.1	4.5	3.50	295	20	4.2
14 x 4.50 - 6	5100251	2	14.5	4.5	3.25	320	20	5.0
16 x 6.50 - 8	5100961	4	16.2	6.3	5.38	620	28	7.5
18 x 9.50 - 8	510080	2	18.1	8.8	7.00	695	12	11.9
20 x 10.00 - 8	510101	4	20.1	9.7	7.00	1190	22	17.3

POWER TRAC



POWER TRAC

All Big Biters are Non-Highway Service Tires

Size	Product Code	Ply	MTD Diameter	MTD Width	Rim Width	Max Load Capacity @ 10 MPH	Max PSI	Tire Weight
4.80 - 8	5109501	2	16.1	4	2.5	435	20	6.2

Riding Mowers, Garden Tractors, Snowthrowers, Tillers, ATVs & Utility Vehicles

TRU POWER



AT101 CHEVRON



TRU POWER

Size	Product Code	Ply	MTD Diameter	MTD Width	Rim Width	Max Load Capacity @ 10 MPH	Max PSI	Tire Weight
18 x 8.50 - 10	523311	4	18.1	7.6	6.00	830	22	10.0
6 - 12	5233C3	4	22.7	5.7	5.00	590	28	12.1
23 x 8.50 - 12	523301	4	22.4	8.2	7.00	1115	22	16.3
23 x 10.50 - 12	523367	4	23.3	10.0	7.00	1340	20	23.2
26 x 12.00 - 12	523361	4	25.6	12.3	8.50	1780	20	30.1
26 x 12.00 - 12	523360	8	25.6	12.3	8.50	2740	42	34.8
29 x 12.50 - 15	5233D4	6	29.3	11.6	10.00	1710	30	41.9
31 x 15.50 - 15	5233A4	8	31.4	15.1	13.00	2760	45	71.5

AT101 CHEVRON

21 x 11.00 - 8	599044	4	21.2	10.9	8.50	1430	22	14.8
21 x 11.00 - 10	599050	4	20.9	10.4	8.50	1380	22	15.8
24 x 12.00 - 12	560352	4	23.8	12.2	8.50	1700	20	21.0

INDUSTRIAL TRAX



INDUSTRIAL TRAX

Size	Product Code	Ply	MTD Diameter	MTD Width	Rim Width	Max Load Capacity @ 10 MPH	Max PSI	Tire Weight
23 x 10.50 - 12	599045	4	22.5	10.40	8.50	1340	20	27.4
25 x 8.50 - 12	560445	6	24.8	8.50	7.00	1650	30	18.8
25 x 10.50 - 12	560446	6	25.0	10.50	7.00	1980	30	28.6

ATVs, Utility Vehicles, Side by Side Vehicles, & Fun-Karts



ATV UTILITY & RECREATIONAL TIRES:

Black Rock, Trail Wolf Sport, Trail Wolf, Mud Wolf, Stryker, AT489, AT489 X/L, All Trail / All Trail II, HD Field Trax, Knobby, Turf Tamer, Badlands A/R, Badlands XTR, A·C·T All Conditions, A·C·T HD.

Our rugged ATV tires are designed with durable rubber compounds and strong nylon cord construction, offering the ultimate in cut and impact resistance. Special tread patterns perform well for a variety of terrains.

ATVs, Utility Vehicles, Side by Side Vehicles, & Fun-Karts

BLACK ROCK



ATV/UTV

BLACK ROCK

Size	Product Code	Ply	MTD Diameter	MTD Width	Rim Width	Max Load Capacity @ 50 MPH	Max PSI	Tire Weight
AT24 x 9-11	560530	6	24.0	9.0	7.0	365	7	17.0
AT24 x 9-12	560534	6	24.0	9.0	7.0	355	7	16.3
AT25 x 8-12	560538	6	25.0	8.0	6.5	340	7	17.6
AT26 x 9-12	560539	6	26.0	9.0	7.0	410	7	19.3
AT25 x 10-12	560540	6	25.25	10.0	8.0	420	7	20.4
AT26 x 11-12	560541	6	26.25	11.0	9.0	480	7	22.5

ATV Tires are Non-Highway Service Tires

ATVs, Utility Vehicles, Side by Side Vehicles, & Fun-Karts

TRAIL WOLF SPORT®



ATV/UTV

TRAIL WOLF SPORT®

Size	Product Code	Ply	MTD Diameter	MTD Width	Rim Width	Max Load Capacity @ 50 MPH	Max PSI	Tire Weight
AT20 x 10-9	560496	6	19.6	9.9	8.0	300	7	13.48
AT22 x 11-9	560498	6	22.2	10.4	8.0	395	7	17.8
AT21 x 7-10	560510	6	20.9	6.7	9.0	235	7	11.7
AT22 x 7-10	560511	6	21.8	7.1	6.0	255	7	12.4

ATV Tires are Non-Highway Service Tires

ATVs, Utility Vehicles, Side by Side Vehicles, & Fun-Karts

TRAIL WOLF®



TRAIL WOLF®

ATV/UTV


Size	Product Code	Ply	MTD Diameter	MTD Width	Rim Width	Max Load Capacity @ 50 MPH	Max PSI	Tire Weight
AT19 x 7 - 8	5370371	2	18.8	6.6	5.38	175	5	8.0
AT19 x 8 - 8	537038	2	19.0	7.1	6.00	200	5	8.3
AT20 x 7 - 8	5370391	2	19.4	6.8	5.38	157	4	8.5
AT20 x 11 - 8	537033	2	20.2	10.5	9.00	340	7	13.8
AT20 x 11 - 9	537034	2	19.6	10.3	9.00	340	7	14.8
AT22 x 10 - 9	537055	2	21.8	10.0	9.00	355	7	18.0
AT25 x 12 - 9	537082	4	25.6	12.3	10.00	430	5	25.9
AT20 x 11 - 10	537035	3	19.9	11.9	10.00	280	5	16.2
AT21 x 7 - 10	537084	3★	21.4	6.8	5.50	205	5	12.0
AT22 x 7 - 10	537048	2	22.1	6.8	5.50	180	4	12.0
AT22 x 10 - 10	537049	2	23.5	9.2	8.00	245	4	17.7
AT25 x 12 - 10	537085	4	25.3	11.6	10.00	430	5	21.1
AT22 x 7 - 11	537054	4	22.2	6.8	6.38	245	7	13.0
AT23 x 8 - 11	537090	4	23.1	7.6	6.38	255	5	15.0
AT24 x 9 - 11	537091	4	24.4	8.5	7.00	316	5	17.0
AT25 x 8 - 12	537062	2	25.3	7.5	6.50	340	7	16.4
AT25 x 10 - 12	537061	2	25.5	9.0	8.00	340	7	21.4
AT25 x 11 - 12	537065	2	25.7	9.1	8.00	455	7	20.6

ATV Tires are Non-Highway Service Tires

*STAR RATED Tires at 50MPH MAX

ATVs, Utility Vehicles, Side by Side Vehicles, & Fun-Karts

MUD WOLF®



MUD WOLF®

Size	Product Code	Ply	MTD Diameter	MTD Width	Rim Width	Max Load Capacity @ 50 MPH	Max PSI	Tire Weight
AT25 x 8 - 12	537125	6	25.0	8.3	6.5	340	7	27.5
AT25 x 11 - 12	537126	6	25.0	11.6	9.0	455	7	30.2
AT26 x 9 - 12	537127	6	26.0	9.2	7.0	410	7	28.8
AT26 x 12 - 12	537128	6	26.0	11.5	8.0	520	7	35.5
AT27 x 9 - 12	537129	6	27.0	9.0	7.0	440	7	31.7
AT27 x 12 - 12	537130	6	27.0	12.0	9.5	550	7	35.7

MUD WOLF® XL



MUD WOLF® XL

AT26X9-14	537131	6	26.55	8.05	7.0"	395	7	19.6
AT26X11-14	537132	6	26.91	10.05	8.0"	465	7	26.8

ATV Tires are Non-Highway Service Tires
 *STAR RATED Tires at 50MPH MAX

ATVs, Utility Vehicles, Side by Side Vehicles, & Fun-Karts

STRYKER®



ATV/UTV

STRYKER®

Size	Product Code	Ply	MTD Diameter	MTD Width	Rim Width	Max Load Capacity @ 50 MPH	Max PSI	Tire Weight
AT22 x 11 - 8	531073	Belted	22.6	11.1	9.00	340	5	21.0
AT22 x 11 - 9	531065	Belted	22.6	11.2	10.00	340	5	22.3
AT25 x 12 - 9	531075	Belted	25.2	12.2	10.00	430	5	28.0
AT22 x 11 - 10	531095	2	22.9	10.1	8.25	330	5	20.8

ATV Tires are Non-Highway Service Tires

*STAR RATED Tires at 50MPH MAX

ATVs, Utility Vehicles, Side by Side Vehicles, & Fun-Karts

AT489



AT489

Size	Product Code	Ply	MTD Diameter	MTD Width	Rim Width	Max Load Capacity @ 50 MPH	Max PSI	Tire Weight
AT22x7-10	5370451	3★	22.2	7.0	6.00	255	7	17.0
AT22x10-10	5370461	3★	21.7	9.9	8.00	355	7	17.9
AT22x7-12	5370521	3★	22.4	6.7	6.00	240	7	12.6
AT22x10-12	5370531	3★	22.3	9.3	8.00	340	7	17.0
AT22x11.00-10	5893V0	2★	22.0	11.0	9.00	330	5	15.6
AT23 x 7 - 10	5893M0	2★	22.7	6.5	5.50	240	5	12.4
AT23 x 8 - 10	589326	3★	23.2	7.9	6.50	300	7	13.8
AT23 x 10 - 10	589327	3★	23.4	9.5	8.00	375	7	17.7
AT24 x 11 - 10	589305	3★	24.0	9.7	9.00	440	7	17.9
AT25 x 11 - 10	589308	3★	25.1	10.6	9.00	455	7	20.3
AT23 x 8 - 11	589304	3★	23.7	7.5	6.50	290	7	14.3
AT24 x 8 - 11	589332	3★	24.5	8.4	6.50	320	7	18.1
AT24 x 9 - 11	5893A9	3★	24.5	8.6	7.00	365	7	18.0
AT24 x 10 - 11	589328	3★	24.4	9.6	8.00	395	7	19.2
AT23 x 8 - 12	589329	3★	23.1	7.4	6.50	280	7	13.6
AT23 x 10 - 12	589330	3★	23.1	9.0	8.00	365	7	17.8
AT24 x 8 - 12	589337	3★	23.8	8.0	6.50	455	7	14.9
AT24 x 9 - 12	589342	2★	23.8	8.9	8.00	265	5	16.5
AT24 x 11 - 12	589344	3★	24.4	10.1	9.00	430	7	20.1
AT25 x 8 - 12	589306	3★	25.2	7.5	6.50	340	7	15.2
AT25 x 10 - 12	589321	3★	25.2	9.1	8.00	420	7	19.2
AT25 x 11 - 12	589346	3★	25.4	10.6	8.00	455	7	21.1

ATV Tires are Non-Highway Service Tires

*STAR RATED Tires at 50MPH MAX

ATVs, Utility Vehicles, Side by Side Vehicles, & Fun-Karts

AT489 X/L



ATV/UTV

AT489 X/L

Size	Product Code	Ply	MTD Diameter	MTD Width	Rim Width	Max Load Capacity @ 50 MPH	Max PSI	Tire Weight
AT25 x 8 - 12	560490	6	25.2	7.43	6.50	340	7	15.09
AT25 x 11 - 12	560491	6	25.5	10.4	8.00	455	7	20.92
AT26 x 8 - 12	560480	6	26.0	7.8	6.50	375	7	17.3
AT26 x 9 - 12	560460	6	26.1	8.7	7.00	410	7	18.76
AT26 x 11 - 12	560461	6	26.3	10.8	8.00	480	7	24.29
AT27 x 9 -12	560470	6	27.0	9.13	7.00	440	7	18.89
AT27 x 11 -12	560471	6	27.3	10.8	8.00	495	7	24.67

ATV Tires are Non-Highway Service Tires

*STAR RATED Tires at 50MPH MAX

ATVs, Utility Vehicles, Side by Side Vehicles, & Fun-Karts

ALL TRAIL™

HD FIELD TRAX



ALL TRAIL® / ALL TRAIL II

Size	Product Code	Ply	MTD Diameter	MTD Width	Rim Width	Max Load Capacity @ 10 MPH	Max PSI	Tire Weight
20 x 10.00 - 8 NHS	510043	4	20.2	9.3	7.00	1190	22	15.2
22 x 10.00 - 8 NHS	510044	4	22.0	10.1	7.00	1350	22	16.0
20 x 10.00 - 10 NHS	510045	4	20.1	8.9	6.00	1160	22	15.0
22 x 9.50 - 10 NHS	55A3N1	4	22.0	9.5	7.75	1280	22	15.2
22 x 11.00 - 10 NHS	510016	4	21.9	10.2	8.00	1475	22	20.2
24 x 9.50 - 10 NHS	55A3P2	4	24.0	9.7	7.50	1410	22	15.0
24 x 10.50 - 10 NHS	55A3N9	4	24.5	10.8	8.00	1490	20	18.0
23 x 8.00 - 12 NHS	511506	4	23.2	8.4	6.50	1125	22	19.6
23 x 10.50 - 12 NHS	511505	4	23.1	9.9	7.00	1340	20	24.4
25 x 8.00 - 12 NHS	511507	4	25.0	8.3	7.00	1305	22	20.2
25 x 10.50 - 12 NHS	511508	4	24.7	10.2	7.00	1570	20	25.0

HD FIELD TRAX

AT22 x 12 - 8	588389	3★	21.3	11.7	9.50	430	7	20.8
AT22.5 x 10 - 8	5883B9	3★	22.5	10.2	7.00	365	7	20.5
AT25 x 13 - 9	588394	3★	24.8	12.4	10.50	535	7	27.1
18 x 8.50 - 10 NHS	5883U1	4	18.2	7.4	7.00	830	22	11.0
24X12.00-12 NHS	560366	2	24.0	11.6	9.50	1135	10	24.7
26 x 12.00 - 12 NHS	560467	2	25.6	11.8	9.50	1185	10	25.9

ATV Tires are Non-Highway Service Tires
*STAR RATED Tires at 50MPH MAX

ATVs, Utility Vehicles, Side by Side Vehicles, & Fun-Karts

KNOBBY



TURF TAMER



ATV/UTV

KNOBBY

Size	Product Code	Ply	MTD Diameter	MTD Width	Rim Width	Max Load Capacity @ 10 MPH	Max PSI	Tire Weight
AT145/70 - 6	5150021	2★	14.3	5.3	4.50	80	4	4.9
AT16 x 8 - 7	5150031	3★	16.5	6.6	5.00	180	7	7.1
AT18 x 9.50 - 8 NHS	537005	2	18.3	8.8	7.00	625	10	10.6
AT22 x 11 - 8	537050	2	22.3	10.5	9.00	495	10	14.4
AT25 x 12 - 9	537081	2	24.6	11.8	10.00	430	5	18.8

TURF TAMER

AT18 x 9.50 - 8	55U346	3★	18.1	9.0	7.50	245	7	10.6
AT20 x 11 - 8	55U3E2	3★	20.0	11.2	9.00	340	7	14.2
22.5 x 10 - 8 NHS	55U3C7	4	22.8	9.2	8.00	1390	22	14.2
AT25 x 12 - 9	55U373	3★	25.3	11.2	9.50	495	7	17.5
AT20 x 11 - 10	55U3F2	3★	20.0	10.7	9.00	330	7	15.1
AT22 x 11 - 10	55U3A5	3★	22.7	10.6	9.00	385	7	16.7

ATV Tires are Non-Highway Service Tires
 *STAR RATED Tires at 50MPH MAX

ATVs, Utility Vehicles, Side by Side Vehicles, & Fun-Karts

BADLANDS A/R



BADLANDS XTR



ATV /UTV

BADLANDS A/R

Size	Product Code	Ply	MTD Diameter	MTD Width	Rim Width	Max Load Capacity @ 50 MPH	Max PSI	Tire Weight
AT205/85R12	530009	3★	25.5	7.7	6.50	375	7	17.6
AT255/70R12	530008	3★	26.1	9.4	8.00	440	7	19.4

BADLANDS XTR

Size	Product Code	Ply	MTD Diameter	MTD Width	Rim Width	Max Load Capacity @ 50 MPH	Max PSI	Tire Weight
AT205/80R12	537068	3★	25.2	7.6	6.50	340	7	14.7
AT255/65R12	537067	3★	25.2	9.4	8.00	420	7	19.7
AT270/60R12	537069	3★	25.0	10.5	8.00	455	7	20.2

ATV Tires are Non-Highway Service Tires

*STAR RATED Tires at 50MPH MAX

ATVs, Utility Vehicles, Side by Side Vehicles, & Fun-Karts

A·C·T



ATV/UTV – RADIAL

A·C·T All Conditions Tire

Size	Product Code	Ply	MTD Diameter	MTD Width	Rim Width	Max Load Capacity @ 50 MPH	Max PSI	Tire Weight
AT23x7.00R12	560408	3★	23.0	7.0	5.50	260	7	14.0
AT23x10.00R12	560409	3★	23.0	10.0	8.00	365	7	18.0
AT25 x 8R12	560425	3★	25.2	7.9	7.00	340	7	17.0
AT26 x 8R12	560441	3★	25.8	7.7	7.00	375	7	17.3
AT25 x 11R12	560426	3★	25.5	10.5	8.00	455	7	24.8
AT26 x 10R12	560442	3★	26.2	10.4	8.00	440	7	24.6
AT26 x 8R14	560518	3★	26.0	8.0	7.00	355	7	17.4
AT26 x 11R14	560519	3★	26.0	11.1	8.00	465	7	23.6

ATV Tires are Non-Highway Service Tires
 *STAR RATED Tires at 50MPH MAX

ATVs, Utility Vehicles, Side by Side Vehicles, & Fun-Karts

A·C·T HD



ATV/UTV – RADIAL

A·C·T HD Heavy Duty sidewall for increased puncture resistance

Size	Product Code	Ply	MTD Diameter	MTD Width	Rim Width	Max Load Capacity @ 50 MPH	Max PSI	Tire Weight
AT25 x 8R12	560481	6	25.2	7.2	6.50	340	7	21.9
AT25 x 11R12	560482	6	25.4	10.0	9.00	455	7	27.7
AT26 x 9R12	560465	6	26.2	8.6	7.00	410	7	25.7
AT26 x 11R12	560466	6	26.6	10.1	9.00	480	7	30.5
AT27 x 9R12	560472	6	27.5	8.9	7.00	440	7	26.6
AT27 x 11R12	560473	6	27.7	10.4	9.00	495	7	31.8

ATV Tires are Non-Highway Service Tires
 *STAR RATED Tires at 50MPH MAX

Boat Trailers, Cargo Trailers, Horse & Stock Trailers, RV-Towable Utility Trailers, & Specialty Trailers

ULTRA SPORT RADIAL



RADIAL – TRAILER

ULTRA SPORT RADIAL

Size	Product Code	Load Range	MTD Dia.	MTD Width	Rim Width	Max Load Capacity	Max PSI	Tire Weight	Tread Depth (32nds)
ST235/60R14	5193081	LRC	25.2	9.1	7.00	1820	50	24.0	16
ST235/60R15	5193091	LRD	26.2	9.2	7.00	2200	65	26.7	16



HIGHWAY SPEED TRAILER TIRES:

Ultra Sport, Radial Trail, USA Trail, Sport Trail, Sport Trail LT

Approved for over-the-highway use, these tires comply with U.S. Department of Transportation requirements. Their long-lasting, wrap-around tread provides sure cornering and safe travel.

Boat Trailers, Cargo Trailers, Horse & Stock Trailers, RV- Towable Utility Trailers, & Specialty Trailers

RADIAL TRAIL



RADIAL TRAIL

RADIAL TRAIL is approved for Highway Speed Use

Size	Product Code	Load Range	MTD Dia.	MTD Width	Rim Width	Max Load Capacity	Max PSI	Tire Weight	Tread Depth (32nds)
ST145/R12	5151291	LRD	21.4	5.8	4.00	1220	65	15.0	8
ST175/80R13	5198121	LRC	24.1	6.7	4.50	1360	50	16.5	10
ST185/80R13	5193521	LRC	24.7	7.1	4.50	1480	50	19.6	10
ST205/75R14	5198131	LRC	26.1	8.0	5.50	1760	50	23.4	10
ST215/75R14	5198141	LRC	26.8	8.2	6.00	1870	50	22.6	10
ST205/75R15	5198151	LRC	27.1	8.0	5.50	1820	50	25.2	10
ST205/75R15	5198081	LRD	27.2	8.0	5.00	2150	65	24.4	10
ST225/75R15	5198161	LRC	28.2	8.8	6.00	2150	50	28.5	10
ST225/75R15	5198171	LRD	28.2	8.8	6.00	2540	65	29.4	10
ST225/75R15	5198221 *	LRE	28.2	9.0	6.00	2830	80	30.5	10
ST235/80R16	5190821	LRE	30.8	9.0	6.00	3420 - S 3000 - D	80	35.0	13
ST235/85R16	5192991	LRE	31.7	9.3	6.00	3640 - S 3200 - D	80	39.5	13
ST235/85R16	5193411 *	LRF	31.9	9.0	6.00	3960 - S 3520 - D	95	41.2	13

*Requires HD Wheel

S = SINGLE D = DUAL

Boat Trailers, Cargo Trailers, Horse & Stock Trailers, RV- Towable Utility Trailers, & Specialty Trailers

USA TRAIL®



USA TRAIL®

USA TRAIL is approved for Highway Speed Use

Size	Product Code	Load Range	MTD Dia.	MTD Width	Rim Width	Max Load Capacity	Max PSI	Tire Weight	Tread Depth (32nds)
4.80 - 8	519056	LRB	17.1	5.1	3.75	585	60	6.6	6
4.80 - 8	519058	LRC	17.4	5.1	3.75	760	90	7.6	6
5.70 - 8	519086	LRB	19.2	6.0	3.75	715	50	9.6	10
5.70 - 8	519087	LRC	18.8	6.0	3.75	910	75	11.3	10
5.70 - 8	519088	LRD	18.9	6.1	3.75	1070	100	12.2	10
6.90 - 9	519572	LRC	22.0	7.1	4.50	1100	60	13.5	10
20.5 x 8.0 - 10	519144	LRE	20.9	8.7	6.00	1520	90	19.2	10
4.80 - 12	519062	LRB	21.0	5.0	4.00	785	60	8.1	8
4.80 - 12	519063	LRC	21.3	5.1	4.00	990	90	10.4	8
5.30 - 12	519076	LRB	21.8	5.3	4.00	855	55	10.2	8
5.30 - 12	519077	LRC	22.1	5.3	4.00	1050	80	11.3	8
ST175/80D13	519161	LRC	25.0	6.7	4.50	1360	50	17.4	10
ST205/75D14	519300	LRC	26.0	8.3	5.50	1760	50	23.6	10
ST215/75D14	519315	LRC	26.3	8.5	6.00	1870	50	24.3	10
ST205/75D15	519400	LRC	27.1	8.0	5.50	1820	50	23.8	10
ST225/75D15	519410	LRC	28.1	8.9	6.00	2150	50	29.2	10
ST225/75D15	519412	LRD	28.6	9.0	6.00	2540	65	34.6	10

Boat Trailers, Cargo Trailers, Horse & Stock Trailers, RV- Towable Utility Trailers, & Specialty Trailers

SPORT TRAIL

SPORT TRAIL LT®



SPORT TRAIL

Size	Product Code	Load Range	MTD Dia.	MTD Width	Rim Width	Max Load Capacity	Max PSI	Tire Weight	Tread Depth (32nds)
4.80-8	5193171	LRB	16.2	4.7	3.75	585	60	5.80	7
4.80-8	5193181	LRC	16.3	4.9	3.75	760	90	6.40	7
5.70-8	5193191	LRB	18.1	5.9	3.75	715	50	9.20	10
5.70-8	5193201	LRC	18.4	6.0	3.75	910	75	9.90	10
16.5 x 6.5 - 8	5193421	LRB	16.6	6.7	5.38	615	45	8.15	7
16.5 x 6.5 - 8	5193461	LRC	16.6	6.8	5.38	785	70	9.45	7
16.5 x 6.5 - 8	5193481	LRD	16.6	6.8	5.38	910	90	10.30	7
18.5 x 8.5 - 8	5193431	LRB	18.0	8.6	7.00	760	35	12.20	11
18.5 x 8.5 - 8	5193451	LRC	17.9	8.7	7.00	935	50	13.36	11
20.5 x 8.0 - 10	5193441	LRB	20.8	8.1	6.00	910	35	14.35	11
20.5 x 8.0 - 10	5193471	LRC	20.9	8.0	6.00	1100	50	16.14	11
20.5 x 8.0 - 10	5193491	LRD	20.7	8.3	6.00	1320	70	17.08	11
20.5 x 8.0 - 10	5193501	LRE	20.8	8.5	6.00	1520	90	17.88	11
20.5 x 8.0 - 10	5193511	LRF	21.2	8.5	6.00	1650	105	18.30	11
4.80-12	5193211	LRB	20.7	5.1	4.00	785	60	9.70	7
4.80-12	5193221	LRC	21.0	5.1	4.00	990	90	10.10	7
5.30-12	5193231	LRB	21.4	5.4	4.00	855	55	9.30	7
5.30-12	5193241	LRC	21.7	5.5	4.00	1050	80	10.90	7
ST175/80D13	5193251	LRB	24.2	6.8	4.50	1100	35	18.10	7
ST175/80D13	5193261	LRC	24.0	6.8	4.50	1360	50	20.40	7
ST185/80D13	5193321	LRC	24.7	7.3	4.50	1480	50	19.68	9
ST185/80D13	5193531	LRD	24.8	7.4	4.50	1710	65	22.12	9
ST205/75D14	5193131	LRC	26.3	7.8	5.50	1760	50	22.90	10
ST215/75D14	5193281	LRC	26.7	8.0	5.50	1870	50	24.20	10
ST205/75D15	5193291	LRB	26.9	7.9	5.00	1480	35	22.40	10
ST205/75D15	5193381	LRC	27.0	7.9	5.00	1820	50	23.20	10
ST225/75D15	5193301	LRC	27.7	8.7	6.00	2150	50	28.90	11
ST225/75D15	5193311	LRD	28.2	8.7	6.00	2540	65	30.70	11

SPORT TRAIL LT®

700 - 15LT	5193351	LRD	29.83	8.29	5.50	2040 - S 1820 - D	60	32.14	15
750 - 16LT	5193371	LRE	32.61	8.62	6.00	2755 - S 2470 - D	75	38.80	15
8 - 14.5LT	5193341	LRF	28.32	8.07	6.00	2835 - S 2470 - D	100	28.69	15

Skid Steers, Backhoes, Subcompact Tractors, Aerial Work Platform Lifts, Rough Terrain Forklifts



CONSTRUCTION

ULTRA GUARD®

Size	Product Code	Ply	MTD Dia.	MTD Width	Rim Width	Max Load Capacity	Max PSI	Tire Weight	Tread Depth (32nds)
10 - 16.5 (TL)	560402	10	30.4	10.4	8.25	4710	75	79.0	44
12 - 16.5 (TL)	560403	12	32.7	12.1	9.75	6320	80	98.0	44

ULTRA GUARD® LVT

10-16.5 (TL)	570075	10	31.4	10.4	8.25	4710	75	90	44
12-16.5 (TL)	570076	14	33.5	12.1	9.75	6780	90	114	44
14-17.5 (TL)	570077	14	37.5	13.6	11.0	8540	80	144	44

**SEVERE SERVICE SKID STEER – ULTRA GUARD®, ULTRA GUARD® LVT**

ULTRA GUARD® – New technology built in with a super rugged heavy duty construction and an abrasion resistant tread compound. Add in an “Ever Compensating” footprint that maximizes performance and durability through its entire life cycle and you have a severe service tire designed to perform even in the most demanding conditions. Extra deep tread depth and heavier ply ratings make this tire a “Must Have” for extreme operating applications. LVT design targeted for hard surface/sharp abrasion conditions.

Skid Steers, Backhoes, Subcompact Tractors, Aerial Work Platform Lifts, Rough Terrain Forklifts

GUARD DOG®



GUARD DOG® HD



CONSTRUCTION

GUARD DOG®

Size	Product Code	Ply	MTD Dia.	MTD Width	Rim Width	Max Load Capacity	Max PSI	Tire Weight	Tread Depth (32nds)
10-16.5 (TL)	560375	8	30.4	10.4	8.25	4140	60	50.8	24
12-16.5 (TL)	560377	10	32.7	12.1	9.75	5520	65	75.0	26

GUARD DOG® HD

10-16.5 (TL)	570130	10	30.3	10.8	8.25	4710	75	53	26
12-16.5 (TL)	570131	12	32.9	12.5	9.75	6320	80	78	28

PREMIUM SKID STEER – GUARD DOG®, GUARD DOG® HD

The Guard Dog's unique tire design was specifically made for applications where increased traction, increased puncture and abrasion resistance are required – ensuring optimum service life.



Skid Steers, Backhoes, Subcompact Tractors, Aerial Work Platform Lifts, Rough Terrain Forklifts

TRAC CHIEF®



TRAC CHIEF® XT



CONSTRUCTION

TRAC CHIEF®

Size	Product Code	Ply	MTD Dia.	MTD Width	Rim Width	Max Load Capacity	Max PSI	Tire Weight	Tread Depth (32nds)
5.70 - 12 (TL)	51S3C2	4	22.4	5.7	4.50	1450	60	15.5	17
18 x 8.50 - 10 (TL)	51S311	4	18.2	8.0	7.00	830	22	13.9	16
23 x 8.50 - 12 (TL)	51S3G8	6	22.6	8.4	7.0	1820	50	32.6	14
23 x 8.50 - 14 (TL)	51S388	4	23.0	8.0	7.00	1560	35	23.2	17
25 x 8.50 - 14 (TL)	51S379	6	25.8	8.4	7.00	2130	50	26.7	17
26 x 12.00 - 12 (TL)	51S361	4	25.5	12.4	10.50	1780	20	33.5	19
27 x 8.50 - 15 (TL)	51S339	6	26.7	9.0	7.00	2400	50	28.4	17
27 x 10.50 - 15 (TL)	51S3H7	6	26.8	10.4	8.50	2610	45	33.7	17
28 x 8.50 - 15 (TL)	570139	6	28.0	8.5	7.00	4710	75	28	16
29 x 10.50 - 15 (TL)	560410	8	29.0	10.5	8.5	4840	70	44.1	19
10 - 16.5 (TL)	51S3D1	8	30.5	10.7	8.25	4140	60	44.0	19
12 - 16.5 (TL)	51S3J7	10	32.8	12.1	9.75	5600	65	62.0	23
14 - 17.5 (TL)	510039	14	36.7	14.1	10.50	8540	80	109.8	25
15 - 19.5 (TL)	510024	12	39.3	16.2	12.25	9190	60	144.5	26

TRAC CHIEF® XT

10 - 16.5 (TL)	570140	10	30.6	10.8	8.25	4710	75	49.0	21
12 - 16.5 (TL)	570141	12	32.8	12.5	9.75	6320	80	69.0	23

Skid Steers, Backhoes, Subcompact Tractors, Aerial Work Platform Lifts, Rough Terrain Forklifts

USA LOADER®



CONSTRUCTION

USA LOADER®

Size	Product Code	Ply	MTD Dia.	MTD Width	Rim Width	Max Load Capacity	Max PSI	Tire Weight	Tread Depth (32nds)
10 - 16.5 (TL)	510713	10	30.9	10.9	8.25	4720	75	62.0	26
12 - 16.5 (TL)	510715	8	32.7	12.6	9.75	4810	50	72.8	27
12 - 16.5 (TL)	510716	10	32.7	12.6	9.75	5600	65	76.0	27

Airport Support Equipment

GROUND FORCE
ULTRA RIB GSE

INDUSTRIAL

GROUND FORCE ULTRA RIB GSE

Size	Product Code	Ply	MTD Dia.	MTD Width	Rim Width	Max Load Capacity @ 10 MPH	Max PSI	Tire Weight	Tread Depth (32nds)
4.80 - 8 (TT)	52N242	8	16.5	4.8	3.75	1160	145	10.4	11
5.70 - 8 (TT)	52N208	8	18.4	5.9	3.75	1470	120	12.5	11
6.90 - 9 (TT)	52N260	10	21.6	6.8	4.00	2200	125	23.3	24
6.50 - 10 (TT)	52N263	10	23.2	7.1	5.00	2535	115	28.5	24
9.00 - 10 (TT)*	52N221	10	27.2	9.7	6.00	3720	85	34.4	9
175/80D13 (TL)	52N3T9	8	23.7	6.1	5.00	3920	100	26.9	24

*Straight Rib



GROUND FORCE ULTRA RIB GSE:

Our Ground Force tires combine extra tread depth and the exclusive **CT-4** tread compound to set a new standard of durability and wear in the ground support industry. Each tire features a built-in rim guard for maximum wheel protection.

Material Handling, Mining, Compaction & Road Paving Equipment

PREMIUM WIDE TRAC



PREMIUM WIDE TRAC Extra heavy duty sidewall

Size	Product Code	Ply	MTD Dia.	MTD Width	Rim Width	Capacity @ 10 MPH	Max PSI	Tire Weight	Tread Depth (32nds)
5.70/5.00 - 8 (TT)	54P2E7	10	18.5	5.5	4.5/3.0	2790	150	15.5	17
18 x 7 - 8 (TT)	54P255	16	18.3	6.6	4.33	4695	145	23.0	21
18 x 9 - 8 (TT)	54P257	16	18.6	8.5	7.00	5585	150	29.0	20
6.90/6.00 - 9 (TT)	54P204	10	22.2	6.0	5.5/4.0	3665	125	28.6	32
6.50 - 10 (TT)	54P263	10	23.8	7.1	5.00	4225	115	37.6	32
7.00 - 12 (TT)	54P212	12	27.3	7.5	5.00	5995	125	51.1	32
7.50 - 15 (TT)	54P269	12	32.4	8.7	6.00	5260	115	61.0	22
28 x 9 - 15 (TT)	54P2B5	12	27.3	8.8	7.00	6880	120	52.2	18
29 x 8 - 15 (TT)	54P216	12	28.9	7.5	5.50	6870	125	57.0	32
8.25 - 15 (TT)	54P2D5	14	33.6	9.8	6.50	9385	120	84.3	24
2.50 - 15 (TT)	54P2H2	18	29.1	9.1	7.50	10100	150	67.8	24
3.00 - 15 (TT)	54P2H3	20	32.7	11.3	8.00	14500	135	118.2	26
28 x 12 - 15 (TT)	54P262	20	28.1	11.5	9.75	10800	150	82.0	24
7.50 - 16 (TT)	54P2K8	12	32.3	8.5	6.00	8000	115	56.4	22

FORKLIFT / MATERIAL HANDLING :

Premium Wide Trac, Industrial Deep Traction, Road Roller, Extra Grip, Industrial All Purpose

Heavy ply construction and increased gauge deliver optimum tire life, while stabilizing features such as a larger tread volume and a wide, flat profile guarantee each of our forklift tires will come in on top.



Material Handling, Mining, Compaction & Road Paving Equipment

INDUSTRIAL
DEEP TRACTION

INDUSTRIAL

INDUSTRIAL DEEP TRACTION Reinforced bead area

Size	Product Code	Ply	MTD Dia.	MTD Width	Rim Width	Max Load Capacity @ 10 MPH	Max PSI	Tire Weight	Tread Depth (32nds)
5.70/5.00 - 8 (TT)	5542A1	8	18.2	5.5	4.5/3.0	2450	120	11.5	9
6.90/6.00 - 9 (TT)	554204	10	21.9	6.9	5.5/4.0	3665	125	20.2	19
6.50 - 10 (TT)	554263	10	23.4	7.4	5.00	4225	115	26.3	20
7.00 - 12 (TT)	554212	12	27.4	7.8	5.00	5995	125	36.3	21
8.25 - 15 (TT)	554231	12	33.6	9.8	6.50	8680	105	58.7	23
29 x 8 - 15 (TT)	554216	12	29.2	7.5	5.50	6870	125	47.5	25

Material Handling, Mining, Compaction & Road Paving Equipment

ROAD ROLLER



INDUSTRIAL

ROAD ROLLER Superior heat resistant nylon fabric plys for paving applications

Size	Product Code	Ply	MTD Dia.	MTD Width	Rim Width	Max Load Capacity @ 10 MPH	Max PSI	Tire Weight	Tread Depth (32nds)
7.50 - 15 (TT)	58R252	12	30.9	8.6	6.00	5860	110	45.5	NA
7.50 - 15 (TT)	58R2E1	14	30.9	8.6	6.00	6300	125	45.5	NA
8.5/90 - 15K (TL)	58R3A2	6	30.9	8.6	6.00	3900	50	39.8	NA

*DOT RATED

Front Tractors, Wagons, Balers, Spreaders, Seeders, Irrigation Systems & Feedyard Scrapers



AGRICULTURAL SERIES :

Farm Specialist® F-2 / F-2M, FI, HF-1, I-1, F-3

Quality, Durability, and Versatility are essential for handling the wide variety of AG/Construction tire applications. For these reasons, Carlisle is proud to present its Proven Front and Implement product line. We make available both Triple and Quad Rib Fronts, Industrial Fronts, Implements in both regular and Highway speed designs, also tube type and tubeless constructions.

Front Tractors, Wagons, Balers, Spreaders, Seeders, Irrigation Systems & Feedyard Scrapers

F-2 TRIPLE RIB

F-2M QUAD RIB



FARM SPECIALIST® F-2 / F-2M

Size	Product Code	Ply	MTD Diameter	MTD Width	Rim Width	Max Load Capacity @ 25 MPH	Max PSI	Tire Weight
4.00 - 15SL F-2 (TT)	52F230	4	24.3	4.4	3.0	585	52	9.5
4.00 - 19SL F-2 (TT)	52F233	4	28.2	4.4	3.0	715	52	12.0
5.00 - 15SL F-2 (TT)	52F235	4	26.0	5.1	3.0	715	44	12.0
7.5L - 15SL F-2 (TT)	52F290	6	29.1	8.0	6.0	1430	44	26.5
9.5L - 15SL F-2 (TL)	52F344	8	31.5	9.9	7.0	1870	48	42.4
9.5L - 15SL F-2 (TT)	52F244	8	31.5	9.9	7.0	1870	48	38.8
11L - 15SL F-2 (TL)	52F318	8	32.0	11.0	8.0	2090	44	52.6
5.50 - 16SL F-2 (TT)	52F239	6	28.0	5.9	4.0	1050	56	18.0
6.00 - 16SL F-2 (TT)	52F275	6	29.1	6.2	4.0	1140	52	19.1
6.00 - 16SL F-2 (TL)	52F375	6	29.1	6.2	4.0	1140	52	20.6
6.50 - 16SL F-2 (TT)	52F281	6	29.8	7.3	4.5	1230	48	21.8
7.50 - 16SL F-2 (TT)	52F283	6	31.8	7.9	5.5	1480	44	27.3
7.50 - 16SL F-2 (TL)	52F384	8	31.8	8.0	5.5	1710	56	33.0
10.00 - 16SL F-2 (TT)	52F298	8	34.9	11.0	8.0	2340	44	52.0
10.00 - 16SL F-2 (TL)	52F398	8	34.9	11.0	8.0	2340	44	56.0
11.00 - 16SL F-2 (TT)	52F295	8	37.8	12.6	10.0	2600	40	65.0
11.00 - 16SL F-2 (TL)	52F395	8	37.8	12.6	10.0	2600	40	74.0
11L - 15SL F-2M (TT)	53F218	8	32.0	10.5	8.0	2090	44	43.3
10.00 - 16SL F-2M (TT)	53F298	8	35.0	10.8	8.0	2340	44	47.0
10.00 - 16SL F-2M (TL)	53F398	8	35.0	10.8	8.0	2340	44	56.0
11.00 - 16SL F-2M (TL)	53F395	8	37.9	12.7	10.0	2600	44	72.0

Front Tractors, Wagons, Balers, Spreaders, Seeders, Irrigation Systems & Feedyard Scrapers

**FARM SPECIALIST® FI Intermittent Highway Service**

Size	Product Code	Ply	MTD Diameter	MTD Width	Rim Width	Max Load Capacity	Max PSI	Tire Weight
9.5L - 15FI (TL)	51H359	D	30.2	9.5	7	2680	60	37.7
9.5L - 15FI (TL)	51H360	E	30.2	9.5	7	3080	75	44.6
10.00 - 15FI (TL)	51H361	D	33.4	11.0	8	3960	60	48.0
11L - 15FI (TL)	51H386	D	30.6	11.0	8	3080	60	45.0
11L - 15FI (TL)	51H392	F	30.6	11.0	8	3960	90	51.0
12.5L - 15FI (TL)	51H3B2	D	32.4	12.5	10	3740	60	59.0
12.5L - 15FI (TL)	51H387	F	32.4	12.5	10	4680	90	66.0
14L - 16.1 FI (TL)	51H362	D	37	14.3	11	4300	45	80.0

FARM SPECIALIST® HF-1 / I-1 Implement

Size	Product Code	Ply	MTD Diameter	MTD Width	Rim Width	Max Load Capacity @30 MPH	Max PSI	Tire Weight
25 x 7.50-15NHS HF-1 (TL)	51F378	6	25.2	7.5	5.5	1230	45	21.6
27 x 9.50-15NHS HF-1 (TL)	51F395	6	27.0	9.0	7.0	1610	45	26.9
31 x 13.50-15NHS HF-1 (TL)	51F397	8	31.8	13.5	10.0	2620	45	50.1
31 x 13.50-15NHS HF-1 (TL)	51F307	10	31.8	13.5	10.0	3080	60	54.5
31 x 13.50-15NHS HF-1 (TL)	570060	12	31.8	13.5	10.0	3520	75	68.0
4.00 - 9 I-1 (TT)	518249	4	17.4	4.8	3.0	550	44	5.0
4.00 - 12 I-1 (TT)	518277	4	20.4	5.0	3.0	675	44	7.0
26 x 12 - 12NHS I-1 (TL)	510361	4	25.5	11.7	10.5	1780	20	25.0
26 x 12 - 12NHS I-1 (TL)	510363	10	25.5	11.7	10.5	3110	52	27.0
26 x 12 - 12NHS I-1 (TL)	560474	12	25.5	11.7	10.5	3520	64	33.0
9.5L - 14SL I-1 (TT)	51F299	8	29.4	9.2	7.0	2400	44	25.6
9.5L - 14SL I-1 (TL)	51F399	8	29.4	9.2	7.0	2400	44	28.5
11L - 14SL I-1 (TL)	51F391	8	29.6	10.6	8.0	2470	36	31.8
5.00 - 15SL I-1 (TT)	51F235	4	25.2	5.4	4.0	950	36	11.9
5.90 - 15SL I-1 (TT)	51F252	4	26.3	6.3	4.5	1140	36	13.4
6.70 - 15SL I-1 (TL)	51F388	6	38.2	7.2	4.5	1610	44	18.0

Front Tractors, Wagons, Balers, Spreaders, Seeders, Irrigation Systems & Feedyard Scrapers

Size	Product Code	Ply	MTD Diameter	MTD Width	Rim Width	Max Load Capacity @ 30 MPH	Max PSI	Tire Weight
7.60 - 15SL I-1 (TL)	51F337	8	28.7	7.9	5.5	2090	52	22.5
9.5L - 15SL I-1 (TT)	51F244	8	29.9	9.2	7.0	2470	44	23.1
9.5L - 15SL I-1 (TL)	51F344	8	29.9	9.2	7.0	2470	44	26.7
9.5L - 15SL I-1 (TL)	51F3D7	12	29.9	9.2	7.0	3000	64	35.0
10.00 - 15SL I-1 (TL)	51F385	8	33.4	11.0	8.0	3200	40	38.0
11L - 15SL I-1 (TT)	51F218	8	30.6	10.7	8.0	2540	36	29.4
11L - 15SL I-1 (TL)	51F318	8	30.6	10.7	8.0	2540	36	33.1
11L - 15SL I-1 (TT)	51F317	12	30.6	10.7	8.0	3200	52	40.0
12.5L - 15SL I-1 (TT)	51F240	8	32.6	12.1	10.0	3000	36	37.8
12.5L - 15SL I-1 (TL)	51F340	8	32.6	12.1	10.0	3000	36	44.8
12.5L - 15SL I-1 (TT)	51F241	10	32.6	12.1	10.0	3420	44	43.0
12.5L - 15SL I-1 (TL)	51F341	10	32.6	12.1	10.0	3420	44	48.3
12.5L - 15SL I-1 (TL)	51F305	12	32.6	12.1	10.0	3860	52	55.0
12.5L - 16SL I-1 (TL)	51F353	14	33.4	12.5	10.0	4780	56	47.1
14L - 16.1SL I-1 (TL)	510131	8	37.0	14.4	11.0	3520	28	76.0
*18L - 16.1SL I-1 (TL)	510130	10	32.5	17.0	14.0	4180	32	77.0

* DIFFERENT RIM TREAD DESIGN

F-3



FARM SPECIALIST® F-3 Industrial Front

Size	Product Code	Ply	MTD Diameter	MTD Width	Rim Width	Max Load Capacity	Max PSI	Tire Weight
11L - 16SL F-3 (TL)	565315	10	33.0	11.0	8.00	2470	52	55.0
11L - 16SL F-3 (TL)	565317	12	33.0	11.0	8.00	2760	64	55.0

R-1



HA-R-1


FARM SPECIALIST® R-1 Multi Angle Long Bar Design

Size	Product Code	Ply	MTD Diameter	MTD Width	Rim Width	Max Load Capacity	Max PSI	Tire Weight
6 - 12 (TL)	570030	6	23.0	6.1	5.00	740	40	16.0
7 - 14 (TL)	570000	6	27.1	7.4	6.00	990	36	27.3
7 - 16 (TL)	570001	6	29.2	7.2	6.00	1100	36	37.0
8 - 16 (TL)	570002	6	31.4	8.9	6.00	1360	28	34.9
9.5 - 16 (TL)	570003	6	33.5	10.0	8.00	1390	30	43.5
8.3 - 24 (TL)	570004	6	39.1	8.3	7.00	1610	34	54.0
9.5 - 24 (TL)	570005	6	41.3	9.5	8.00	1870	30	65.0
11.2 - 24 (TL)	570006	6	43.4	11.2	10.00	2090	26	80.0
12.4 - 24 (TL)	570007	4	45.6	12.4	11.00	1870	16	88.0
12.4 - 24 (TL)	570008	8	45.6	12.4	11.00	2830	32	93.0

FARM SPECIALIST® HA-R-1 Old Style Straight Bar Design

9.5 - 24 (TL)	570034	6	41.3	9.5	8.00	1870	30	60
11.2 - 24 (TL)	570035	6	43.4	11.2	10.00	2090	26	75

TRAC CHIEF® I-3



TRAC CHIEF® I-3

* *With Mud Breakers* Between Shoulder Lugs



TRAC CHIEF® I-3

Size	Product Code	Ply	MTD Diameter	MTD Width	Rim Width	Max Load Capacity	Max PSI	Tire Weight
10.5/80 - 18 (TL)	*570120	10	35.6	10.8	9.00	3840	54	83
12.5/80 - 18 (TL)	*570121	12	38.5	12.5	9.00	4710	45	99
12.4 - 16 (TL)	570122	6	37.2	12.9	11.00	2340	30	80

TURF PRO R-3



MULTI TRAC CS R-3



TURF PRO R-3

Size	Product Code	Ply	MTD Diameter	MTD Width	Rim Width	Max Load Capacity	Max PSI	Tire Weight
13.6 - 16 (TL)	570080	4	38.0	14.2	12.00	1570	14	88
9.5 - 24 (TL)	570084	6	40.3	9.5	8.00	1870	30	52
11.2 - 24 (TL)	570085	6	42.4	11.2	10.00	2080	26	72

MULTI TRAC CS R-3

Size	Product Code	Ply	MTD Diameter	MTD Width	Rim Width	Max Load Capacity	Max PSI	Tire Weight
41 x 14.00 -20 (TL)	570083	4	42.7	14.5	11.00	3080	26	100.0

WHEELS – TRAILER

Boat Trailers, Cargo Trailers, Horse & Stock Trailers, RV- Towable Utility Trailers, & Specialty Trailers

HIGHWAY STANDARD



HIGHWAY SUPREME



HIGHWAY EIGHT SPOKE



HIGHWAY STANDARD

Size	Bolt Pattern	White	Offset	Dia. Pilot Hole	Lugs	Weight	Load Capacity
8 x 3.75	4 on 4	0815443266	0	2.812"	4	4.7	900 @ 90 PSI
8 x 3.75	5 on 4.5	0810923266	0	2.812"	5	4.7	900 @ 90 PSI
8 x 5.375	4 on 4	0815293266	-.75	2.812"	4	5.5	900 @ 90 PSI
8 x 5.375	5 on 4.5	0815295266	-.75	2.812"	5	5.5	900 @ 90 PSI
8 x 7	4 on 4	0815301266	0	2.500"	4	6.5	900 @ 50 PSI
8 x 7	5 on 4.5	0815299266	0	2.812"	5	6.5	900 @ 50 PSI
10 x 6	4 on 4	1015239266	0	2.500"	4	10.6	1330 @ 70 PSI
10 x 6	5 on 4.5	1015240266	0	2.812"	5	10.6	1535 @ 90 PSI

HIGHWAY SUPREME

13 x 4.5	5 on 4.5	1318371564	0	3.300	4	13.0	1480 @ 50 PSI
14 x 6	5 on 4.5	1418221564	0	3.300	5	20.0	1870 @ 50 PSI
15 x 6	5 on 5.5	1518278564	0	4.280	5	22.0	2540 @ 65 PSI
16 x 6	6 on 5.5	1618329564	0	4.280	6	27.0	3200 @ 80 PSI
16 x 6	8 on 6.5	1618330564	0	5.150	8	27.0	3640 @ 80 PSI

HIGHWAY EIGHT SPOKE

12 x 4	4 on 4	1221135564	-1/8"	2.800	4	10.0	1045 @ 90 PSI
12 x 4	5 on 4.5	1221131564	-1/8"	2.800	5	10.0	1045 @ 90 PSI
13 x 4.5	4 on 4	1318077564	-1/8"	2.800	4	13.0	1100 @ 50 PSI
13 x 4.5	5 on 4.5	1321136564	-1/8"	3.300	5	13.0	1480 @ 50 PSI
14 x 6	5 on 4.5	1421137564	0	3.300	5	20.0	1870 @ 50 PSI
15 x 6	5 on 4.5	1521138564	0	3.300	5	22.0	2150 @ 50 PSI
15 x 6	6 on 5.5	1521139564	0	4.280	6	22.0	2540 @ 65 PSI
16 x 6	6 on 5.5	1618326564	0	4.280	6	27.0	3200 @ 80 PSI
16 x 6	8 on 6.5	1618327564	0	5.150	8	27.0	3640 @ 80 PSI

WHEELS



HIGHWAY (DOT) APPROVED TRAILER WHEELS :

Standard, Supreme, Eight Spoke, Star

Our extensive offering of styles and finishes fit all popular tire sizes. These sturdy, reliable wheels are suitable for most trailer applications.

Front Tractors, Wagons, Balers, Spreaders, Seeders, Irrigation Systems & Feedyard Scrapers



IMPLEMENT / AGRICULTURE WHEELS :

Carlisle manufactures a wide selection of the most common low-speed, high capacity agricultural wheels for various wagons, spreaders, seeders and other implement applications.

IMPLEMENT WHEELS

Size	Product Code	Bolt Pattern	Diameter Pilot Hole	Offset	Weight
15 x 6	1519293038	6 on 6	4.62"	+1.12"	23.0
15 x 8	1519294038	6 on 6	4.62"	+1.12"	27.0



SLOW-SPEED & NON-HIGHWAY WHEELS :

Our variety of slow-speed tire and wheel assemblies, non-highway wheels and trailer hubs are the right replacement parts for use with our non-highway tires.

Lawn & Garden, Industrial, ATV, Golf Car, Truck, Passenger, Farm, Grader & Mining Applications



LAWN & GARDEN, INDUSTRIAL, TRAILER

Size	Product Code	Valve	Unit Weight	Units Per Case	Size	Product Code	Valve	Unit Weight	Units Per Case
9 x 3.50 - 4	320030	TR87	0.4	10	300-8	320110	TR13	0.5	10
9 x 3.50 - 4	320031	JS87P	0.4	10	350/400-8	320120	TR13	0.5	10
2.80/2.50 - 4	320050	TR87	0.3	10	3.50/4.00 - 8	320360	TR87	0.5	10
280/250 - 4	320010	JS87P	0.3	10	4.80/4.00 - 8	320400	TR13	0.5	10
4.10/3.50 - 4	320100	TR87	0.4	10	480/400-8	320130	JS87C	0.6	10
410/350 - 4	320040	TR13	0.4	10	5.70/5.00 - 8	320450	TR13	1.0	10
410/350 - 4	320020	JS87P	0.4	10	16 x 6.50/7.50 - 8	320420	TR13	1.0	10
3.40/3.00 - 5	320150	TR87	0.4	10	20x7-8	320140	TR6	1.6	10
4.10/3.50 - 5	320200	TR87	0.6	10	18 x 6.50/8.50/9.50 - 8				
410/350 - 5	320070	TR13	0.5	10	20 x 8.00/10.00 - 8	320410	TR13	1.6	10
410/350 - 5	320060	JS87P	0.5	10	6.90/6.00 - 9	321500	TR13	1.5	10
10/450 - 5	323980	TR87	0.5	10	20 x 8.00/10.00 - 10	320770	TR13	1.8	10
11/400 - 5	320080	TR87	0.5	10	4.80/5.30-12 COMBO	320921	TR13	1.3	10
11/6.00 - 5	323520	TR87	0.6	10	23 x 8.50/9.50/10.50 - 12	321370	TR13	3.3	10
11/710 - 5	323970	TR87	0.7	10	26 x 12 - 12	321050	TR13	3.4	10
4.10/3.50 - 6	320250	TR87	0.5	10					
410/350 - 6	320160	TR13	0.6	10					
13 x 5.00 - 6	320260	TR87	0.6	10					
13 x 5.00 - 6	323790	TR13	0.6	10					
13x650 - 6	320090	TR87	0.6	10					
13x650 - 6	320170	TR13	0.6	10					
5.30/4.50 - 6	320270	TR87	0.6	10					
15 x 6.00 - 6	320290	TR87	0.8	10					
15 x 6.00 - 6	323800	TR13	0.8	10					

TUBES/FLAPS

51

Lawn & Garden, Industrial, ATV, Golf Car, Truck, Passenger, Farm, Grader & Mining Applications

RADIAL ATV				
Size	Product Code	Valve	Unit Weight	Units Per Case
AT21/22 x 11/12R8	320440	TR6	1.6	10
AT25 x 12/13R9	321520	TR6	2.2	10
AT20 x 8/10R10	320771	TR6	1.6	10
AT22/23 x 8R11/12	321371	TR6	3.3	10
AT24/26 x 12R12	321051	TR6	3.4	10
RADIAL PASSENGER				
ER 12/13	322160	TR13	0.9	10
FR 13/14	322010	TR13	1.6	10
FR 15	322170	TR13	1.4	10
GR 13/14/15	322020	TR13	1.8	10
KR 14/15	322030	TR13	2.4	10
MR 14/15	322040	TR13	2.8	10
GR/KR 16	322050	TR13	2.0	10
GR/KR 16	322190	TR15CW	1.8	10
RADIAL LIGHT TRUCK				
7.00/7.50R 15	322070	TR150	2.4	10
7.00/7.50R 15	322230	TR13CW	2.3	10
7.00/7.50R 16	322060	TR150	2.5	10
7.00/7.50R 16	322200	TR13	2.5	10
7.00/7.50R 16	322210	TR440	2.6	10
7.00/7.50R 16	322220	TR15CW	2.5	10
7.00/7.50R 16	322430	TR13CW	2.4	10
7.00/7.50R 17/18	322440	TR440	3.5	10
RADIAL HEAVY TRUCK				
8.25R 20	322080	TR442	4.9	4
9.00R 20	322090	TR443	6.5	4
10.00R 20 12/80R - 20	322100	TR444	7.2	4
11.00R 20 13/80R - 20	322110	TR444	8.4	4
12.00R 20 14/80R - 20	322460	TR444	8.6	4
10.00R 22	322270	TR444	8.1	4
11.00R 22	322280	TR444	8.1	4
HEAVY DUTY BIAS				
10.00 - 20	322330	TR444	6.8	6
RV & WIDE BASE TRUCK BIAS & SKID STEER				
9.50/10 - 16.5LT	322480	TR15CW	3.9	6
12 - 16.5	322490	TR15CW	3.9	6

RV & WIDE BASE TRUCK RADIAL & SKID STEER				
Size	Product Code	Valve	Unit Weight	Units Per Case
10/11R - 15LT	322310	TR13	3.9	6
9.50/10R - 16.5LT	322320	TR150CW	4.0	6
12R - 16.5LT	323990	TR15CW	3.9	6
LOW PLATFORM RADIAL				
7.00/7.50R 15TR	322450	TR440	2.4	6
8.25R 15TR	322240	TR444	3.1	6
9.00/10.00/11.00R 15TR	322250	TR444	3.9	6
MOBILE HOME BIAS				
7/8/9 - 14.5MH	322290	TR300	2.9	6
OTR/CONSTRUCTION/SKID STEER				
8.3/9.5/12.5 - 18/20	322000	TR15CW	3.8	6
13.00/14.00 - 24 TG	322340	TR220A	16.9	1
RADIAL OTR/CONSTRUCTION/SKID STEER				
14R17.5	323111	TR300	5.5	3
15R19.5	323131	TR15CW	7.1	3
13.00/14.00R24 TG	322341	TR220A	16.9	1
17.5R25	323661	TRJ1175C	14.3	1
20.5R25	323671	TRJ1175C	18.7	1
23.5R25	323681	TRJ1175C	25.5	1
HEAVY DUTY INDUSTRIAL LIFT/ FORK TRUCK MINING				
5.70/5.00 - 8	323820	JS2	0.99	36
5.70/5.00 - 8NHS				
4.80/4.00 - 8/9NHS	322410	JS2	0.60	12
7.00 - 12NHS	322420	TR440	2.40	6
6.90/6.00 - 9	323830	JS2	1.50	28
6.50 - 10	323840	JS2	1.76	22
7.50/8.25-15 COMBO	323850	TR440	3.00	14
28 x 9 - 15	323860	TR440	3.00	14
8.25 - 15	323870	TR442	3.40	12
2.50 - 15	323880	TR440	2.47	11
3.00 - 15	323890	TR440	3.53	10
28 x 12 - 15	323900	TR440	3.75	10
32 x 12 - 15	323910	TR440	3.99	10
7.50 - 16	323940	TR440	3.02	14
29 x 8 - 15	323920	TR440	3.00	14

Lawn & Garden, Industrial, ATV, Golf Car, Truck, Passenger, Farm, Grader & Mining Applications

FRONT FARM BIAS

Size	Product Code	Valve	Unit Weight	Units Per Case
4.00/5.90/6.00 - 15SL	322350	TR15	1.4	6
5.50/5.90/6.00/6.40 - 15/16SL	322120	TR15	1.8	6
6.50/7.00/7.50/8.00 - 15/16SL	322360	TR15	2.5	6
10.00 - 15/16SL	322130	TR15CW	4.1	6
11.00 - 16SL	322370	TR15CW	3.9	6
6.50/7.00/7.50 - 18SL	322140	TR15	2.9	6
4.00 - 18/19SL	322380	TR15	1.3	6
8.3/9.5/12.5 - 18/20	322000	TR15CW	3.8	6

REAR FARM RADIAL

Size	Product Code	Valve	Unit Weight	Units Per Case
11.2/12.4R - 24	323960	TR218A	6.7	4
7.5R24SL, 7.5/8.3/9.5R - 24	323601	TR218A	6.6	8
13.6/14.9R - 24	323950	TR218A	10	3
14.9 - 16.9/17.5LR - 24	323760	TR218A	12.8	3
18.4/19.5L/21LR - 24	323770	TR218A	16.3	2
11.2/12.4R - 28, 11.25R28SL	323591	TR218A	8.5	3
13.6/14.9R - 28/30	323750	TR218A	12.1	3
13.6/14.9R - 26/28	324110	TR218A	10.6	3
16.9/18.4R - 26/28	323730	TR218A	14.9	2
14.9R - 30	323741	TR218A	13.2	2
16.9/18.4R - 30	323780	TR218A	16.7	2
11.2R - 34, 11.2/12.4R - 36	323651	TR218A	9.1	3
24.5 R - 32	323742	TR218A	24.8	2
13.6/14.9R - 34	324120	TR218A	12.1	3
16.9/18.4R - 34	323700	TR218A	18.2	2
13.6/14.9 R -36	323621	TR218A	15.4	3
11.2/12.4 R - 38	323631	TR218A	9.1	3
14.9R-36,13.6/14.9/15.5R -38	323720	TR218A	15.4	3
16.9/18.4R - 38	323690	TR218A	19.4	4
20.8R - 38	323710	TR218A	25.3	2
18.4/20.8R - 42	323740	TR218A	20.5	2
16.9/18.4R - 46	323693	TR218A	22.6	2

HD SEVERE SERVICE-REAR FARM RADIAL

16.9/18.4R - 38	323691	TR218A	21.4	2
18.4/20.8R - 42	323692	TR218A	26.0	2
16.9/18.4R - 46	323694	TR218A	25.8	2

FARM IMPLEMENT BIAS

Size	Product Code	Valve	Unit Weight	Units Per Case
8.5/9.5/11L-14 and 8.5/9.5L15	322390	TR13	2.9	6
11L - 15/16SL	322150	TR218A	4.2	6
11L - 15/16SL	322400	TR15CW	3.8	6
12.5 - 15/16SL	322470	TR218A	3.8	6
12.5 - 15/16	323810	TR15CW	3.8	6
13.6/14L-16.1	320032	TR218A	7.2	7
16.5/18.4L-16.1	320033	TR218A	10.1	4
21.5L-16.1	320034	TR218A	12.1	2

RADIAL INDUSTRIAL FLAPS

Size	Product Code	Unit Weight	Units Per Case
8R3.0	05508	0.44	20
8R7.0	12311	1.6	15
9R6.7	11009	0.66	20
10R6.7	12310	0.68	15
12R6.0	12812	0.88	15
15R10.00	19015	3.97	10
16R6.50/7.00/7.50/8.25	17016	2.54	14
15R6.50/7.00/7.50/8.25	17015	2.38	14
20R7.50/8.25	17020	3.42	10
20R8.25	18020	3.53	8
20R9.00/10.00	20520	4.63	7
22R10.00/11.00	20522	5.29	6
20R11.00/12.00	21020	5.84	6
20R13.00/14.00	23020	7.05	4
24R11.1- Off Center	19016	6.9	4
24R11.1- Center	21024	6.9	4

TUBELESS VALVE STEMS

Size	Product Code	Rim Hole Dr (inch)	Length (inch)
TR412	010200000007	0.453	0.88
TR413	010200000005	0.453	1.25
TR600HP*	010200000008	0.453	1.27

Inner Tube Fitment Charts

INNER TUBE FITMENT CHART

Industrial, Fun-Kart, Lawn & Garden Sizes

Size	Product Code	Valve	Also Fits
4.10/3.50 - 4	320100	TR-87	11 x 4.00 - 4
4.10/3.50 - 5	320200	TR-87	11 x 4.00 - 5
13 x 5.00 - 6	320260	TR-87	12 x 5.00 - 6, 14 x 4.50 - 6
5.30/4.50 - 6	320270	TR-87	13 x 6.50 - 6, 14.5/7.00 - 6
18 x 6.50/7.50 - 8	320410	TR-13	18 x 8.50/9.50 - 8, 20 x 8.00/9.00/10.00 - 8
23 x 8.50/9.50 - 12	321370	TR-13	22 x 7.50/9.00 - 12, 23/24 x 10.50 - 12
26 x 12.00 - 12	321050	TR-13	24 x 12.00 - 12, 26 x 10.50 - 12

RADIAL ATV TUBE FITMENT CHART

ATV Tires

Size	Product Code	Valve	Also Fits
AT21/22 x 11/12R8	320440	TR6	18 x 8-8 18 x 8.5/9.5-8 18 x 10/11-8 19 x 8.5/9.5-8 19 x 10/11-8 AT20 x 7-8 AT20 x 10/11-8 AT21 x 10/11R8 AT21 x 12R8 AT22 x 9R8 AT22 x 10R8 AT22 x 11R8 AT22 x 12R8 AT21 x 8R9 AT20 x 7R9 AT22 x 7R9 AT23 x 8R9 AT22 x 11R9
AT25 x 12/13R9	321520	TR6	AT24 x 11R9 AT24 x 12/13R9 24 x 13.5-9 25 x 13.5-9 AT25 x 11R9 AT25 x 12R9 AT24 x 11R10 AT25 x 11R10 AT25 x 12R10 AT26 x 12R10
AT20 x 8/10R10	320771	TR6	AT18 x 10R10 AT18 x 11R10 20 x 7.5-10 AT20 x 8R10 AT20 x 10R10 AT20 x 11R10 AT21 x 7R10 AT22 x 7R10 AT23 x 7R10 AT22 x 8R10 AT22 x 10R10 AT22 x 11R10 22 x 12.5-10 AT23 x 9R10 AT23 x 10R10
AT22/23 x 8R11/12	321371	TR6	AT23 x 8-11 AT24 x 8-11 AT24 x 9-11 23.5 x 8-11 AT23 x 8R12 AT24 x 8R12 AT25 x 8R12 AT23 x 9R12 AT23 x 10R12 AT24 x 10R12 AT25 x 10R12
AT24/26 x 12R12	321051	TR6	AT24 x 12R12 AT25 x 12/13R12 AT25 x 8R11/12 AT26 x 8R11/12 AT27 x 8R11/12 AT26 x 10R12 AT26 x 12R12 AT25 x 11R12 AT26 x 11R11/12 AT27 x 11/12R12

RADIAL LT TUBE FITMENT CHART

LT Tires

700/750R15LT	322230	TR13CW	670R/710R/750R15LT GR/HR/LR15LT LT215/225/235R15LT LT245/70R15LT LT255/70R15LT P215/75R15 P225/75R15 P235/75R15 P245/70R15 P255/70R15
--------------	--------	--------	--

Inner Tube Fitment Charts

INNER TUBE FITMENT CHART (CONT.)

LT Tires

Size	Product Code	Valve	Also Fits		
700/750R15	322070	TR150	670R/710R750R15LT LT215/235/75R15	P235/245/70R15 P255/65R15 P255/60R15	
700/750R16LT	322060	TR150	GR/HR/LR16LT LT215/235/85R16 LT225/245/265/75R16		
700/750R16LT	322200	TR13	LR78-16LT LT225/70R16 LT235/75R16 LT225/85R16 LT235/85R16 LT255/60R17 LT215/235/85R16	LT235/65R16 LT235/70R16 LT245/70R16 LT245/75R16 LT255/70R17 LT235/65R17 P245/75R16	P265/75R16 P215/225/75R16LT P225/70R16 P225/235/85R16 P235/65R16 P235/70R17 P265/70R16
700/750R16LT	322220	TR15CW	GR/HR/LR78-16LT LT215/235/85R16 LT225/85R16 LT235/70R16 LT245/70R16	MR16HD LR78-16LT LT225/70R16 LT235/75R16 LT255/70R16	P215/225/75R16LT 8.25R16LT
7.00/7.50R16LT	322210	TR440			
700/750R16LT	322430	TR13CW	LT215/235/85R16	MR16HD322440	
700/750R17/18	322440	TR440	P265/60R17 LT255/70R17 LT255/60R17	P255/60R17 LT235/65R17	P235/65R17
9.50/10R16.5	322320	TR15CW	31 x 1050R16.5LT	LT265/60D16.5	
12R16.5LT	323990	TR15CW	33 x 12.5R16.5LT	305/70D16.5NHS	305/90D16.5NHS

REAR FARM RADIAL

Size	Product Code	Valve	Also Fits Metric Sizes
11.2/12.4R-24	323960	TR218A	320/85R24
13.6/14.9R-24	323950	TR218A	340/85R24, 380/85R24
14.9-16.9/17.5LR-24	323760	TR218A	460/70R24
18.4/19.5L/21LR-24	323770	TR218A	500/70R24, 540/70R24
13.6/14.9R-28/30	323750	TR218A	340/85R28, 380/85R28, 380/85R30
13.6/14.9R-26/28	324110	TR218A	340/85R28, 380/85R28
16.9/18.4R-26/28	323730	TR218A	480/80R26
14.9R-30	323741	TR218A	380/85R30
16.9/18.4R-30	323780	TR218A	420/90R30, 480/80R30
24.5R-32	323742	TR218A	650/75R-32
13.6/14.9R-34	324120	TR218A	380/85R34
16.9/18.4R-34	323700	TR218A	420/85R34, 480/85R34
11.2/12.4R-38	323631	TR218A	290/90R-38
14.9R-36, 13.6/14.9/ 15.5R-38	323720	TR218A	380/80R38
16.9/18.4R-38	323690/323691	TR218A	480/80R38
20.8R-38	323710	TR218A	520/85R38
18.4R/20.8R-42	323740/323692	TR218A	480/80R42, 520/85R42
16.9/18.4R-46	323693/323694	TR218A	420/80R46, 480/80R46

Inner Tube Fitment Charts

PASSENGER TUBE FITMENT CHART (CONT.)

Passenger/Trailer Tires

Size	Product Code	Valve	Also Fits			
ER 12/13	322160	TR-13	A78-13 135R12 145R12/13 155R12/13 165R13	145/80R12/13 155/80R13 165/70R12/13 155/70R12	185/60R13 195/60R13 AR78-12 BR78-12	5.00-12/13 5.20-12/13 5.50-12 5.60-12/13 6R12SL
FR 13/14	322010	TR-13	A78-13/14 B78-13/14 A70-13 B70-13/14 A60-13/14 B60-13/14 175R13 155R14	165R14 165/80R13/14 175/80R13 155/80R14 165/75R13/14 175/75R13/14 185/75R13 175/70R13/14	185/70R13/14 205/60R13/14 185/60R14 195/60R14 AR78-13/14 BR78-13/14 AR70-13 BR70-13/14	6.00-13/14 6.15-13 6.40-13 6.50-13 6R14SL 7R14SL
FR 15	322170	TR-13	A78-15 B78-15 B70-15 155R15 165R15	175R15 155/80R15 165/80R15 175/75R15 185/70R15	195/60R15 205/60R15 AR78-15 BR78-15 BR70-15	5.00-15 5.50-15 6.00-15
GR 13/14/15	322020	TR-13	C78-13/14/15 D78-13/14/15 E78-14/15 F78-14/15 C70-13/14/15 D70-13/14/15 E70-14/15 F70-14/15 C60-14/15 D60-14/15 E60-14/15 F60-14/15	G60-14 185R13/14/15 195R13/14/15 175R14 185/80R13/14 175/80R14 195/75R13/14/15 185/75R14/15 205/75R14 195/70R13/14/15 205/70R13/14/15 235/6013/14	215/60R14/15 225/60R14/15 245/60R14 CR78-13/14/15 DR78-13/14/15 ER78-14/15 FR78-15 CR70-13/14/15 DR70-13/14/15 ER70-14/15 FR70-14/15 6.70R13/14	7.00R13/14 6.50R14 7.35R14 6.85R15 LT195/75R14 700R14LT 7.9R14LT 26 x 850R14LT 27 x 850R14LT 27 x 750R15LT
KR 14/15	322030	TR-13	G78-14/15 H78-14/15 G70-14/15 H70-14/15 H60-14/15 G60-15 205R14/15 215R14/15	225R15 195/80R15 215/75R14/15 225/75R14 205/75R15 215/70R14/15 225/70R14/15 255/60R14	235/60R15 245/60R15 FR78-14 GR78-14/15 HR78-14/15 GR70-14/15 HR70-14/15 7.50R14/15	7.75R14/15 8.00R14/15 8.25R14/15 8.55R15
MR 14/15	322040	TR-13	J78-14/15 K78-15 L78-15 N78-15 J70-14/15 K70-15 L70-15 J60-14 L60-14/15	M60-14/15 N60-15 225R14 235R15 235/75R14/15 225/75R15 235/70R14/15 245/70R14/15 255/70R15	265/60R14/15 275/60R14/15 255/60R15 JR78-14/15 KR78-15 LR78-15 NR78-15 JR70-14/15 KR70-15	LR70-15 8.50R14 8.85R14/15 9.00R14/15 9.50R14 9.15R15
GR/KR 16	322050	TR-15	F78-16 H78-16 L78-16 LR78-16	FR78-16 HR78-16 JR78-16 6.70R16 7.00R16 7.50R16	5.50R16 6.00R16 6.50R16	7R16SL 8R16SL
GR/KR 16	322190	TR-15CW	F78-16 H78-16 L78-16	FR78-16 HR78-16 LR78-16	8.00R16 8.25R16	

Carlisle Tire & Wheel Company Agricultural Tire

Workmanship & Materials Warranty

Carlisle Tire & Wheel ("CT&W") warrants, subject to the terms, conditions and limitations stated herein, tires to be free from defects in materials and workmanship.

CT&W's liability for tires and wheels shall be limited to replacement of any defective tire or wheel plus applicable taxes.

CARLISLE TIRE & WHEEL COMPANY'S WARRANTY

- This warranty applies to the original consumer of the CT&W product(s) for a period of five (5) years from the date of purchase or from the date of tire manufacture. (Proof of purchase must be provided by consumer if using date of purchase as basis for service time.)
- This warranty **DOES NOT** cover incidental or consequential damages, including, but not limited to, lost time, lost wages, inconvenience, loss of equipment use, cost of service work or transportation, related property damage, personal injury or consequential damages of any type or nature.
- What is warranted?** This warranty applies to CT&W brand Front Farm, Implement, and Rear Tractor Tires, purchased after 06/30/08. (Skid Steer Tires are covered under our Specialty Tire Warranty). If any tire becomes unserviceable due to defective workmanship or materials, (conditions which may be within CT&W's control), CT&W will replace the defective product with an equivalent new CT&W Tire on a pro rata basis.
- This warranty is void if a covered tire is worn past 3/32" of Tread depth at any point on the tread contact surface.
- Any tires submitted for ride condition, issues must be presented by the consumer within the first six (6) months of service if accompanied by Proof of Purchase.
- This warranty **DOES NOT** cover mounting, balancing, or related service/labor charges.
- This warranty **DOES NOT** apply to the following:
 - FIELD HAZARD OR STUBBLE DAMAGE (cuts, snags, punctures, chunk in tread or shoulder area, penetration from foreign objects and stubble related tire damage).
 - Overloading, improper inflation pressure, and/or resulting run flat failures.
 - Misapplication of tire or wheel components.
 - Improper repair or insertion of balancing materials or sealant.
 - Tires damaged due to chemical contamination.
 - Improper mounting or tire storage conditions.
 - Tires used in pulling contests.
 - Cosmetic irregularities or tires marked "NA" (Non-Adjustable)
 - Skid Steer Tires (See Specialty Tire Warranty)
- Warranty Pro Rata Calculations**
All calculations will be based on the date of tire manufacture or the date of purchase. If using date of purchase as basis for service time, the consumer must supply the original proof of purchase.

After the "No Charge" period, pro rata replacement tire charges are calculated as follows:

Service Time	Workmanship and Materials Coverage	
	Replacement Tire Charge to Consumer	
	Agricultural	
Up to 1 Year	No Charge	
During 2nd Year	20% Charge	
During 3rd Year	35% Charge	
During 4th Year	50% Charge	
During 5th Year	70% Charge	

To determine the replacement price to the consumer, the pro rata percentage charge is multiplied by the CT&W Tire dealer's current selling price on an equivalent CT&W Tire. Appropriate taxes, mounting, or other service charges will be added to the replacement price, which is the responsibility of the consumer.

- CT&W makes no express claims of expected tire wear. Variables that effect tire wear include service and soil conditions, as well as load and tire inflation pressures.

To obtain warranty adjustments or warranty information contact your CT&W dealer or call CT&W's Customer Care Unit at 1.800.260.7959 in the USA or 1.800.265.6155 in Canada. Claims must be made within thirty (30) days of discovery of defect.

CT&W reserves the right to inspect all products before making adjustments.

Carlisle Tire & Wheel Company Agricultural Tire

Field Hazard & Stubble Damage Warranty

CARLISLE TIRE & WHEEL COMPANY'S WARRANTY

Although Agricultural Field Hazards and Stubble Damage are **NOT** the result of defects in workmanship and materials, Carlisle Tire & Wheel Company ("CT&W") as elected to share the burden with the original purchaser when excessive Stubble Damage or Field Hazards render a tire unusable.

- Field Hazard- is defined as cuts, snags and punctures incurred during normal agricultural service that may render a tire unserviceable.
- Stubble Damage- is defined as the tire damage caused by severe abrasions and scarring, due to field debris, crop residue, and field stubble, which eventually render the tire unusable

What is warranted? CT&W will extend a Field Hazard and Stubble Damage Policy for CT&W brand R-1, R-2 and R-3 agricultural tires used in normal agricultural service for three (3) years from the date of the purchase or date of the manufacture. (proof of purchase must be provided by the consumer if using date of purchase as basis for service time.)

- What IS NOT** covered by this Field Hazard/Stubble Damage Policy:
 - Improper mounting or tire storage conditions.
 - Misapplication of tire or wheel components.
 - Overloading, improper inflation pressure, and/or resulting run flat failures.
 - Accident, collision, fire or vandalism.
 - Improper repair or insertion of balancing materials or sealant
 - Tires damaged due to chemical contamination.
 - Tires used in pulling contests.
 - Cosmetic irregularities or tires marked "NA" (Non-Adjustable)
- This warranty **DOES NOT** cover incidental or consequential damages, including, but not limited to, lost time, lost wages, inconvenience, loss of equipment use, cost of service work or transportation, related property damage, personal injury or consequential damages of any type or nature.
- Warranty Pro Rata Calculations for Field Hazard/Stubble Damage Coverage
All calculations will be based on the date of tire manufacture or the consumer's date of consumer's purchase. If using date of purchase, the consumer must provide the original proof of purchase.

Pro rata replacement charges are calculated as follows:

Service Time	Field Hazard and Stubble Coverage Replacement Tire Charge to Consumer
Up to 1 Year	25% Charge
During 2nd Year	50% Charge
During 3rd Year	75% Charge
End of 3rd Year	Coverage Expires

To determine the replacement price to the consumer, the pro rata percentage charge is multiplied by the CT&W dealer's current selling price on an equivalent CT&W tire. Appropriate taxes, mounting, or other service charges will be added to the replacement price which is the responsibility of the consumer.

- CT&W makes no express claims of expected tire wear. Variables that effect tire wear include service and soil conditions, as well as load and tire inflation pressures.

To obtain warranty adjustments or warranty information contact your CT&W dealer or call CT&W's Customer Care Unit at 1.800.260.7959 in the USA or 1.800.265.6155 in Canada. Claims must be made within thirty (30) days of discovery of defect.

CT&W reserves the right to inspect all products before making adjustments.

THERE ARE NO REPRESENTATIONS OR WARRANTIES EITHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH EXTEND BEYOND THE DESCRIPTION OF THE WARRANTY STATED ABOVE. CT&W SHALL NOT BE LIABLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES. NO REPRESENTATIVE OF CT&W HAS AUTHORITY TO MAKE ANY REPRESENTATIONS OR PROMISES EXCEPT AS STATED HEREIN.

SPECIALTY TIRE – LIMITED WARRANTY

HIGHWAY/NON-HIGHWAY TIRE & WHEEL WARRANTY

Carlisle Tire & Wheel Company [“**Carlisle**”] warrants, subject to the terms, conditions and limitations stated herein, tires & wheels to be free from defects in materials and workmanship.

Carlisle’s liability for tires and wheels shall be limited to replacement of any defective tire or wheel plus any applicable taxes.

HIGHWAY / NON-HIGHWAY TUBE WARRANTY

Carlisle Tire & Wheel Company [“**CT&W**”] warrants, subject to the terms, conditions and limitations stated herein, its Highway/Non-Highway Tubes (tubes) to be free from defects in materials and workmanship.

CARLISLE’S WARRANTY

- 1. THE CARLISLE TIRE & WHEEL WARRANTY [“Warranty”]** applies only to the original purchaser for two (2) years from the date of purchase.
 - (a) The Warranty period for the coating of the wheel is ninety (90) days from the date of purchase.
2. The Warranty is void if the tire or wheel fails due to damage from improper inflation pressures, exceeding the maximum speed limit, or overloading the tire beyond the maximum load capacity stated on the sidewall.
3. The Warranty does not cover incidental or consequential damages, including, but not limited to, lost time, inconvenience, loss of vehicle use, cost of towing or transportation, related property damage or consequential damages of any type or nature.
4. The Warranty does not cover mounting and balancing charges.
5. The Warranty is void if a covered tire is worn past last 3/32 of tread depth at any point on the tread contact surface.
6. The Warranty **DOES NOT** apply to the following:
 - (a) repaired tubes, tires or wheels
 - (b) tires or wheels used in racing or competition
 - (c) tires or wheels subjected to road hazards, overloading, under-inflation, improper mounting, fitment to incorrect rim, purposeful abuse or chemical contamination
 - (d) tires or wheels which have been patched, plugged or repaired or into which liquid balancers or sealants have been introduced
 - (e) cosmetic irregularities
7. Carlisle makes no expressed claims of expected tire wear. Variables that affect tire wear are driving conditions, load and tire inflation pressure.

To obtain warranty adjustments or warranty information contact your Carlisle dealer or call Carlisle’s Product Service Department at **1-800-260-7959** or fax to **1-800-352-0075**. Claims must be made within 30 days of discovery of defect. Carlisle reserves the right to inspect all products before making adjustments.

THERE ARE NO WARRANTIES EITHER EXPRESSED OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH EXTEND BEYOND THE DESCRIPTION ON THE FACE HEREOF. CARLISLE SHALL NOT BE LIABLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES. NO REPRESENTATIVE OF CARLISLE TIRE & WHEEL COMPANY HAS AUTHORITY TO MAKE ANY REPRESENTATIONS OR PROMISES EXCEPT AS STATED HEREIN.

Some states do not permit limitations on the period of an implied warranty lasts and do not permit the exclusion or limitation of incidental or consequential damages, therefore, the above limitations or exclusions may not apply. This warranty provides specific legal rights. Other rights may vary from state/province to state/province.

CT&W’S WARRANTY

- 1. THE CT&W WARRANTY [“Warranty”]** applies only to the original purchaser of the tubes and only if they are used in the service for which they are intended. Rear tractor tubes are warranted for a period of five (5) years from date of manufacture. All other tubes are warranted for a period of three (3) years from date of manufacture. A covered tube will be warranted in the following manner:
 - (a) replace tube
 - (b) refund cost of tube (proof of purchase required)
2. The Warranty is void if the tube fails due to damage from improper inflation pressures, exceeding or overloading the tube/tire beyond the maximum load capacity stated on the sidewall.
3. The Warranty does not cover incidental or consequential damages, including, but not limited to, lost time, inconvenience, loss of vehicle use, cost of towing or transportation, related property damage or consequential damages of any type or nature.
4. The Warranty does not cover mounting and balancing charges.
5. The Warranty **DOES NOT** apply to the following:
 - (a) repaired tubes
 - (b) tubes used in racing or competition
 - (c) tubes subjected to road hazards (punctures, cuts, stubble damage, impact, valve pulled from tube, etc), overloading, under-inflation, mounting damage, fitment to incorrect rim, purposeful abuse or chemical contamination
 - (d) tubes into which liquid balancers or sealants have been introduced
 - (e) cosmetic irregularities
 - (f) weather checking caused by improper storage

To obtain warranty adjustments or warranty information contact your CT&W dealer or call CT&W’s Product Service Department at **1-800-260-7959** or fax to **1-800-352-0075**. Claims must be made within 30 days of discovery of defect. CT&W reserves the right to inspect all products before making adjustments. THERE ARE NO WARRANTIES EITHER EXPRESSED OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH EXTEND BEYOND THE DESCRIPTION ON THE FACE HEREOF. CT&W SHALL NOT BE LIABLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES. NO REPRESENTATIVE OF CT&W HAS AUTHORITY TO MAKE ANY REPRESENTATIONS OR PROMISES EXCEPT AS STATED HEREIN.

Some states do not permit limitations on the period of an implied warranty lasts and do not permit the exclusion or limitation of incidental or consequential damages, therefore, the above limitations or exclusions may not apply. This warranty provides specific legal rights. Other rights may vary from state/province to state/province.

NOTE: All specifications subject to change without notice.



Carlisle Tire & Wheel Company

23 Windham Boulevard
Aiken, South Carolina 29805
1-800-827-1001

www.carlisletire.com

2009

